

**Dames & Moore**

**Header Sheet**

**Doc ID #**

1007

**"BECHTEL RADIOLOGICAL SURVEY REPORT"**

**1985**

**MANHATTAN PROJECT**

RADIOLOGICAL SURVEY  
OF THE  
E. I. DUPONT DE NEMOURS AND COMPANY  
CHAMBERS WORKS PLANT  
DEEPWATER, NEW JERSEY

MARCH 1985

Prepared for

UNITED STATES DEPARTMENT OF ENERGY  
OAK RIDGE OPERATIONS OFFICE  
Under Contract No. DE-AC05-81OR20722

By

Bechtel National, Inc.  
Advanced Technology Division  
Oak Ridge, Tennessee

Bechtel Job No. 14501

## ABSTRACT

During October and November 1983, a radiological survey was conducted in six separate areas of the DuPont Chambers Works Plant in Deepwater, New Jersey. The survey was performed as part of the Formerly Utilized Sites Remedial Action Program (FUSRAP), a U.S. Department of Energy effort to identify, clean up, or otherwise control sites where low-level radioactive contamination (exceeding current guidelines) remains from the early years of the nation's atomic energy program.

A 1977 radiological survey conducted by Oak Ridge National Laboratory had established that contamination existed at the site. The 1983 survey was necessary to define locations and boundaries of the contamination. The survey was conducted by the FUSRAP Program Management Contractor, Bechtel National, Inc., and its radiological subcontractor, Eberline Analytical Corporation (EAC).

Measurements taken during the 1983 radiological survey indicate that four of the six site areas surveyed are contaminated above current guidelines. In both soil and water samples, the major contaminant was found to be uranium-238. In some areas, contamination was found at depths greater than 3 m (9 ft), and in some cases contamination extended into the water table.

If remedial action were performed at the site, approximately 6300 m<sup>3</sup> (8200 yd<sup>3</sup>) of contaminated materials would require removal to decontaminate exterior areas. One building would require surface decontamination [approximately 50 m<sup>3</sup> (70 yd<sup>3</sup>) of material] or total demolition [approximately 2300 m<sup>3</sup> (3000 yd<sup>3</sup>) of material]. However, in the areas of subsurface contamination, measures currently enforced by DuPont to protect against the site's chemical contaminants are adequate to protect personnel from the low-level radioactive contamination. DuPont does not permit excavation in areas of known chemical contamination and this prohibition extends to low-level radioactive contamination. Additionally, DuPont has positive access controls to the site.

## TABLE OF CONTENTS

	<u>Page</u>
Abbreviations	viii
1.0 Introduction and Summary	1
2.0 Site Description and History	3
2.1 Location and Description	3
2.2 Site History and Previous Radiological Surveys	3
- 2.3 Present Site Conditions	6
3.0 Health and Safety Plan	8
4.0 Survey Procedures	9
4.1 Field Survey Procedures	9
4.1.1 Measurements Taken and Methods Used	9
4.1.2 Sample Collection and Analyses	10
4.2 Building 845 Survey Procedures	18
4.2.1 Measurements Taken and Methods Used	18
4.2.2 Sample Collection and Analyses	22
5.0 Survey Results	23
5.1 Field Survey Results	23
5.1.1 Building 845 Area	24
5.1.2 Central Drainage Ditch	25
5.1.3 F Corral Parking Area	26
5.1.4 Building J-26 Area	27
5.1.5 East Burial Area	27

	<u>Page</u>
5.1.6 Lagoon A	28
5.2 Building 845 Survey Results	26
5.2.1 First Level	29
5.2.2 Second Level	30
5.2.3 Third Level	31
5.2.4 Fourth Level	32
6.0 Significance of Findings	47
6.1 Field Survey	47
6.1.1 Building 845 Area	47
6.1.2 Central Drainage Ditch	49
6.1.3 F Corral Parking Area	49
6.1.4 Building J-26 Area	50
6.1.5 East Burial Area	50
6.1.6 Lagoon A	53
6.2 Building 845 Survey	53
References	64

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
2-1	Location of the DuPont Chambers Works Plant	4
2-2	Aerial Photograph of the DuPont Chambers Works Plant, Looking East	5
4-1	Boreholes and Sampling Locations in the Vicinity of Building 845	11
4-2	Borehole and Sediment Sample Locations, Central Drainage Ditch and Feeder Ditch	14
4-3	Boreholes and Sampling Locations, F Corral Area	15
4-4	Boreholes and Water Sampling Locations, Building J-26 Area	16
4-5	Borehole and Sampling Locations, East East Burial Area	17
4-6	Borehole and Sediment Sampling Locations, Lagoon A	19
4-7	Core Borings and Soil Sample Locations, Building 845 (Ground Floor)	21
6-1	Building 845 Area and Wooden Trough Requiring Remedial Action	48
6-2	F Corral Area Requiring Remedial Action	51
6-3	East Burial Area Requiring Remedial Action	52
6-4	Building 845, First Floor: Areas of Surface Contamination on Floor, Walls, and Floor/Wall Intersections	55
6-5	Building 845, First Floor Ceiling: Areas of Surface Contamination	56
6-6	Building 845, Second Floor: Areas of Contamination on Floor, Walls, and Floor/Wall Intersections	57
6-7	Building 845, Second Floor Ceiling: Areas of Surface Contamination	58
6-8	Building 845, Third Floor: Areas of Surface Contamination on Floor, Walls, and Floor/Wall Intersections	59

<u>Figure</u>	<u>Title</u>	<u>Page</u>
6-9	Building 845, Third Floor Ceiling: Areas of Surface Contamination	60
6-10	Building 845, Fourth Floor, Areas of Surface Contamination on Floor, Walls, and Floor/Wall Intersections	61
6-11	Building 845, Fourth Floor Ceiling: Areas of Surface Contamination	62
6-12	Areas of Contamination Beneath Building 845	63



LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
5-1	Background Radiation Rates and Radionuclide Concentrations in Soil	33
5-2	Radionuclide Concentrations in the Delaware River	34
5-3	Residual Contamination Guidelines and Criteria for FUSRAP Sites	35
5-4	DuPont Chambers Works Site: Pre-Remedial Action Summary of Outdoor Measurement Results	36
5-5	DuPont Chambers-Works Site: Gamma Spectrometry of Soil Samples	37
5-6	DuPont Chambers Works Site: Gamma Spectrometry of Sediment Samples	42
5-7	DuPont Chambers Works Site: Gamma Spectrometry of Water Samples	43
5-8	DuPont Chambers Works Site: Pre-Remedial Action Summary of Building 845 Measurement Results	45

## ABBREVIATIONS

cm	centimeter
cm <sup>2</sup>	square centimeter
cpm	counts per minute
dpm/cm <sup>2</sup>	disintegrations per minute per square centimeter
ft	foot
ha	hectare
l	liter
m	meter
μR/h	microroentgens per hour
mg	milligram
mrads/h	millirads per hour
pCi/g	picocuries per gram
pCi/l	picocuries per liter
yd <sup>3</sup>	cubic yards

## 1.0 INTRODUCTION AND SUMMARY

This report describes the procedures, results, and significance of findings for a radiological survey conducted during October and November 1983 at the DuPont Chambers Works Plant in Deepwater, New Jersey. The survey was conducted as part of the Formerly Utilized Sites Remedial Action Program (FUSRAP). FUSRAP is a U. S. Department of Energy (DOE) program to identify, clean up, or otherwise control sites where low-level radioactive contamination, at levels above current guidelines, remains from the early years of the nation's atomic energy program. Under contract to DOE, Bechtel National, Inc., (BNI) acts as the Program Management Contractor (PMC) for FUSRAP.

An earlier radiological survey, performed in 1977 by Oak Ridge National Laboratory (ORNL), established that contamination existed at the site and resulted in its designation as a FUSRAP site (Ref. 1). The 1983 radiological survey was necessary to define the locations and boundaries of the contamination identified in the ORNL survey, as a prelude to possible remedial action at the site. BNI and its radiological subcontractor, Eberline Analytical Corporation (EAC), conducted the 1983 survey.

Six separate areas were surveyed throughout the site: Building 845 (interior and exterior); Central Drainage Ditch; F Corral Parking Area; Building J-26 Area; East Burial Area and Lagoon A.

Surface and subsurface measurements in the J-26 and Lagoon A areas indicate the areas are not contaminated above guidelines and do not require remedial action. The remaining areas surveyed were contaminated above guidelines. In some areas, subsurface contamination exists at depths greater than 3 m (9 ft). Due to the high water table under the DuPont site, contamination at depths below the water line could not be quantified. The major on-site contaminant was found to be uranium-238, both in water and soil samples.

Groundwater uranium-238 concentrations collected from the F Corral Parking area ranged from background levels to over 105,105 pCi/l. Contamination in soil was found to exist in stratified layers down to the water table.

External-gamma radiation levels ranged from 11.2 to 27.8  $\mu\text{R}/\text{h}$ . These levels are above the normal background level for the DuPont area; however, they are below the DOE guideline of 60  $\mu\text{R}/\text{h}$  above background.

The survey also determined the extent of contamination present in Building 845. The building was surveyed for beta-gamma and alpha contamination; elevated dose rates and above-guideline alpha surface contamination were measured on all four levels of the building. First floor corehole loggings indicated areas of contamination beneath the building up to depths of 1.2 m (4 ft).

If remedial action were to be performed at the site, a total of approximately 6300  $\text{m}^3$  (8200  $\text{yd}^3$ ) of contaminated materials would have to be excavated from the site's exterior areas. In addition, surface decontamination of Building 845 would result in approximately 50  $\text{m}^3$  (70  $\text{yd}^3$ ) of contaminated material. Total demolition of Building 845 would result in approximately 2300  $\text{m}^3$  (3000  $\text{yd}^3$ ) of contaminated material. In areas of subsurface radioactive contamination, measures presently required by DuPont to protect against chemical contaminants are adequate to protect personnel from the low-level radioactive contamination. DuPont does not permit excavation in areas of known chemical contamination and this prohibition extends to low-level radioactive contamination. Additionally, DuPont has positive access controls to the site.

## 2.0 SITE DESCRIPTION AND HISTORY

### 2.1 LOCATION AND DESCRIPTION

The DuPont Chambers Works Plant is an active chemical plant which primarily manufactures organic chemicals. Products include fluorinated hydrocarbons (Freon), petroleum chemicals (tetraalkyl lead), elastomers (Viton and Hytrel), specialty chemicals (Zepel and organic titanates), and aromatics (phenylene diamines). The Chambers Works covers approximately 283 na (700 acres) in Pennsville and Carneys Point townships on the southeast shore of the Delaware River, adjacent to the residential community of Deepwater, New Jersey. The site location is illustrated in Figure 2-1.

The following areas were investigated as part of the site radiological survey: Building 845 interior and exterior areas, F Corral (demolished Building 708, now a parking area), Building J-26 Area, East Burial Area, sections of the Central Drainage Ditch, and Lagoon A. These areas are shown in an aerial photograph of the site presented in Figure 2-2.

### 2.2 SITE HISTORY AND PREVIOUS RADIOLOGICAL SURVEYS

Operations involving uranium at the Chambers Works began in 1942. DuPont was conducting experiments with uranium hexafluoride under contract to the U. S. Office of Scientific Research and Development when the Manhattan Engineer District (MED) was established. As a part of its work on the MED program, DuPont worked on developing a process for converting uranium oxide to produce uranium tetrafluoride and small quantities of uranium metal. Other research activities were also performed.

All MED activities were transferred to the Atomic Energy Commission (AEC) when that agency was created by Congress in 1946. DuPont continued its research activities for AEC until late 1947.




FIGURE 2-1 LOCATION OF THE DUPONT CHAMBERS WORKS PLANT



FIGURE 2-2 AERIAL VIEW OF THE DUPONT SITE

In 1948 and 1949, the AEC conducted radiological surveys and decontamination activities at the site. These activities included sandblasting, vacuuming, and washing building surfaces. Following a radiological survey based on then-existing criteria, AEC released the buildings back to DuPont in 1949.

In March 1977, another radiological survey of the site was conducted by ORNL as part of FUSRAP. The 1977 survey results indicated that elevated concentrations of uranium were present in rubble from the operations building and in some surface and subsurface soil samples. Alpha and beta-gamma contamination levels in some areas of Building 845 were above present federal guidelines (Ref. 1). The 1977 survey concluded that, under current conditions of site use, this contamination does not cause employees working at the site to receive radiation exposures appreciably different from those due to background radiation. However, under different conditions of use (e.g., actions which involved agitation or abrasion of dry contaminated surfaces), the potential for low-level radiation exposures to employees and the public could result.

Based on the 1977 survey results, the DOE Assistant Secretary for Environment determined that the DuPont site warranted remedial action under FUSRAP. In its role as PMC for FUSRAP, BNI conducted the 1983 survey to more accurately define the boundaries and depth of contamination at the site.

### 2.3 PRESENT SITE CONDITIONS

Of the three buildings used for MED activities, only Building 845 remains. Building 845 is presently used as a miscellaneous stores warehouse. The other two buildings were demolished from 1945 to 1953.

In 1945, part of Building 708 was demolished and removed from the site. In 1953, the remainder of Building 708 was removed along with several feet of underlying earth. Materials removed in 1953 were



disposed of in the Lagoon A area (Ref. 2). A parking facility, F Corral, is now located on the location of Building 708.

Following release of the site by the AEC in 1949, Building J-16 was demolished and disposed of in the Lagoon A area (Ref. 2). A new building, J-26, now stands at this location.

The East Burial Area contains some equipment from the demolition of Building 845. In addition, various chemical wastes and small amounts of New Jersey-approved low-level radioactive material have been stored in this area.

The Central Drainage Ditch is in approximately the same location as in the 1940s. The primary purpose of the ditch is to carry residual wastes from chemical operations. In the past, residual wastes from Building 845 were discharged into a wooden trough located east of the building. The trough dumped into the Central Drainage Ditch approximately 150 feet north of Building 845. The Central Drainage Ditch flows toward the northeast, adjacent to the northwest corner of Building 845, and drains out into the eastern corner of Lagoon A. The composite from Lagoon A is then pumped into the on-site water treatment facility for chemical processing of the waste.

### 3.0 HEALTH AND SAFETY PLAN

The presence of various chemicals used and manufactured at the site posed potential health hazards to employees involved in the sampling and handling of subsurface soil and water samples. These conditions necessitated the use of special measures to protect employees involved with the subsurface investigations and a Health and Safety Plan was designed by BNI.

The primary components of the Health and Safety Plan were: pre-work medical examinations; safety education in handling and sampling precautions; personal protective equipment consisting of gloves, shoe covers, disposable coveralls, eye protection, hard hats, and butyl-rubber air-supplied suits; urine sampling; and follow-up medical examinations performed upon completion of the survey. Controls required for chemical protection were reviewed and approved by DuPont. All drilling and soil sampling in the Central Drainage Ditch, Lagoon A, and East Burial Area, under direction from DuPont, were carried out with drillers and support personnel attired in one-piece, air-supplied butyl-rubber suits. In addition, two 30-minute self-contained breathing apparatus air cylinders were used during the sediment sampling conducted west and northwest of Building 845 along secondary drainage ditches.

During the radiological survey, the FUSRAP BNI Safety Supervisor was present and supervised operations. There were no recorded illnesses or injuries involving any person working on this survey. Medical examinations given at the conclusion of the survey showed no evidence of personnel having been exposed to hazardous chemicals.

## 4.0 SURVEY PROCEDURES

### 4.1 FIELD SURVEY PROCEDURES

The survey grid system for the site, exclusive of the grid for the interior of Building 845, was established by a civil surveyor during October 1983 and was based on the New Jersey state geological survey. The areas surveyed on a 15-m (50-ft) grid included Lagoon A, East Burial Area, Central Drainage Ditch, F Corral parking lot, areas around Building J-26, and areas around Building 845. The radiological measurements taken and the methods used for taking the measurements are described in the following subsections.

#### 4.1.1 Measurements Taken and Methods Used

Within the grid blocks of all field areas, beta-gamma measurements were made on the ground surfaces at 6-m (20-ft) intervals. The measurements were made using a pancake geometry (Geiger-Mueller) probe coupled to a digital ratemeter/scaler [Eberline Instrument Corporation (EIC) models HP-210 and PRS-1, respectively].

Near-surface gamma measurements were made 30 cm (12 in.) above the ground surface at 6-m (20-ft) intervals within the grid using a 5- x 5-cm (2- x 2-in.) sodium-iodide (NaI) detector. This detector (EIC model SPA-3) was mounted in a probe assembly surrounded with a conical lead shield to reduce the gamma intensity through the sides, thus producing a downward directional response.

Gamma exposure rates at 1 m (3 ft) above the ground were measured using a pressurized ionization chamber (PIC) with a response to gamma radiation that is proportional to exposure in roentgens. Readings were made at 15-m (50-ft) intervals above all open area surfaces in all gridded areas (gamma exposure rate measurements were not taken in the J-26 area).

Boreholes 15 cm (6 in.) in diameter were drilled in all areas. Material from the boreholes was returned to the holes. Drilling was conducted in accordance with safety precautions described in Section 3.0. The locations and number of holes in each area were based on near-surface gamma measurements made in the area and the historical data on the site. A section of 10-cm (4-in.) diameter PVC plastic pipe with a closed bottom was inserted into each hole as a temporary sleeve to allow gamma logging. A 5- x 5-cm (2- x 2-in.) NaI (Tl) gamma scintillation detector (SPA-3 NaI crystal in a modified probe used specifically for borehole logging), coupled with a PRS-1 ratemeter/scaler, was lowered into the pipe to obtain a profile of the depth of contamination. Timed gamma measurements were made at 15-cm (6-in.) vertical intervals. By calibrating these measurements with the results from laboratory analyses of soil samples, borehole loggings provide a reliable estimate of radionuclide concentrations in subsurface soils.

#### 4.1.2 Sample Collection and Analyses

##### Building 845 (Exterior) Area

In the area surrounding Building 845, in addition to the boreholes drilled for gamma logging, undisturbed (Shelby tube) soil samples, water samples, and sediment samples were taken. The locations of the boreholes and of each type of sample taken are illustrated in Figure 4-1. In some cases, more than one type of sample was taken at the same location.

Based on the gamma logs, four Shelby tube soil samples were taken in areas which had revealed the most significant subsurface deposits of radioactivity. The soil samples extended to 30 cm (1 ft) below the depth of the radionuclide deposits as indicated by the gamma logging. Shelby tubes, 61 cm long and 7.6 cm in diameter (24 x 3 in.) were used to collect these soil samples. The soil in the tubes was extruded in 10-cm (4-in.) sections, placed in 500-ml plastic containers, identified, and packaged. The samples were




FIGURE 4-1 BOREHOLES AND SAMPLING LOCATIONS IN THE VICINITY OF BUILDING 845

shipped to DOE's Niagara Falls Storage Site where they were dried, pulverized, and homogenized before they were analyzed for uranium-238. The samples were analyzed by EAC personnel using the high resolution gamma spectrometry system in the FUSRAP in situ van (Ref. 3). Each sample was analyzed for 10 minutes using an intrinsic germanium detector housed in a lead counting cave lined with cadmium and copper. The detector is coupled to a computer base pulse height analyzer. Following the initial gamma spectrometry analysis of the soil samples, aliquots of selected samples were taken and sent to the EAC laboratory in Albuquerque, New Mexico, for radiochemical analysis. This analysis was performed to measure the concentrations of uranium-234 and uranium-235 in the samples and also to verify the uranium-238 analysis.

Water samples also were collected from all boreholes in the Building 845 area whenever the water table was reached. Water table depth proved to vary from 1 to 1.3 m (3 to 4 ft). Water samples were collected in 1-liter plastic sample bottles, clearly marked, and identified. (Chemical contamination of the water samples was evident through both odor and consistency of the liquid. For handling precautions, analytical laboratory personnel were advised of the possibility of chemical contamination.) All water samples collected were shipped to the EAC Albuquerque laboratory for analysis for uranium-234, uranium-235, and uranium-238 by radiochemical techniques.

Ten sediment samples were collected at 15-m (50-ft) intervals in the wooden drainage trough east of Building 845. Prior to analysis, all samples were heated on-site in an oven (at the in situ van) to 600°C (1112°F) to remove organics and eliminate possible chemical exposures during handling. Sediment samples then were analyzed using the same methods used for soil samples.

#### Central Drainage Ditch

Ten sediment samples were collected from the Central Drainage Ditch between grid location N4700-2485 and N5150-E3220. Sediment sampling

locations are shown in Figure 4-2. Sediment samples were collected primarily utilizing foot and traffic bridges and in areas of the ditch that were accessible during drilling operations.

Four sediment samples were collected at 15-m (50-ft) intervals from the Feeder Ditch. All sediment samples taken were heated to 600°C (1112°F) to remove organics and to eliminate possible chemical exposures during handling. Samples were then analyzed for radioactivity by the same methods used for soil samples.

#### F Corral Parking Area

Two Shelby tube soil samples were collected in the F Corral parking area. Samples were collected and analyzed in the same manner as described earlier. Water samples also were collected from boreholes in the F Corral when applicable. Water was collected and analyzed as described earlier. Sampling locations are shown in Figure 4-3.

#### Building J-26 Area (Formerly J-16)

Water samples were collected from boreholes, when possible, in the Building J-26 area. Boreholes and water sample locations are shown in Figure 4-4.

#### East Burial Area

In the East Burial Area, two locations were selected for Shelby tube soil samples. These samples were taken in the immediate vicinity of the two boreholes which revealed the most significant subsurface deposits of radioactivity. Water samples also were collected from boreholes when possible. Sampling locations are shown in Figure 4-5.




FIGURE 4-2 BOREHOLE AND SEDIMENT SAMPLE LOCATIONS, CENTRAL DRAINAGE DITCH AND FEEDER DITCH






FIGURE 4-3 BOREHOLES AND SAMPLING LOCATIONS, F CORRAL AREA




FIGURE 4-4 BOREHOLES AND WATER SAMPLING LOCATIONS, BUILDING J-26 AREA




FIGURE 4-5 BOREHOLE AND SAMPLING LOCATIONS, EAST BURIAL AREA

## Lagoon A

Two sediment samples were taken from Lagoon A and were processed using the same method used on the sediment samples taken from central drainage ditch. Sampling locations are shown in Figure 4-6.

### 4.2 BUILDING 845 SURVEY PROCEDURES

The grid system used for Building 845 consisted of a 1.8- x 1.8-m (6- x 6-ft) grid established on the walls, floors, and ceilings. Building 845 presently has four floors. During early plant operation this was not the case. The building contained equipment that reached from the ground floor to the upper parts of the building, and upper floors were only partial -- to varying extents. The present upper floors contain original flooring and recently added "new" flooring. For the purposes of this radiological survey, each floor of Building 845 was gridded independently and random measurements were made on the new floor areas to verify that these areas were not contaminated.

#### 4.2.1 Measurements Taken and Methods Used

The surface of each floor of Building 845 was monitored for beta-gamma radiation, with a total of five measurements made in each grid segment on the original floor areas and random measurements made on the new floor areas. Measurements were made with a thin window ( $7 \text{ mg/cm}^2$ ) Geiger-Mueller detector with digital readout (EIC model HP-210/PRS-1). The HP-210 detector was in contact with floor surfaces. Five 30-second counts were obtained and recorded in each grid block. Measurements were made along the floor/wall intersection and along new and old floor joints at 3-ft intervals.

Wall surface measurements were obtained in the same manner as floor surface measurements. A 1.8-m (6-ft) grid was used from the floor to a height of 1.8 m (6 ft) above the floor. For upper walls the




FIGURE 4-6 BOREHOLE AND SEDIMENT SAMPLING LOCATIONS, LAGOON A

grid was increased to 5 m (16 ft). All horizontal surfaces, such as window sills, also were scanned and radiation levels were recorded. All wall measurements are referenced to the floor grid numbering system.

Ceilings were monitored in the same manner as floors and walls. Measurement points were selected on horizontal and vertical surfaces such as beams, pipes, and ledges in each building unit (rooms, halls). All ceiling measurements were referenced to the floor grid numbering system.

Alpha radiation measurements were made at the same locations as beta-gamma measurements, using a 59-cm<sup>2</sup> zinc sulfide (ZnS) scintillation detector with digital readout (EIC models AC-3/PRS-1).

Based on results of the 1977 ORNL survey and surface beta-gamma measurements conducted during the 1983 building survey, 27 locations were identified for coring through the ground floor concrete slab. Locations are illustrated in Figure 4-7. Typical cores indicated the concrete slab was 10 to 15 cm (4 to 6 in.) thick, with a spread foundation footing 15 to 45 cm (6 to 18 in.) deep under columns.

A sealed drain trench was located in core boring number 4 (CB-4) and CB-6. The trench extended approximately 11 m (35 ft) south of CB-6 and was an average 45 cm (1.5 ft) deep. In CB-6, a 7.5-cm (3-in.) diameter steel drain pipe was located in the sealed trench at a depth of 22 to 30 cm (9 to 12 in.). This pipe contained elevated levels of radiological contamination in a dry, yellow powder form.

Augering techniques inside the building varied from methods used in the exterior areas of the plant due to limited overhead clearances. A 15-cm (6-in.) diameter hand auger was used to remove soil in 10-cm (4-in.) increments, allowing sufficient clearance for insertion of the PVC pipe for downhole gamma logging.




FIGURE 4-7 CORE BORINGS AND SOIL SAMPLE LOCATIONS, BUILDING 845 (GROUND FLOOR)

#### 4.2.2 Sample Collection and Analysis

Shelby tube soil samples were collected inside Building 845 near all core boring locations. These samples were collected and analyzed using the same methods described in Subsection 4.1.2 of this report. Water samples also were taken from the borings when possible and processed as noted in Subsection 4.1.2.

During this radiological survey, four particulate air samplers (EIC Model RAS-1) were employed. These samplers, one on each floor, ran continuously and sampling filters were exchanged daily. Composite samples for each location were sent to the NFSS, where they were analyzed for gross alpha and beta-gamma.

Two composite dust samples also were collected from the first and fourth floors of Building 845. These samples were analyzed for uranium-238 and radium-226 at the EAC Albuquerque Laboratory.



## 5.0 SURVEY RESULTS

### 5.1 FIELD SURVEY RESULTS

All direct field measurements and laboratory results in this report represent gross readings; background measurements and concentrations have not been subtracted.

Background measurements were made in 1977 as part of the ORNL survey. At six locations on the DuPont property, at distances ranging from 300 to 1800 m (1000 to 6000 ft) from the nearest area in which radioactive materials were handled or stored, surface soil samples were taken to determine radionuclide concentrations. Concentrations of uranium-238 in the background soil samples ranged from 0.3 to 4.0 pCi/g and averaged 1.8 pCi/g.

External gamma measurements 1 m (3 ft) above the ground were made at the same six points. Background external gamma readings ranged from 3 to 6  $\mu\text{R}/\text{h}$  and averaged 4.5  $\mu\text{R}/\text{h}$  (Ref. 1). Background radiation rates and radionuclide concentrations in soil are summarized in Table 5-1, at the end of Section 5.0.

In addition to these background data, a series of additional external gamma exposure rate measurements were made throughout the state of New Jersey. The average statewide measurement was 6.1  $\mu\text{R}/\text{h}$  (Ref. 4).

During the 1977 ORNL survey, three river water samples, which were assumed to represent background concentrations, were collected from the Delaware River. The results of these samples are presented in Table 5-2.

Background near-surface gamma measurements for the DuPont site were made during the 1983 BNI survey using an EIC SPA-3 detector. These measurements showed the site's near-surface gamma reading to be 2500 cpm.

Current DOE guidelines for radionuclide concentrations in soil, sediment and water are presented in Table 5-3.

In all field areas, measurements were taken for near-surface gamma, surface beta-gamma, and gamma exposure rates 1 m (3 ft) above the ground (gamma exposure rates were not measured in the J-26 area). Boreholes were drilled and gamma logging was performed, and undisturbed (Shelby tube) soil samples, water samples, and sediment samples were taken in each area as appropriate.

The results of near-surface gamma, surface beta-gamma, and gamma exposure rates are summarized in the following subsections. A summary table, Table 5-4, is presented at the end of Section 5.0. Analysis results for soil, sediment, and water samples also are summarized in the following sections, with specific results reported in Tables 5-5 (soil), 5-6 (sediment), and 5-7 (water) at the end of Section 5.0.

#### 5.1.1 Building 845 Area

Near-surface gamma readings taken in the Building 845 area ranged from 1770 to 12,246 cpm. Only four surface areas east of Building 845 exhibited readings greater than twice background. All beta-gamma measurements were below the DOE guideline of 0.20 mrad/h dose rate averaged over one square meter.

Gamma exposure rates in the area ranged from 11.6 to 27.8  $\mu\text{R}/\text{h}$ . As noted earlier, the overall site background rate measured by ORNL is 4.5  $\mu\text{R}/\text{h}$ . The DOE criteria for continuous exposure to an individual in the general population is 60  $\mu\text{R}/\text{h}$  above background.

Twenty-five boreholes, ranging in depth from 1.4 to 2.8 m (4.5 to 9 ft) were drilled in the area around Building 845. Borehole gamma logging then was performed to indicate general depth and concentrations of contamination. When possible, the borehole gamma loggings were correlated with undisturbed (Shelby tube) soil samples

analyses, relating the gamma detector's cpm response to the specific radionuclide concentration in picocuries per gram (pCi/g).

Due to the high water table encountered under the DuPont site, in many instances soil samples could not be collected. However, four Shelby tube soil samples were taken in the area east of Building 845 (refer to Figure 4-1). Specific analysis results are presented in Table 5-5, which lists the samples by coordinates and depth. The results indicate uranium is the major contaminant in the Building 845 exterior area, with levels ranging from 0.63 to 7398.0 pCi/g. The DOE remedial action guideline for uranium is 150 pCi/g.

Ten sediment samples were collected from the drainage trough located east of Building 845. Sampling locations are shown in Figure 4-1. All samples were analyzed for uranium-238, and concentrations ranged from 1.9 to 255.6 pCi/g. Selected samples also were analyzed for uranium-234, uranium-235, thorium-232, and radium-226. Results are given in Table 5-6. All results were below the DOE guidelines for these radionuclides (Ref. 5).

Twenty-one water samples were collected from boreholes in the area around Building 845. These samples were analyzed for total uranium. Results, given in Table 5-7, range from 1.5 to 11,712.0 pCi/l.

#### 5.1.2 Central Drainage Ditch

Near-surface gamma measurements and beta-gamma measurements were made along both sides of the Central Drainage Ditch and the Feeder Ditch. Near-surface gamma readings ranged from 1806 to 14,532 cpm. Three measurements taken in the southwest portion of the Feeder Ditch had readings greater than twice background. All beta-gamma dose rates were below the DOE guideline.

Gamma exposure rates in the area of the Central Drainage Ditch ranged from 12.8 to 15.4  $\mu$ R/n. These measurements are elevated above natural background but are below the DOE guideline of 60  $\mu$ R/h.

Eleven boreholes were drilled 1.8 to 2.6 m (6 to 8.5 ft) deep along the sides of the Central Drainage Ditch (refer to Figure 4-2). Boreholes were gamma logged, and elevated measurements were detected along both sides of the ditch. All measurements were below but near the guideline limit.

Sediment samples were collected from 10 locations in the Central Drainage Ditch and 4 locations in the Feeder Ditch. These samples were analyzed for uranium-234, -235, and -238. Results ranged from 0.90 to 4.10 pCi/g for uranium-238, 1.20 to 1.90 pCi/g for uranium-234, and 0.04 to 0.15 pCi/g for uranium-235. Complete results are given in Table 5-6. All results were below the DOE guidelines.

### 5.1.3 F Corral Parking Area

Near-surface gamma measurements and beta-gamma measurements were made in the F Corral parking area at 6-m (20-ft) intervals.

Near-surface gamma readings ranged from 1608 to 5020 cpm. All beta-gamma dose rates were below the DOE guideline. Gamma exposure rates in the F Corral parking area ranged from 11.6 to 13.8  $\mu$ R/h.

Nineteen boreholes ranging from 0.6 to 2.7 m (2 to 9 ft) in depth were drilled in the F Corral area (refer to Figure 4-3). Based on gamma logs, subsurface contamination is indicated in layers to a depth greater than 2.7 m (9 ft).

Two Shelby tube soil samples were collected from the F Corral, and sample results are given in Table 5-5 by depth and coordinate. Uranium-238 was the major contaminant found in the parking area, with concentrations ranging from 0.90 to 4347 pCi/g.

Eleven water samples were collected from boreholes located in the F Corral. These samples were analyzed for total uranium. Results, given in Table 5-7, ranged from 1.50 to 105,105 pCi/l.

#### 5.1.4 Building J-26 Area

In the Building J-26 area, near-surface gamma measurements ranged from 1568 to 4334 cpm. Beta-gamma dose rates were below the DOE guideline.

Six boreholes were drilled in the area around Building J-26 (refer to Figure 4-4), and one water sample was collected. The total uranium concentration of the sample was 13.51 pCi/l. Analysis results are given in Table 5-7.

#### 5.1.5 East Burial Area

Near-surface gamma readings in the East Burial area ranged from 1212 to 17,878 cpm. Three measurements exceeded normal background levels. All beta-gamma dose rates were below the DOE guideline. Gamma exposure rates in the East Burial area ranged from 12.2 to 15.0  $\mu$ R/h.

Twenty boreholes were drilled in the East Burial area (refer to Figure 4-5). Gamma loggings indicate contamination exists in layers to depths greater than 2.6 m (8.5 ft). Higher count rates were observed in the boreholes drilled adjacent to the road.

Two Snelby tube soil samples were collected in the East Burial area, and samples were analyzed for uranium-238, thorium-232, and radium-226. Uranium-238 was the major contaminant found, with concentrations ranging from 297 to 20,810 pCi/g. Both sampling locations also showed concentrations of radium-226 above the DOE guideline, with concentrations ranging from 0.19 to 27.8 pCi/g. All thorium-232 concentrations were below the DOE guideline. Complete results are given in Table 5-5. Due to the high water table, subsurface soil samples could not be collected below 1 m (3 ft).

Groundwater samples were collected from two locations at a depth of 90 cm (36 in.). Water samples were analyzed for total uranium. Both samples had uranium-238 concentrations below the DOE guideline.

#### 5.1.6 Lagoon A

In the Lagoon A area, near-surface gamma measurements ranged from 1566 to 3436 cpm. All beta-gamma dose rates were below the DOE guideline. Gamma exposure rates ranged from 11.2 to 15.8 uR/h.

Ten boreholes were drilled in the Lagoon A area (refer to Figure 4-6). Gamma loggings exhibited readings above background but below the guideline.

A surface water sample was collected from Lagoon A. The total uranium concentration in the sample was 4.20 pCi/l. Results are given in Table 5-7.

#### 5.2 BUILDING 845 SURVEY RESULTS

All building survey measurements in this report represent gross readings; background measurements have not been subtracted. Beta-gamma dose-rate measurements taken on the DuPont site in buildings that have not been contaminated with radioactive materials were less than 0.03 mrad/h (Ref. 1). DOE guidelines for the release of property for unrestricted use state that beta-gamma dose rates at 1 cm from the surface shall not exceed 0.2 mrad/h (averaged over one square meter) and 1.0 mrad/h maximum in an area not greater than 100 cm<sup>2</sup> (Ref. 5). The guidelines also state that alpha surface contamination levels shall not exceed 1000 dpm/100 cm<sup>2</sup> average and 3000 dpm/100 cm<sup>2</sup> maximum when natural uranium is known to be the contaminant.

Results of measurements for beta-gamma dose rates and alpha contamination taken in Building 845 are summarized in the following subsections. More detailed results are presented in summary form in Table 5-8. Results for soil and water samples are summarized in the following sections, with specific results reported in Tables 5-5 (soil) and 5-7 (water).

While work was being performed inside Building 845, air particulate samples were taken. All results were within the DOE guideline for gross alpha of  $0.1 \text{ pCi/m}^3$  (for uncontrolled areas) (Ref. 6).

#### 5.2.1 First Level

A total of five measurements were made for beta-gamma and alpha contamination in each floor grid block. Average and maximum values per grid block are recorded in this report. The floor beta-gamma dose rates per grid block ranged from 0 to 4.54 mrad/h. Alpha measurement averages ranged from 0 to 6819 dpm/100  $\text{cm}^2$ , with a maximum reading of 26,544 dpm/100  $\text{cm}^2$ .

Floor/wall intersections were surveyed in 1-m (3-ft) increments for beta-gamma and alpha contamination. Beta-gamma dose rate averages ranged from 0 to 6.05 mrad/h, with a maximum reading of 3.88 mrad/h. Alpha measurement averages ranged from 0 to 10,621 dpm/100  $\text{cm}^2$ , with a maximum reading of 18,041 dpm/100  $\text{cm}^2$ .

Beta-gamma dose rates measured on the ceiling ranged from 0 to 4.78 mrad/h. Alpha measurements ranged from 0 to 5568 dpm/100  $\text{cm}^2$ . Beta-gamma and alpha measurement results are summarized in Table 5-8.

Twenty-seven coreholes were drilled through the first floor of Building 845. Locations are shown in Figure 4-7. In several locations, the auger hit the spread footings of the building's foundation. Thus, the corehole depths ranged from 0.5 to 2 m (1.5 to 6.0 ft). Eighteen boreholes indicated elevated gamma readings.

Soil samples were collected at all corehole locations and were analyzed for uranium-238, thorium-232, and radium-226. The major contaminant was uranium-238, with concentrations ranging from 0.70 to 8334 pCi/g. Thorium-232 and radium-226 concentrations were below the DOE criteria limit. Several samples were selected for uranium-234 and uranium-235 analysis, and concentrations were below guidelines. Results are given in Table 5-5.

One water sample was collected from CB-13 at a depth of 105 cm (42 in.), and the sample was analyzed for total uranium. The analysis results given in Table 5-7 indicate 7508 pCi/l of total uranium.

During building coring operations, two coreholes were drilled into the drainage trench used during MED operations. Two soil samples were collected from the drain and analyzed for uranium-238, thorium-232, and radium-226. All analysis results were below DOE guideline.

The building's elevator shaft could not be surveyed because of flooding conditions in the shaft. During the ORNL survey, the walls of the shaft were surveyed and one sediment sample was taken and analyzed. The sediment sample showed radium-226 concentrations above guideline (35 pCi/g), while all surface readings were below guidelines (Ref. 1).

Two composite dust samples were collected from first floor beams and horizontal surfaces. Both samples were analyzed by gamma spectrometry for uranium-238, and one sample was analyzed for radium-226. Uranium results ranged from 489 to 1625 pCi/g. The radium-226 result was 2.8 pCi/g. These results can be compared with surface-soil guidelines for uranium-238 and radium-226 of 150 pCi/g and 5 pCi/g above background, respectively.

#### 5.2.2 Second Level

Beta-gamma and alpha measurements were taken on the old floor area of the second level. The new floor area was spot checked for contamination. Beta-gamma dose rate averages ranged from 0 to 2.85 mrad/h, with a maximum reading of 3.45 mrad/h. Alpha measurement averages ranged from 0 to 264 dpm/100 cm<sup>2</sup>, with a maximum reading of 584 dpm/100 cm<sup>2</sup>.



Beta-gamma and alpha measurements also were made on accessible lower wall areas during the survey. Beta-gamma dose rates ranged from 0.05 to 10.92 mrad/h. Alpha measurements ranged from 0 to 9068 dpm/100 cm<sup>2</sup>.

Floor/wall intersections and the new floor/old floor intersections also were also surveyed. Beta-gamma dose rate averages ranged from 0.01 to 2.16 mrad/h, with a maximum reading of 2.77 mrad/h. All alpha measurements were below the guideline.

On the ceiling, beta-gamma dose rates ranged from 0.02 to 4.87 mrad/h. Alpha measurements ranged from 8 to 3992 dpm/100 cm<sup>2</sup>.

Results of second level readings are summarized in Table 5-8.

### 5.2.3 Third Level

Beta-gamma and alpha measurements were taken on the old floor areas of the third level, and new floor areas were spot checked for contamination. Beta-gamma dose-rate averages ranged from 0 to 1.40 mrad/h, with a maximum reading of 2.38 mrad/h. Alpha measurement averages ranged from 0 to 1017 dpm/100 cm<sup>2</sup>.

On the lower walls, beta-gamma dose rate averages ranged from 0.08 to 2.84 mrad/h, with a maximum reading of 2.84 mrad/h. Alpha measurements ranged from 37 to 3076 dpm/100 cm<sup>2</sup>.

At floor/wall intersections and new floor/old floor intersections, beta-gamma dose rates ranged from 0 to 0.68 mrad/h, with a maximum reading of 0.98 mrad/h. Alpha measurements ranged from 0 to 1930 dpm/100 cm<sup>2</sup>, with a maximum reading of 2599 dpm/100 cm<sup>2</sup>.

On the third level ceiling, beta-gamma dose rate measurements ranged from 0.02 to 1.49 mrad/h, with a maximum reading of 7.05 mrad/h. Alpha measurement averages ranged from 8 to 1347 dpm/100 cm<sup>2</sup>.

Beta-gamma and alpha measurement results for the third level are summarized in Table 5-8.

#### 5.2.4 Fourth Level

On the old floor area of the fourth level, beta-gamma dose rate averages ranged from 0 to 1.0 mrad/h, with a maximum reading of 1.76 mrad/h. Alpha measurement averages ranged from 0 to 885 dpm/100 cm<sup>2</sup>, with a maximum reading of 2561 dpm/100 cm<sup>2</sup>.

On all accessible lower wall areas, beta-gamma dose rates ranged from 0.03 to 3.39 mrad/h. Alpha measurements ranged from 0 to 3487 dpm/100 cm<sup>2</sup>.

On the ceiling, beta-gamma dose rates ranged from 0.05 to 4.34 mrad/h. Alpha measurement averages ranged from 76 to 2703 dpm/100 cm<sup>2</sup>.

Beta-gamma and alpha measurement results for the fourth level are summarized in Table 5-8.

The fourth level ceiling heaters also were monitored for beta-gamma and alpha contamination. All measurements were below guideline. Two composite dust samples were collected from fourth level beams and horizontal surfaces. These samples were analyzed for total uranium-238, and results ranged from 1879 to 2984 pCi/g. These results can be compared to the uranium-238 guideline in soil of 150 pCi/g.

TABLE 5-1  
 BACKGROUND RADIATION RATES AND RADIONUCLIDE  
 CONCENTRATIONS IN SOIL

Location	Gamma Exposure Rate at 1 m ( $\mu$ R/h)	Radionuclide Concentrations (pCi/g)			
		U-238	Ra-226	Ac-227	Tn-232
1	4	1.5	0.8	not found	0.7
2	4	1.9	0.5	0.3	0.6
3	6	4.0	0.6	2.2	0.7
4	6	1.6	0.9	not found	1.0
5	3	0.3	0.2	not found	0.3
6	4	1.8	0.8	not found	0.8
Averages	4.5	1.8	0.6	0.4	0.7

Source: ORNL (Ref. 1)

TABLE 5-2  
 RADIONUCLIDE CONCENTRATIONS IN THE DELAWARE RIVER

Location	Radionuclide Concentrations (pCi/ml)			
	U-238	Ra-226	Th-230	Pb-210
W-1	$1.5 \times 10^{-3}$	$9 \times 10^{-6}$	$1.7 \times 10^{-5}$	$9 \times 10^{-4}$
W-2	$1.1 \times 10^{-3}$	$9 \times 10^{-6}$	$1.5 \times 10^{-5}$	$9 \times 10^{-4}$
W-3	$4.3 \times 10^{-4}$	$2.3 \times 10^{-5}$	$3.2 \times 10^{-5}$	$4.5 \times 10^{-4}$

Source: ORNL (Ref. 1)

TABLE 5-3

## RESIDUAL CONTAMINATION GUIDELINES AND CRITERIA FOR FUSPAP SITES

<u>Soil and Sediment</u> <sup>a, b</sup>	<u>Guidelines</u>		
Uranium-238 <sup>c</sup>	150 pCi/g above background		
Uranium-235 <sup>c</sup>	140 pCi/g above background		
Uranium-234 <sup>c</sup>	150 pCi/g above background		
Radium-226 and Thorium-232	5 pCi/g above background when averaged over the first 15 cm of soil below the surface; 15 pCi/g above background when averaged over 15-cm thick soil layers more than 15 cm below the surface and less than 1.5 m below the surface		
<u>Radionuclides in Water</u>	<u>Criteria</u>		
Total Uranium	600 pCi/l		
<u>Surface Contamination</u>	<u>Average</u> <sup>d</sup>	<u>Maximum</u> <sup>e</sup>	<u>Units</u>
Beta-gamma dose rates	0.2	1.0	µrad/h
Alpha surface for U-natural, U-238, U-235, and associated decay products	5000	15000	dpm/100 cm <sup>2</sup>
<u>External Gamma</u>	60 µR/h above background		
<u>Air Particulate</u>	0.1 pCi/m <sup>3</sup>		

<sup>a</sup>Except for radium-226, these criteria represent unrestricted-use concentrations above background, averaged across any 15-cm layer to any depth and over any contiguous 100-m<sup>2</sup> surface area. The same conditions prevail for radium-226 except for soil layers beneath 1.5 m. The allowable radium-226 concentration may be affected by site-specific conditions and must be evaluated accordingly.

<sup>b</sup>Localized concentrations in excess of these limits are allowable provided that the average over 100 m<sup>2</sup> is not exceeded.

<sup>c</sup>Assumes that no other uranium isotopes are present.

<sup>d</sup>Measurements of average contamination are averaged over areas of no greater than 1 m<sup>2</sup>.

<sup>e</sup>The maximum contamination levels apply to areas of not more than 100 cm<sup>2</sup>.

Sources: DOE (Ref. 5 and 6)

TABLE 5-4  
 DUPONT CHAMBERS WORKS SITE: PRE-REMEDIAL ACTION  
 SUMMARY OF OUTDOOR MEASUREMENT RESULTS

Measurement Location and Type <sup>a</sup>	Units	Number of Measurements Made	Range	Normal Background (BKG)
<u>Building 845 Area</u>				
Near-surface gamma	cpm	142	1770-12246	2,500
Beta-gamma dose rates	mrad/h	142	BKG - 0.08	0.02
External gamma exposure rates	μR/h	31	11.6 - 27.8	4.5
<u>Feeder Ditch and Central Drainage Ditch</u>				
Near-surface gamma	cpm	73	1806-14532	2,500
Beta-gamma dose rates	mrad/h	73	BKG-0.13	0.02
External gamma exposure rates	μR/h	12	12.8 - 15.4	4.5
<u>F Corral Parking Area</u>				
Near-surface gamma	cpm	203	1608-5020	2,500
Beta-gamma dose rates	mrad/h	203	BKG-0.14	0.02
External gamma exposure rates	μR/h	27	11.6 - 13.8	4.5
<u>Building J-26 Area</u>				
Near-surface gamma	cpm	41	1568-4334	2,500
Beta-gamma dose rates	mrad/h	41	BKG-0.05	0.02
<u>East Burial Area</u>				
Near-surface gamma	cpm	89	1212-17878	2,500
Beta-gamma dose rates	mrad/h	89	BKG-0.04	0.02
External gamma exposure rates	μR/h	15	12.2-15.0	4.5
<u>Lagoon A</u>				
Near-surface gamma	cpm	64	1566-3436	2,500
Beta-gamma dose rates	mrad/h	64	BKG-0.05	0.02
External gamma exposure rates	μR/h	4	11.2-15.8	4.5

<sup>a</sup>Near-surface gamma measurements were made with a SPA-3 coupled with a PRS-1. Beta-gamma dose rates were measured with an HP-210 and PRS-1. Gamma exposure rates were measured with a PIC.

TABLE 5-5

## DUPONT CHAMBERS WORKS SITE: GAMMA SPECTROMETRY OF SOIL SAMPLES

Page 1 of 5

Sampling Location	Depth (inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)					
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235	
<b>Building 845 Area:</b>							
<u>Grid E</u>	<u>Grid N</u>						
2761	4730	6-10	581.20 + 11.80	1.83 + .28	.96 + .55	---	---
2761	4730	10-14	427.60 + 9.68	1.07 + .20	1.51 + .56	---	---
2761	4730	14-18	164.80 + 5.34	.38 + .13	---	---	---
2761	4730	18-22	61.92 + 21.60	.33 + .22	.86 + .29	---	---
2761	4730	22-26	4.92 + 1.47	.28 + .23	.62 + .26	---	---
2761	4745	0-4	7398.00 + 32.70	4.06 + .77	---	---	---
2761	4745	6-10	720.10 + 9.50	.67 + .20	.66 + .23	---	---
2761	4745	42-45	321.80 + 7.14	.78 + .19	.46 + .26	---	---
2761	4745	46-50	358.40 + 11.14	.69 + .21	---	---	---
2761	4745	50-54	269.50 + 6.88	.36 + .17	.40 + .42	---	---
2761	4745	54-58	94.98 + 5.88	.37 + .29	---	---	---
2761	4745	58-62	152.40 + 9.25	.86 + .20	---	---	---
2761	4745	62-66	.63 + 1.54	.63 + .14	.94 + .28	---	---
2780	4771	6-10	10.61 + 6.69	---	---	---	---
2780	4771	10-14	25.61 + 5.12	---	---	---	---
2780	4771	14-18	159.30 + 10.19	.90 + .29	---	---	---
2780	4771	36-40	40.87 + 3.39	.92 + .15	.97 + .49	---	---
2782	4730	2-3	4355.00 + 68.70	5.12 + 2.17	---	---	---
2782	4730	3-7	561.40 + 11.12	1.99 + .27	---	---	---
2782	4730	7-11	58.06 + 2.93	.82 + .16	---	---	---
2782	4730	11-15	.80 + .20	.63 + .11	.58 + .22	.70 + .20	.09 + .08
2782	4730	15-19	---	.53 + .13	.48 + .17	---	---
2782	4730	19-23	---	.42 + .14	.23 + .23	---	---
2782	4730	23-27	---	.46 + .25	---	---	---
<b>F Corral Parking Area:</b>							
<u>Grid E</u>	<u>Grid N</u>						
2507	4900	13-17	323.70 + 16.36	1.04 + .42	---	---	---
2507	4900	17-21	1333.00 + 41.20	8.58 + .93	---	---	---
2507	4900	21-25	1768.00 + 42.40	8.91 + .86	---	---	---
2507	4900	25-29	863.30 + 26.24	2.66 + .50	---	---	---
2507	4900	29-33	3531.00 + 25.90	2.11 + .62	---	---	---
2507	4900	54-56	1629.00 + 51.30	1.69 + .86	---	---	---
2507	4900	56-60	4378.00 + 25.29	1.16 + .48	---	---	---
2507	4900	60-64	4247.00 + 61.35	1.03 + .71	---	---	---
2507	4900	64-68	1734.00 + 44.40	.76 + .56	---	---	---
2507	4900	68-72	662.30 + 37.91	1.10 + .58	---	---	---
2507	4900	72-76	536.20 + 18.65	---	.79 + .26	---	---
2540	4850	6-10	12.59 + 2.21	.28 + .16	---	---	---
2540	4850	10-14	1.40 + .20	---	---	---	---
2540	4850	14-18	.90 + .20	---	---	1.70 + .20	.12 + .05

TABLE 5-5  
(continued)

Page 2 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)					
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235	
<b>F Corral Parking Area:</b>							
<u>Grid E</u>	<u>Grid N</u>						
2540	4850	18-22	3.90 + 1.01	.15 + .05	---	.80 + .20	.05 + .04
2540	4850	22-26	6.93 + 1.46	.19 + .12	.11 + .12	---	---
2540	4850	26-30	281.20 + 11.70	2.72 + .33	.62 + .18	---	---
2540	4850	36-42	1066.00 + 12.11	6.51 + .51	.84 + .38	---	---
<b>East Burial Area:</b>							
<u>Grid E</u>	<u>Grid N</u>						
5518	3018	9-13	11210. + 39.40	27.84 + 2.28	---	---	---
5518	3018	13-17	20810. + 54.38	25.98 + 2.37	---	---	---
5518	3018	17-21	673.30 + 9.59	1.27 + .10	.69 + .34	---	---
5518	3018	21-25	185.40 + 4.94	1.04 + .08	1.05 + .24	---	---
5518	3018	25-29	296.90 + 6.59	3.93 + .32	---	---	---
5518	3018	29-33	375.40 + 8.33	.19 + .02	---	---	---
5518	3018	34-38	602.10 + 13.30	5.02 + .41	.64 + .53	---	---
5533	3018	6-10	18670. + 16.83	5.13 + .42	---	---	---
5533	3018	10-14	6029.00 + 30.04	16.02 + 1.31	---	---	---
5533	3018	14-18	710.20 + 9.75	5.45 + .45	---	---	---
5533	3018	18-23	577.40 + 11.39	3.73 + .31	---	---	---
5533	3018	22-26	745.80 + 9.92	1.87 + .15	.48 + .60	---	---
5533	3018	26-30	517.20 + 8.04	.63 + .22	---	---	---
5533	3018	30-32	530.10 + 11.10	1.24 + .39	.57 + .58	---	---
<b>Building 845 (Interior)</b>							
<u>Grid No.</u>	<u>Core No.</u>						
9	CB-1	6-9	2092.00 + 3.31	1.44 + .19	1.05 + .40	---	---
9	CB-1	9-13	21.82 + 2.54	.80 + .17	1.14 + .30	---	---
11	CB-13	15-19	3281.00 + 28.45	---	---	---	---
11	CB-13	19-24	1342.00 + 13.80	.43 + .28	---	---	---
11	CB-13	24-29	130.10 + 3.70	.90 + .29	---	---	---
11	CB-13	33-36	1351.00 + 18.00	1.40 + .46	---	---	---
11	CB-13	39-43	18.35 + 2.33	.70 + .14	.73 + .28	---	---
11	CB-13	43-47	1.35 + 1.49	1.30 + .20	1.28 + .25	---	---
11	CB-13	47-51	---	.90 + .45	---	---	---
11	CB-13	51-55	---	1.07 + .18	.97 + .29	---	---
11	CB-13	55-59	1.14 + .93	.65 + .14	---	---	---
11	CB-13	59-63	4.09 + 1.44	.43 + .12	.28 + .31	---	---
40	CB-2	0-6	149.80 + 8.21	1.13 + .20	---	---	---
40	CB-2	0-6	86.89 + 5.00	.33 + .16	.61 + .17	---	---
40	CB-2	12-16	166.40 + 8.10	1.09 + .38	.86 + .45	---	---
40	CB-2	12-16	36.24 + 1.32	.48 + .08	.62 + .14	---	---
40	CB-2	16-20	145.60 + 10.47	---	---	---	---



TABLE 5-5  
(continued)

Page 3 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)					
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235	
Building 845 (Interior):							
Grid No.	Core No.						
40	CB-2	16-20	177.20 + 8.04	.48 + .31	.18 + .50	---	---
40	CB-2	20-24	106.20 + 8.36	.57 + .22	---	---	---
40	CB-2	20-24	49.37 + 4.26	.56 + .24	.13 + .45	---	---
40	CB-2	24-28	29.09 + 3.70	.85 + .37	---	---	---
40	CB-2	24-28	56.79 + 4.63	.94 + .28	.23 + .39	---	---
40	CB-2	28-32	43.66 + 6.30	---	---	---	---
40	CB-2	28-32	18.58 + 5.29	---	---	---	---
65	CB-3	0-3	1256.00 + 42.13	---	---	---	---
65	CB-3	3-7	484.70 + 19.50	---	---	---	---
65	CB-3	7-11	569.90 + 10.30	.35 + .19	---	---	---
65	CB-3	11-15	427.80 + 9.74	.22 + .32	.99 + .31	---	---
67	CB-4	23-27	45.87 + 3.64	.77 + .16	.62 + .25	---	---
67	CB-4	27-31	790.10 + 10.00	.66 + .44	---	---	---
71	CB-14	20-23	39.12 + 3.00	.74 + .13	.42 + .21	---	---
80	CB-5	21-30	72.63 + 7.24	.84 + .21	---	---	---
80	CB-5	30-39	10.09 + 2.87	---	---	---	---
106	CB-6	22-27	9.82 + 7.59	---	---	---	---
107	CB-26	6-10	43.14 + 7.67	1.01 + .25	---	---	---
107	CB-26	10-14	37.89 + 2.64	.51 + .20	.91 + .32	---	---
107	CB-26	14-18	42.07 + 3.13	.90 + .13	.37 + .22	---	---
107	CB-26	18-22	17.89 + 2.19	.92 + .14	.71 + .16	---	---
123	CB-15	8-12	2014.00 + 15.80	.78 + .32	1.20 + .41	---	---
123	CB-15	12-16	166.80 + 5.78	.98 + .18	1.22 + .31	---	---
123	CB-15	16-20	71.34 + 4.29	.36 + .16	.75 + .29	---	---
123	CB-15	20-24	12.52 + 2.29	1.10 + .20	1.15 + .39	---	---
123	CB-15	24-28	1.00 + .20	.99 + .18	10.44 + .25	1.00 + .20	.04 + 0.3
136	CB-12	7-12	38.16 + 3.63	.85 + .17	---	---	---
136	CB-12	12-18	56.41 + 3.92	1.64 + .28	.61 + .28	---	---
136	CB-12	18-21	3.30 + .30	---	---	3.40 + .30	.11 + .07
143	CB-7	6-10	991.20 + 11.71	1.42 + .21	---	---	---
143	CB-7	10-14	94.34 + 4.39	.63 + .15	1.16 + .25	---	---
143	CB-7	14-18	1.24 + 6.96	---	---	---	---
143	CB-7	18-22	1.53 + 1.06	.44 + .23	.56 + .29	---	---
143	CB-7	22-26	1.69 + 1.46	1.10 + .15	.54 + .31	---	---
173	CB-16	6-10	2785.00 + 48.20	4.94 + .82	---	---	---
173	CB-16	10-14	5839.00 + 76.74	4.27 + .90	---	---	---
173	CB-16	14-18	8057.00 + 3.62	.83 + .70	---	---	---
173	CB-16	18-22	6721.00 + 31.70	---	---	---	---
173	CB-16	33-37	2083.00 + 16.50	.80 + .35	---	---	---
173	CB-16	37-41	843.20 + 11.10	1.23 + .34	.95 + .33	---	---
173	CB-16	41-45	719.00 + 10.30	1.10 + .24	---	---	---

TABLE 5-5  
(continued)

Page 4 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)				
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235
Building 845 (Interior):						
Grid No.	Core No.					
173	CB-16	45-49	7.76 + 3.90	.78 + .17	---	---
173	CB-16	49-53	35.37 + 3.43	.62 + .22	.93 + .32	---
192	CB-17	0-1	4699.00 + 68.90	---	---	---
192	CB-17	6-10	2517.00 + 18.63	.54 + .38	---	---
192	CB-17	10-14	1471.00 + 13.25	---	---	---
192	CB-17	14-18	151.90 + 5.36	.49 + .12	---	---
192	CB-17	18-22	197.10 + 5.91	.35 + .14	.34 + .27	---
194	CB-27	6-10	32.62 + 2.38	.32 + .13	---	---
197	CB-18	6-10	187.90 + 4.78	1.73 + .20	---	---
199	CB-11	6-10	8334.00 + 122.40	---	---	---
199	CB-11	10-14	3938.00 + 31.60	.31 + .77	---	---
199	CB-11	14-18	2168.00 + 58.40	---	---	---
199	CB-11	18-22	409.90 + 10.49	.48 + .30	---	---
199	CB-11	22-26	302.10 + 11.06	.72 + .36	---	---
199	CB-11	26-30	59.62 + 4.04	.58 + .18	.56 + .30	---
221	CB-24	0-4	2.30 + .30	---	---	2.40 + .30
221	CB-24	4-12	3.40 + .30	---	---	3.40 + .30
221	CB-24	4-12	6.89 + 1.75	.67 + .20	.71 + .20	---
221	CB-24	12-16	7.00 + 1.69	.58 + .13	---	---
221	CB-24	12-16	3.23 + 2.22	.55 + .16	.72 + .26	---
221	CB-24	16-20	6.23 + 3.47	---	---	---
221	CB-24	16-20	5.66 + 1.43	.76 + .16	.41 + .19	---
221	CB-24	20-24	3.61 + 3.03	.31 + .14	---	---
221	CB-24	20-24	3.00 + 1.88	.70 + .13	---	---
252	CB-8	6-8	268.90 + 15.50	---	---	---
252	CB-8	8-12	29.24 + 3.92	.26 + .18	---	---
252	CB-8	12-16	23.54 + 2.13	.38 + .15	.33 + .12	---
253	CB-19	35-36	1143.00 + 53.20	---	---	---
253	CB-19	36-40	446.60 + 9.70	.74 + .25	.63 + .20	---
253	CB-19	40-44	817.50 + 27.91	---	---	---
253	CB-19	44-48	1113.00 + 11.70	---	---	---
253	CB-19	48-52	12.83 + 1.72	.55 + .11	---	---
253	CB-19	52-56	---	.52 + .13	.32 + .22	---
253	CB-19	56-60	2.67 + 1.32	.42 + .12	.80 + .18	---
260	CB-20	7-10	25.03 + 4.17	.23 + .10	---	---
260	CB-20	10-14	3.32 + 1.23	.08 + .12	---	---
260	CB-20	14-18	---	.41 + .18	---	---
260	CB-20	18-22	---	.15 + .12	.43 + .13	---
260	CB-20	22-26	1.19 + 1.54	.47 + .16	.55 + .30	---
260	CB-20	26-30	---	.47 + .17	.86 + .27	---
271	CB-9					
277	CB-23	6-10	.70 + .10	.42 + .15	.59 + .19	.80 + .10
277	CB-23	10-14	---	.52 + .29	---	---
277	CB-23	14-18	---	.26 + .10	.59 + .19	---
277	CB-23	18-22	---	.49 + .13	.55 + .15	---

TABLE 5-5  
(continued)

Page 5 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)				
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235
Building 845 (Interior):						
Grid No.	Core No.					
277	CB-23	22-26	---	.67 ± .13	.82 ± .18	---
309	CB-21	6-10	17.29 ± 2.14	.47 ± .14	---	---
309	CB-21	10-14	3.16 ± .97	.26 ± .08	---	---
309	CB-21	14-18	10.61 ± 4.58	.25 ± .20	---	---
312	CB-10	6-7	305.50 ± 1.96	3.30 ± 1.96	---	---
312	CB-10	7-11	17.95 ± 1.94	.61 ± .10	.34 ± .26	---
316	CB-22	6-10	44.95 ± 6.20	1.01 ± .25	---	---
316	CB-22	10-14	11.50 ± 2.05	.60 ± .12	.46 ± .18	---
316	CB-22	14-18	---	.69 ± .28	---	---
316	CB-22	18-22	5.82 ± 1.17	.86 ± .15	---	---
316	CB-22	22-26	4.64 ± 2.07	1.53 ± .23	.98 ± .36	---
316	CB-22	26-30	---	.55 ± .29	---	---
360	CB-25	5-9	3.56 ± 1.19	.33 ± .14	---	---

TABLE 5-6

## DUPONT CHAMBERS WORKS SITE: GAMMA SPECTROMETRY OF SEDIMENT SAMPLES

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)				
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235
Wooden Trough East of Building 845:						
<u>Grid E</u>	<u>Grid N</u>					
2710	4980	0-6	42.03 ± 9.62	1.03 ± .70	---	---
2730	4935	0-6	255.60 ± 18.50	2.45 ± .65	1.86 ± 1.07	---
2755	4890	0-6	40.98 ± 6.11	1.27 ± .34	.47 ± .64	---
2775	4840	0-6	49.13 ± 6.74	.87 ± .28	---	---
2775	4848	0-6	10.99 ± 4.53	---	---	---
2795	4795	0-6	127.60 ± 11.90	1.67 ± .73	2.03 ± .12	---
2800	4845	0-6	1.90 ± .30	---	---	2.10 ± .30
2820	4755	0-6	31.99 ± 4.45	---	---	---
2845	4715	0-6	16.52 ± 6.29	---	---	---
2760	4690	0-6	21.81 ± 6.09	2.58 ± .46	---	---
Central Drainage Ditch and Feeder Ditch:						
<u>Grid E</u>	<u>Grid N</u>					
2485	4700	0-6	1.20 ± .20	---	---	1.40 ± .20
2485	4700	0-6	1.00 ± .20	---	---	1.20 ± .20
2550	4770	0-6	1.70 ± .20	---	---	1.60 ± .20
2600	4990	0-6	4.10 ± 2.85	.50 ± .26	---	---
2630	4970	0-6	1.00 ± .20	---	---	1.20 ± .20
2650	4950	0-6	.90 ± .20	.41 ± .21	---	1.80 ± .20
2670	4940	0-6	1.50 ± .20	---	---	1.80 ± .20
2700	4990	0-6	1.60 ± .20	---	---	1.70 ± .20
2740	5060	0-6	1.50 ± .20	---	---	1.60 ± .20
2805	4820	0-6	1.20 ± .20	---	---	1.20 ± .20
2840	5130	0-6	1.60 ± .20	---	---	1.50 ± .20
2900	5145	0-6	1.70 ± .20	---	---	1.60 ± .20
2950	5160	0-6	1.00 ± .20	---	---	1.30 ± .20
3050	5150	0-6	2.10 ± .30	---	---	1.90 ± .30
3220	5150	0-6	1.90 ± .30	---	---	1.80 ± .30
Lagoon A:						
<u>Grid E</u>	<u>Grid N</u>					
4850	5800	0-6	.20 ± .10	---	---	.40 ± .10
4980	5665	0-6	1.60 ± .20	---	---	1.70 ± .20

TABLE 5-7  
 DUPONT CHAMBERS WORKS SITE:  
 RESULTS OF RADIOCHEMISTRY ANALYSIS OF WATER SAMPLES

Page 1 of 2

Sampling Location	Depth (inches)	Total Uranium (pCi/l $\pm$ 2 sigma)
Inside Building 845:	42	7507.51
Building 845 Area:		
<u>Grid E</u>	<u>Grid N</u>	
2534	4710	12.01
2600	4655	10.51
2624	4766	18.02
2650	4766	15.32
2650	4798	1.80
2650	4816	2.70
2667	4600	1.50
2678	4829	1.50
2681	4765	1.50
2717	4824	5.11
2747	4822	2.10
2761	4745	1,381.38
2768	4586	60.06
2768	4750	660.66
2779	4738	246.25
2780	4702	150.15
2790	4771	11,712.00
2799	4701	10.21
2799	4730	132.13
2799	4748	150.15
2816	4670	1,001.80
F Corral:		
<u>Grid E</u>	<u>Grid N</u>	
2444	5000	6.01
2450	4850	105.11
2450	4954	1,621.62
2492	4802	156.16
2500	4950	2,852.85
2500	4995	4.50
2507	4900	105,105.00
2540	4850	16,817.00
2565	4958	264.26
2580	4844	7.51
2603	4897	1.50

TABLE 5-7  
(continued)

Page 2 of 2

Sampling Location	Depthn (inches)	Total Uranium (pCi/l $\pm$ 2 sigma)
Building J-26 Area:		
Grid E 1765	Grid N 2910	30
		14
East Burial Area:		
Grid E 5440	Grid N 3080	36
5580	3070	36
		24
		6
Lagoon A:	Surface	4

TABLE 5-8

DUPONT CHAMBERS WORKS SITE: PRE-REMEDIAL ACTION  
SUMMARY OF BUILDING 845 MEASUREMENT RESULTS

Page 1 of 2

Measurement Locations	Measurement Type <sup>a</sup>	Units <sup>a</sup>	No. of Readings Taken	Grid Block Average Range	Maximum Reading Observed
<u>First Level</u>					
Ceiling	Beta-Gamma Dose Rate	mrad/h	41	0-4.78	4.78
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	41	0-5568	5568
Floor	Beta-Gamma Dose Rate	mrad/h	1850	0-4.54	5.78
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	1850	0-6819	26544
East Wall	Beta-Gamma Dose Rate	mrad/h	120	0-10.34	10.34
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	120	2-4169	6229
West Wall	Beta-Gamma Dose Rate	mrad/h	175	0-8.69	16.30
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	175	8-2461	6110
North Wall	Beta-Gamma Dose Rate	mrad/h	105	0.04-3.29	3.65
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	105	17-483	890
South Wall	Beta-Gamma Dose Rate	mrad/h	65	0.08-1.51	1.57
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	65	29-102	161
Floor/Wall Intersection	Beta-Gamma Dose Rate	mrad/h	244	0-6.05	8.88
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	244	0-10621	18041
<u>Second Level</u>					
Ceiling	Beta-Gamma Dose Rate	mrad/h	38	0.02-4.87	4.67
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	38	8-3992	3992
Floor	Beta-Gamma Dose Rate	mrad/h	580	0-2.85	3.45
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	580	0-264	564
East Wall	Beta-Gamma Dose Rate	mrad/h	20	0.09-10.92	10.92
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	20	51-9068	9068
West Wall	Beta-Gamma Dose Rate	mrad/h	30	0.05-5.53	5.53
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	30	0-3712	3712
North Wall	Beta-Gamma Dose Rate	mrad/h	60	0.07-0.96	1.19
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	60	14-763	763
South Wall	Beta-Gamma Dose Rate	mrad/h	15	0.07-0.54	0.54
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	15	34-44	85
Floor/Wall Intersection	Beta-Gamma Dose Rate	mrad/h	118	0.01-2.16	2.77
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	118	0-1221	1516

TABLE 5-8  
(Continued)

Page 2 of 2

Measurement Locations	Measurement Type <sup>a</sup>	Units <sup>a</sup>	No. of Readings Taken	Grid Block Average Range	Maximum Reading Observed
Ceiling	Beta-Gamma Dose Rate	mrad/h	240	0.02-1.49	7.05
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	240	8-1347	1347
Floor	Beta-Gamma Dose Rate	mrad/h	120	0-1.40	2.38
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	120	0-1017	1281
East Wall	Beta-Gamma Dose Rate	mrad/h	24	0.09-2.84	2.84
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	24	53-3976	3076
West Wall	Beta-Gamma Dose Rate	mrad/h	180	0.25-2.37	2.37
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	180	42-1754	1754
North Wall	Beta-Gamma Dose Rate	mrad/h	36	0.08-0.61	0.65
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	36	37-653	653
South Wall	Beta-Gamma Dose Rate	mrad/h	10	0.08-0.08	0.10
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	10	49-69	110
Floor/Wall Intersection	Beta-Gamma Dose Rate	mrad/h	142	0-0.68	0.98
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	142	0-1930	2599
<u>Fourth Level</u>					
Ceiling	Beta-Gamma Dose Rate	mrad/h	39	0.05-4.34	4.34
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	39	76-2703	2703
Floor	Beta-Gamma Dose Rate	mrad/h	1095	0-1.00	1.76
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	1095	0-885	2561
East Wall	Beta-Gamma Dose Rate	mrad/h	33	0.03-1.26	1.26
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	33	36-2331	2331
West Wall	Beta-Gamma Dose Rate	mrad/h	33	0.08-1.46	1.46
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	33	0-3318	3318
North Wall	Beta-Gamma Dose Rate	mrad/h	20	0.07-0.27	0.27
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	20	47-572	572
South Wall	Beta-Gamma Dose Rate	mrad/h	9	0.34-3.39	3.39
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	9	40-3487	3487
Ceiling Heaters	Beta-Gamma Dose Rate	mrad/h	6	0.02-0.06	0.06
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	6	93-195	195

<sup>a</sup>For beta-gamma dose rate, the average criteria limit is 0.2 mrad/h and maximum criteria limit is 1.0 mrad/h. For direct alpha activity on surfaces, the average criteria limit is 5000 dpm/100 cm<sup>2</sup> and maximum criteria limit is 15,000 dpm/100 cm<sup>2</sup> (Ref. 5).



## 6.0 SIGNIFICANCE OF FINDINGS

The 1983 survey results show that five of the six areas surveyed are contaminated above current guidelines. The interior of Building 845 also is contaminated. These results are explained in greater detail in the following subsections.

### 6.1 FIELD SURVEY

The volumes of material contaminated above applicable remedial action criteria were based on the areal extent of the contamination plus the depth of contamination based on estimates and/or measurements. For soils, the extent of contamination was based on near-surface gamma measurements, surface soil samples, gamma logging of boreholes, and subsurface soil sampling. The depth of contaminated layers was based on actual measurements.

The extent of surface contamination in Building 845 was based on surface alpha and beta-gamma measurements, with beta-gamma measurements used as the primary survey method. The depth of contamination was estimated to be 1 inch, averaged over the contaminated area.

#### 6.1.1 Building 845 Area

Results from near-surface gamma radiation measurements were used to determine the extent of surface contamination. An area east of Building 845 was found to have readings greater than twice background, a finding in agreement with the ORNL survey (Ref. 1). The area that exhibited readings above criteria is shown in Figure 6-1.

Results from borehole gamma logs and subsurface soil samples were used to determine the depth of contamination. The major contaminant was found to be uranium-238, and subsurface contamination appears to be in layers to depths greater than 3 m (9 ft). However, the most




FIGURE 6-1 BUILDING 845 AREA AND WOODEN DRAINAGE TROUGH REQUIRING REMEDIAL ACTION

significant layer of contamination was located in the upper 1 m (3 ft) of soil. Gamma loggings in the soil below the depth of 1 m (3 ft) are approaching remedial action criteria.

Based on results from sediment samples, the wooden drainage trough located east of Building 845 would also require remedial action.

To comply with DOE guidelines, an estimated 765 m<sup>3</sup> (1000 yd<sup>3</sup>) of material would require removal from the area around Building 845, including the wooden drainage trough, during remedial action.

#### 6.1.2 Central Drainage Ditch

Results from near-surface gamma measurements made in the Central Drainage Ditch area indicated that an area located southwest of the drainage ditch had readings which were greater than twice background. Borehole gamma loggings in this area indicated areas of elevated readings which approach remedial action criteria limits. The elevated areas appear to be in layers which are at depths from 15 cm (6 in.) to greater than 2.5 m (8 ft).

Sediment samples taken from the Central Drainage Ditch and the Feeder ditch indicated below-criteria concentrations of uranium-238, -235, and -234.

During remedial action, the banks of the Central Drainage Ditch would require "hot spotting" to comply with guidelines. During hot spotting operations, approximately 11 m<sup>3</sup> (15 yd<sup>3</sup>) of material would require removal from the area.

#### 6.1.3 F Corral Parking Area

One near-surface gamma measurement exceeded twice background. All other measurements were within background levels. Borehole gamma loggings indicated contamination at depths greater than 3 m (9 ft), with the most significant layer of contamination located in the

upper 1 m (3 ft) of soil. Major readings below this depth approach remedial action guidelines. Soil samples show the contaminant is uranium-238, and the maximum uranium-238 concentration observed in subsurface soil samples was 4378 pCi/g.

Groundwater sample results from the F Corral parking area showed total uranium concentrations above the criteria limit. The maximum concentration observed for uranium-238 was 105,105 pCi/l. This sample was collected at a depth of 1 m (3 ft).

The area exhibiting measurements above guidelines is shown in Figure 6-2. During remedial action, an estimated 2700 m<sup>3</sup> (3500 yd<sup>3</sup>) would require removal to meet DOE guidelines.

#### 6.1.4 Building J-26 Area

All surface and subsurface measurements made in the Building J-26 area indicate the area is not contaminated. Water samples collected from the J-26 area were below criteria limits.

#### 6.1.5 East Burial Area

Near-surface gamma readings indicate three locations which exceeded twice background levels. All beta-gamma dose rates were below criteria limits.

Borehole gamma logging indicated contaminated layers of soil to depths greater than 2.7 m (8.5 ft). The most significant layer of contamination was located in the upper 1 m (3 ft). Elevated readings below this depth approach remedial action criteria. Higher count rates were observed in the boreholes drilled adjacent to the road. Areas which exhibited measurements above criteria are shown on Figure 6-3.




FIGURE 6-2 F CORRAL AREA REQUIRING REMEDIAL ACTION




FIGURE 6-3 EAST BURIAL AREA REQUIRING REMEDIAL ACTION

Based on soil sample results, uranium-238 is the major contaminant, and the maximum concentration observed was 20,810 pCi/g. Elevated concentrations of radium-226 were observed in some soil samples (see Table 5-5).

During remedial action, an estimated 2800 m<sup>3</sup> (3700 yd<sup>3</sup>) of material would require removal from the East Burial Area to comply with criteria.

#### 6.1.6 Lagoon A

All surface measurements made in the Lagoon A area were within normal background. Borehole gamma count rates below 1.6 m (5.0 ft) indicated readings above background, but below the guideline.

#### 6.2 BUILDING 845 SURVEY

As shown in Table 5-8, alpha and beta-gamma contamination levels on some interior surfaces of all four levels of Building 845 were in excess of the surface contamination guidelines for release of property for unrestricted use (Ref. 4). Figures 6-4 through 6-11 show floor, wall, and ceiling areas which indicated surface readings above guidelines. The area shown inside the lunch room (Grid Block Numbers 210, 211, 212, 214, 220, 230, 242, 254, and 258) indicated beta-gamma measurements above criteria. This contamination is fixed and poses no health hazard for activities presently carried on in the lunch room.

Building 845 first floor corehole loggings, coupled with Shelby tube soil samples indicated areas of contamination beneath the building up to depths of 1.2 m (4 ft). These areas of contamination are illustrated in Figure 6-12.

Based on these results, an estimated 560 m<sup>3</sup> (760 yd<sup>3</sup>) of soil would require removal from beneath Building 845 to comply with criteria. In addition, remedial action would include the

decontamination of all areas inside Building 845 which exhibited surface measurements above remedial action criteria limits. Surface decontamination of the building would involve removal of 2.5 cm (1 in.) of material from approximately 2050 m<sup>2</sup> (22,000 ft<sup>2</sup>) of contaminated surface areas. This would result in approximately 50 m<sup>3</sup> (70 yd<sup>3</sup>) of material which would require removal. Total demolition of Building 845 would result in approximately 2300 m<sup>3</sup> (3000 yd<sup>3</sup>) of material.






FIGURE 6-4 BUILDING 845, FIRST FLOOR: AREAS OF SURFACE CONTAMINATION ON FLOOR, WALLS, AND FLOOR/WALL INTERSECTIONS



10	20	38	44	50	58	68	78	88	98	104	114	124	134	144	154	164	174	184	194	204	214	224	234	244	254	264	274	284	294	304	314	324	334	344	354	364
9	19	32	46	58	71	84	97	110	123	135	148	161	174	187	199	212	225	238	251	264	277	290	303	316	329	342	355	368	381	394	407	420	433	446	459	472
8	18	31	44	57	70	83	96	109	122	135	148	161	174	187	200	213	226	239	252	265	278	291	304	317	330	343	356	369	382	395	408	421	434	447	460	473
7	17	30	43	56	69	82	95	108	121	134	147	160	173	186	199	212	225	238	251	264	277	290	303	316	329	342	355	368	381	394	407	420	433	446	459	472
6	16	29	42	55	68	81	94	107	120	133	146	159	172	185	198	211	224	237	250	263	276	289	302	315	328	341	354	367	380	393	406	419	432	445	458	471
5	15	28	41	54	67	80	93	106	119	132	145	158	171	184	197	210	223	236	249	262	275	288	301	314	327	340	353	366	379	392	405	418	431	444	457	470
4	14	27	40	53	66	79	92	105	118	131	144	157	170	183	196	209	222	235	248	261	274	287	300	313	326	339	352	365	378	391	404	417	430	443	456	469
3	13	26	39	52	65	78	91	104	117	130	143	156	169	182	195	208	221	234	247	260	273	286	299	312	325	338	351	364	377	390	403	416	429	442	455	468
2	12	25	38	51	64	77	90	103	116	129	142	155	168	181	194	207	220	233	246	259	272	285	298	311	324	337	350	363	376	389	402	415	428	441	454	467
1	11	24	37	50	63	76	89	102	115	128	141	154	167	180	193	206	219	232	245	258	271	284	297	310	323	336	349	362	375	388	401	414	427	440	453	466


LEGEND







AREAS OF CEILING SURFACE CONTAMINATION

SCALE 0 6 12 ft  
0 18 36 m

FIGURE 6-5 BUILDING 845, FIRST FLOOR CEILING: AREAS OF SURFACE CONTAMINATION



LEGEND

-  CONTAMINATED FLOOR AND INTERIOR SURFACES OF EXTERIOR WALLS
-  CONTAMINATED SURFACE OF INTERIOR WALL OR PARTITION
-  CONTAMINATED FLOOR/WALL INTERSECTIONS
-  OUTLINE OF OLD FLOOR AREAS

SCALE 0 6 12 ft  
0 1.5 3.6 m

FIGURE 8-6 BUILDING 845, SECOND FLOOR: AREAS OF CONTAMINATION ON FLOOR, WALLS, AND FLOOR/WALL INTERSECTIONS



10	20	30	40	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240	250	260	270	280	290	300	310	320	330	340	350	360	370	380	390	400	410	420	430	440	450	460	470	480	490	500	510	520	530	540	550	560	570	580	590	600	610	620	630	640	650	660	670	680	690	700	710	720	730	740	750	760	770	780	790	800	810	820	830	840	850	860	870	880	890	900	910	920	930	940	950	960	970	980	990	1000	
9	19	29	39	49	59	69	79	89	99	109	119	129	139	149	159	169	179	189	199	209	219	229	239	249	259	269	279	289	299	309	319	329	339	349	359	369	379	389	399	409	419	429	439	449	459	469	479	489	499	509	519	529	539	549	559	569	579	589	599	609	619	629	639	649	659	669	679	689	699	709	719	729	739	749	759	769	779	789	799	809	819	829	839	849	859	869	879	889	899	909	919	929	939	949	959	969	979	989	999	1009
8	18	28	38	48	58	68	78	88	98	108	118	128	138	148	158	168	178	188	198	208	218	228	238	248	258	268	278	288	298	308	318	328	338	348	358	368	378	388	398	408	418	428	438	448	458	468	478	488	498	508	518	528	538	548	558	568	578	588	598	608	618	628	638	648	658	668	678	688	698	708	718	728	738	748	758	768	778	788	798	808	818	828	838	848	858	868	878	888	898	908	918	928	938	948	958	968	978	988	998	1008
7	17	27	37	47	57	67	77	87	97	107	117	127	137	147	157	167	177	187	197	207	217	227	237	247	257	267	277	287	297	307	317	327	337	347	357	367	377	387	397	407	417	427	437	447	457	467	477	487	497	507	517	527	537	547	557	567	577	587	597	607	617	627	637	647	657	667	677	687	697	707	717	727	737	747	757	767	777	787	797	807	817	827	837	847	857	867	877	887	897	907	917	927	937	947	957	967	977	987	997	1007
6	16	26	36	46	56	66	76	86	96	106	116	126	136	146	156	166	176	186	196	206	216	226	236	246	256	266	276	286	296	306	316	326	336	346	356	366	376	386	396	406	416	426	436	446	456	466	476	486	496	506	516	526	536	546	556	566	576	586	596	606	616	626	636	646	656	666	676	686	696	706	716	726	736	746	756	766	776	786	796	806	816	826	836	846	856	866	876	886	896	906	916	926	936	946	956	966	976	986	996	1006
5	15	25	35	45	55	65	75	85	95	105	115	125	135	145	155	165	175	185	195	205	215	225	235	245	255	265	275	285	295	305	315	325	335	345	355	365	375	385	395	405	415	425	435	445	455	465	475	485	495	505	515	525	535	545	555	565	575	585	595	605	615	625	635	645	655	665	675	685	695	705	715	725	735	745	755	765	775	785	795	805	815	825	835	845	855	865	875	885	895	905	915	925	935	945	955	965	975	985	995	1005
4	14	24	34	44	54	64	74	84	94	104	114	124	134	144	154	164	174	184	194	204	214	224	234	244	254	264	274	284	294	304	314	324	334	344	354	364	374	384	394	404	414	424	434	444	454	464	474	484	494	504	514	524	534	544	554	564	574	584	594	604	614	624	634	644	654	664	674	684	694	704	714	724	734	744	754	764	774	784	794	804	814	824	834	844	854	864	874	884	894	904	914	924	934	944	954	964	974	984	994	1004
3	13	23	33	43	53	63	73	83	93	103	113	123	133	143	153	163	173	183	193	203	213	223	233	243	253	263	273	283	293	303	313	323	333	343	353	363	373	383	393	403	413	423	433	443	453	463	473	483	493	503	513	523	533	543	553	563	573	583	593	603	613	623	633	643	653	663	673	683	693	703	713	723	733	743	753	763	773	783	793	803	813	823	833	843	853	863	873	883	893	903	913	923	933	943	953	963	973	983	993	1003
2	12	22	32	42	52	62	72	82	92	102	112	122	132	142	152	162	172	182	192	202	212	222	232	242	252	262	272	282	292	302	312	322	332	342	352	362	372	382	392	402	412	422	432	442	452	462	472	482	492	502	512	522	532	542	552	562	572	582	592	602	612	622	632	642	652	662	672	682	692	702	712	722	732	742	752	762	772	782	792	802	812	822	832	842	852	862	872	882	892	902	912	922	932	942	952	962	972	982	992	1002
1	11	21	31	41	51	61	71	81	91	101	111	121	131	141	151	161	171	181	191	201	211	221	231	241	251	261	271	281	291	301	311	321	331	341	351	361	371	381	391	401	411	421	431	441	451	461	471	481	491	501	511	521	531	541	551	561	571	581	591	601	611	621	631	641	651	661	671	681	691	701	711	721	731	741	751	761	771	781	791	801	811	821	831	841	851	861	871	881	891	901	911	921	931	941	951	961	971	981	991	1001

SCALE 0 6 12 M  
0 1.8 3.6 M

LEGEND  
[ ] AREAS OF CEILING SURFACE CONTAMINATION

FIGURE 6-7 BUILDING 845, SECOND FLOOR CEILING: AREAS OF CONTAMINATION




FIGURE 6-8 BUILDING 845, THIRD FLOOR: AREAS OF SURFACE CONTAMINATION ON FLOOR, WALLS, AND FLOOR/WALL INTERSECTIONS



10	20	35	46	59	72	85	98	111	124	138	151	164	177	190	203	216	229	242	255	268	281	294	307	320	333	346	359	372	385	398	411	424	437	450	463	476	489	502	515	528	541	554	567	580	593	606	619	632	645	658	671	684	697	710	723	736	749	762	775	788	801	814	827	840	853	866	879	892	905	918	931	944	957	970	983	996	1009	1022	1035	1048	1061	1074	1087	1100	1113	1126	1139	1152	1165	1178	1191	1204	1217	1230	1243	1256	1269	1282	1295	1308	1321	1334	1347	1360	1373	1386	1399	1412	1425	1438	1451	1464	1477	1490	1503	1516	1529	1542	1555	1568	1581	1594	1607	1620	1633	1646	1659	1672	1685	1698	1711	1724	1737	1750	1763	1776	1789	1802	1815	1828	1841	1854	1867	1880	1893	1906	1919	1932	1945	1958	1971	1984	1997	2010	2023	2036	2049	2062	2075	2088	2101	2114	2127	2140	2153	2166	2179	2192	2205	2218	2231	2244	2257	2270	2283	2296	2309	2322	2335	2348	2361	2374	2387	2400	2413	2426	2439	2452	2465	2478	2491	2504	2517	2530	2543	2556	2569	2582	2595	2608	2621	2634	2647	2660	2673	2686	2699	2712	2725	2738	2751	2764	2777	2790	2803	2816	2829	2842	2855	2868	2881	2894	2907	2920	2933	2946	2959	2972	2985	2998	3011	3024	3037	3050	3063	3076	3089	3102	3115	3128	3141	3154	3167	3180	3193	3206	3219	3232	3245	3258	3271	3284	3297	3310	3323	3336	3349	3362	3375	3388	3401	3414	3427	3440	3453	3466	3479	3492	3505	3518	3531	3544	3557	3570	3583	3596	3609	3622	3635	3648	3661	3674	3687	3700	3713	3726	3739	3752	3765	3778	3791	3804	3817	3830	3843	3856	3869	3882	3895	3908	3921	3934	3947	3960	3973	3986	3999	4012	4025	4038	4051	4064	4077	4090	4103	4116	4129	4142	4155	4168	4181	4194	4207	4220	4233	4246	4259	4272	4285	4298	4311	4324	4337	4350	4363	4376	4389	4402	4415	4428	4441	4454	4467	4480	4493	4506	4519	4532	4545	4558	4571	4584	4597	4610	4623	4636	4649	4662	4675	4688	4701	4714	4727	4740	4753	4766	4779	4792	4805	4818	4831	4844	4857	4870	4883	4896	4909	4922	4935	4948	4961	4974	4987	5000	5013	5026	5039	5052	5065	5078	5091	5104	5117	5130	5143	5156	5169	5182	5195	5208	5221	5234	5247	5260	5273	5286	5299	5312	5325	5338	5351	5364	5377	5390	5403	5416	5429	5442	5455	5468	5481	5494	5507	5520	5533	5546	5559	5572	5585	5598	5611	5624	5637	5650	5663	5676	5689	5702	5715	5728	5741	5754	5767	5780	5793	5806	5819	5832	5845	5858	5871	5884	5897	5910	5923	5936	5949	5962	5975	5988	6001	6014	6027	6040	6053	6066	6079	6092	6105	6118	6131	6144	6157	6170	6183	6196	6209	6222	6235	6248	6261	6274	6287	6300	6313	6326	6339	6352	6365	6378	6391	6404	6417	6430	6443	6456	6469	6482	6495	6508	6521	6534	6547	6560	6573	6586	6599	6612	6625	6638	6651	6664	6677	6690	6703	6716	6729	6742	6755	6768	6781	6794	6807	6820	6833	6846	6859	6872	6885	6898	6911	6924	6937	6950	6963	6976	6989	7002	7015	7028	7041	7054	7067	7080	7093	7106	7119	7132	7145	7158	7171	7184	7197	7210	7223	7236	7249	7262	7275	7288	7301	7314	7327	7340	7353	7366	7379	7392	7405	7418	7431	7444	7457	7470	7483	7496	7509	7522	7535	7548	7561	7574	7587	7600	7613	7626	7639	7652	7665	7678	7691	7704	7717	7730	7743	7756	7769	7782	7795	7808	7821	7834	7847	7860	7873	7886	7899	7912	7925	7938	7951	7964	7977	7990	8003	8016	8029	8042	8055	8068	8081	8094	8107	8120	8133	8146	8159	8172	8185	8198	8211	8224	8237	8250	8263	8276	8289	8302	8315	8328	8341	8354	8367	8380	8393	8406	8419	8432	8445	8458	8471	8484	8497	8510	8523	8536	8549	8562	8575	8588	8601	8614	8627	8640	8653	8666	8679	8692	8705	8718	8731	8744	8757	8770	8783	8796	8809	8822	8835	8848	8861	8874	8887	8900	8913	8926	8939	8952	8965	8978	8991	9004	9017	9030	9043	9056	9069	9082	9095	9108	9121	9134	9147	9160	9173	9186	9199	9212	9225	9238	9251	9264	9277	9290	9303	9316	9329	9342	9355	9368	9381	9394	9407	9420	9433	9446	9459	9472	9485	9498	9511	9524	9537	9550	9563	9576	9589	9602	9615	9628	9641	9654	9667	9680	9693	9706	9719	9732	9745	9758	9771	9784	9797	9810	9823	9836	9849	9862	9875	9888	9901	9914	9927	9940	9953	9966	9979	9992	10005
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	-------

LEGEND



AREAS OF CEILING SURFACE CONTAMINATION

SCALE 0 6 12 ft  
0 1.8 3.6 m

FIGURE 6-9 BUILDING 845, THIRD FLOOR CEILING: AREAS OF SURFACE CONTAMINATION





10	20	33	46	59	72	85	98	111	124	137	150	163	176	189	202	215	228	241	254	267	280	293	306	319	332	345	358	371	384	397	410	423	436	449	462	475	488	501	514	527	540	553	566	579	592	605	618	631	644	657	670	683	696	709	722	735	748	761	774	787	800	813	826	839	852	865	878	891	904	917	930	943	956	969	982	995	1008	1021	1034	1047	1060	1073	1086	1099	1112	1125	1138	1151	1164	1177	1190	1203	1216	1229	1242	1255	1268	1281	1294	1307	1320	1333	1346	1359	1372	1385	1398	1411	1424	1437	1450	1463	1476	1489	1502	1515	1528	1541	1554	1567	1580	1593	1606	1619	1632	1645	1658	1671	1684	1697	1710	1723	1736	1749	1762	1775	1788	1801	1814	1827	1840	1853	1866	1879	1892	1905	1918	1931	1944	1957	1970	1983	1996	2009	2022	2035	2048	2061	2074	2087	2100	2113	2126	2139	2152	2165	2178	2191	2204	2217	2230	2243	2256	2269	2282	2295	2308	2321	2334	2347	2360	2373	2386	2399	2412	2425	2438	2451	2464	2477	2490	2503	2516	2529	2542	2555	2568	2581	2594	2607	2620	2633	2646	2659	2672	2685	2698	2711	2724	2737	2750	2763	2776	2789	2802	2815	2828	2841	2854	2867	2880	2893	2906	2919	2932	2945	2958	2971	2984	2997	3010	3023	3036	3049	3062	3075	3088	3101	3114	3127	3140	3153	3166	3179	3192	3205	3218	3231	3244	3257	3270	3283	3296	3309	3322	3335	3348	3361	3374	3387	3400	3413	3426	3439	3452	3465	3478	3491	3504	3517	3530	3543	3556	3569	3582	3595	3608	3621	3634	3647	3660	3673	3686	3699	3712	3725	3738	3751	3764	3777	3790	3803	3816	3829	3842	3855	3868	3881	3894	3907	3920	3933	3946	3959	3972	3985	3998	4011	4024	4037	4050	4063	4076	4089	4102	4115	4128	4141	4154	4167	4180	4193	4206	4219	4232	4245	4258	4271	4284	4297	4310	4323	4336	4349	4362	4375	4388	4401	4414	4427	4440	4453	4466	4479	4492	4505	4518	4531	4544	4557	4570	4583	4596	4609	4622	4635	4648	4661	4674	4687	4700	4713	4726	4739	4752	4765	4778	4791	4804	4817	4830	4843	4856	4869	4882	4895	4908	4921	4934	4947	4960	4973	4986	4999	5012	5025	5038	5051	5064	5077	5090	5103	5116	5129	5142	5155	5168	5181	5194	5207	5220	5233	5246	5259	5272	5285	5298	5311	5324	5337	5350	5363	5376	5389	5402	5415	5428	5441	5454	5467	5480	5493	5506	5519	5532	5545	5558	5571	5584	5597	5610	5623	5636	5649	5662	5675	5688	5701	5714	5727	5740	5753	5766	5779	5792	5805	5818	5831	5844	5857	5870	5883	5896	5909	5922	5935	5948	5961	5974	5987	6000	6013	6026	6039	6052	6065	6078	6091	6104	6117	6130	6143	6156	6169	6182	6195	6208	6221	6234	6247	6260	6273	6286	6299	6312	6325	6338	6351	6364	6377	6390	6403	6416	6429	6442	6455	6468	6481	6494	6507	6520	6533	6546	6559	6572	6585	6598	6611	6624	6637	6650	6663	6676	6689	6702	6715	6728	6741	6754	6767	6780	6793	6806	6819	6832	6845	6858	6871	6884	6897	6910	6923	6936	6949	6962	6975	6988	7001	7014	7027	7040	7053	7066	7079	7092	7105	7118	7131	7144	7157	7170	7183	7196	7209	7222	7235	7248	7261	7274	7287	7300	7313	7326	7339	7352	7365	7378	7391	7404	7417	7430	7443	7456	7469	7482	7495	7508	7521	7534	7547	7560	7573	7586	7599	7612	7625	7638	7651	7664	7677	7690	7703	7716	7729	7742	7755	7768	7781	7794	7807	7820	7833	7846	7859	7872	7885	7898	7911	7924	7937	7950	7963	7976	7989	8002	8015	8028	8041	8054	8067	8080	8093	8106	8119	8132	8145	8158	8171	8184	8197	8210	8223	8236	8249	8262	8275	8288	8301	8314	8327	8340	8353	8366	8379	8392	8405	8418	8431	8444	8457	8470	8483	8496	8509	8522	8535	8548	8561	8574	8587	8600	8613	8626	8639	8652	8665	8678	8691	8704	8717	8730	8743	8756	8769	8782	8795	8808	8821	8834	8847	8860	8873	8886	8899	8912	8925	8938	8951	8964	8977	8990	9003	9016	9029	9042	9055	9068	9081	9094	9107	9120	9133	9146	9159	9172	9185	9198	9211	9224	9237	9250	9263	9276	9289	9302	9315	9328	9341	9354	9367	9380	9393	9406	9419	9432	9445	9458	9471	9484	9497	9510	9523	9536	9549	9562	9575	9588	9601	9614	9627	9640	9653	9666	9679	9692	9705	9718	9731	9744	9757	9770	9783	9796	9809	9822	9835	9848	9861	9874	9887	9900	9913	9926	9939	9952	9965	9978	9991	10004	10017	10030	10043	10056	10069	10082	10095	10108	10121	10134	10147	10160	10173	10186	10199	10212	10225	10238	10251	10264	10277	10290	10303	10316	10329	10342	10355	10368	10381	10394	10407	10420	10433	10446	10459	10472	10485	10498	10511	10524	10537	10550	10563	10576	10589	10602	10615	10628	10641	10654	10667	10680	10693	10706	10719	10732	10745	10758	10771	10784	10797	10810	10823	10836	10849	10862	10875	10888	10901	10914	10927	10940	10953	10966	10979	10992	11005	11018	11031	11044	11057	11070	11083	11096	11109	11122	11135	11148	11161	11174	11187	11200	11213	11226	11239	11252	11265	11278	11291	11304	11317	11330	11343	11356	11369	11382	11395	11408	11421	11434	11447	11460	11473	11486	11499	11512	11525	11538	11551	11564	11577	11590	11603	11616	11629	11642	11655	11668	11681	11694	11707	11720	11733	11746	11759	11772	11785	11798	11811	11824	11837	11850	11863	11876	11889	11902	11915	11928	11941	11954	11967	11980	11993	12006	12019	12032	12045	12058	12071	12084	12097	12110	12123	12136	12149	12162	12175	12188	12201	12214	12227	12240	12253	12266	12279	12292	12305	12318	12331	12344	12357	12370	12383	12396	12409	12422	12435	12448	12461	12474	12487	12500	12513	12526	12539	12552	12565	12578	12591	12604	12617	12630	12643	12656	12669	12682	12695	12708	12721	12734	12747	12760	12773	12786	12799	12812	12825	12838	12851	12864	12877	12890	12903	12916	12929	12942	12955	12968	12981	12994	13007	13020	13033	13046	13059	13072	13085	13098	13111	13124	13137	13150	13163	13176	13189	13202	13215	13228	13241	13254	13267	13280	13293	13306	13319	13332	13345	13358	13371	13384	13397	13410	13423	13436	13449	13462	13475	13488	13501	13514	13527	13540	13553	13566	13579	13592	13605	13618	13631	13644	13657	13670	13683	13696	13709	13722	13735	13748	13761	13774	13787	13800	13813	13826	13839	13852	13865	13878	13891	13904	13917	13930	13943	13956	13969	13982	13995	14008	14021	14034	14047	14060	14073	14086	14099	14112	14125	14138	14151	14164	14177	14190	14203	14216	14229	14242	14255	14268	14281	14294	14307	14320	14333	14346	14359	14372	14385	14398	14411	14424	14437	14450	14463	14476	14489	14502	14515	14528	14541	14554	14567	14580	14593	14606	14619	14632	14645	14658	14671	14684	14697	14710	14723	14736	14749	14762	14775	14788	14801	14814	14827	14840	14853	14866	14879	14892	14905	14918	14931	14944	14957	14970	14983	14996	15009	15022	15035	15048	15061	15074	15087	15100	15113	15126	15139	15152	15165	15178	15191	15204	15217	15230	15243	15256	15269	15282	15295	15308	15321	15334	15347	15360	15373	15386	15399	15412	15425	15438	15451	15464	15477	15490	15503	15516	15529	15542	15555	15568	15581	15594	15607	15620	15633	15646	15659	15672	15685	15698	15711	15724	15737	15750	15763	15776	15789	15802	15815	15828	15841	15854	15867	15880	15893	15906	15919	15932	15945	15958	15971	15984	15997	16010	16023	16036	16049	16062	16075	16088	16101	16114	16127	16140	16153	16166	16179	16192	16205	16218	16231	16244	16257	16270	16283	16296	16309	16322	16335	16348	16361	16374	16387	16400	16413	16426	16439	16452	16465	16478	16491	16504	16517	16530	16543	16556	16569	16582	16595	16608	16621	16634	16647	16660	16673	16686	16699	16712	16725	16738	16751	16764	16777	16790	16803	16816	16829	16842	16855	16868	16881	16894	16907	16920	16933	16946	16959	16972	16985	16998	17011	17024	17037	17050	17063	17076	17089
----	----	----	----	----	----	----	----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------






FIGURE 6-12 AREAS OF CONTAMINATION BENEATH BUILDING 845

## REFERENCES

1. Oak Ridge National Laboratory. Radiological Survey of the E. I. DuPont de Nemours and Company, Deepwater, New Jersey, DOE/EV-000E/8, prepared for the U.S. Department of Energy, Washington, D.C., 1978.
2. Letter, J. Curry to J. Eastman. "Draft Radiological Survey Report DuPont Chambers Works Site," August 24, 1984.
3. Glenn, R.D., et al. "Radiation Measurement Capability for Decontamination to Unrestricted Use," paper presented at the 1982 International Decommissioning Symposium, Seattle, WA, October, 1982.
4. T. E. Myrick, et al. State Background Radioactive Levels: Measurements Taken during 1975-1979, ORNL Report ORNL/TM-7343, November 1981.
5. Letter, E. L. Keller to R. L. Rudolph. "Comments on the Radiological Survey Report for the Former Middlesex Sampling Plant, Middlesex, New Jersey and the Draft Radiological Survey Report for the DuPont Chambers Works Plant, Deepwater, New Jersey," September 11, 1984.
6. U.S. Department of Energy, Order 5480.1A. "Environmental Protection, Safety, and Health Protection Program for DOE Operations," Washington, DC.

Lot 2

DOE/OR/20722-22

---

Formerly Utilized Sites Remedial Action Program (FUSRAP)  
Contract No. DE-AC05-81OR20722

---

**RADIOLOGICAL SURVEY REPORT  
FOR THE DUPONT  
CHAMBERS WORKS PLANT**

Deepwater, New Jersey

---

March 1985



Bechtel National, Inc.  
Advanced Technology Division

---

— LEGAL NOTICE —

This report was prepared as an account of work sponsored by the United States Government. Neither the United States nor the United States Department of Energy, nor any of their employees, nor any of their contractors, subcontractors, or their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness or usefulness of any information, apparatus, product or process disclosed, or represents that its use would not infringe privately owned rights.

RADIOLOGICAL SURVEY  
OF THE  
E. I. DUPONT DE NEMOURS AND COMPANY  
CHAMBERS WORKS PLANT  
DEEPWATER, NEW JERSEY

MARCH 1985

Prepared for

UNITED STATES DEPARTMENT OF ENERGY  
OAK RIDGE OPERATIONS OFFICE  
Under Contract No. DE-AC05-81OR20722

By

Bechtel National, Inc.  
Advanced Technology Division  
Oak Ridge, Tennessee

Bechtel Job No. 14501

## ABSTRACT

During October and November 1983, a radiological survey was conducted in six separate areas of the DuPont Chambers Works Plant in Deepwater, New Jersey. The survey was performed as part of the Formerly Utilized Sites Remedial Action Program (FUSRAP), a U.S. Department of Energy effort to identify, clean up, or otherwise control sites where low-level radioactive contamination (exceeding current guidelines) remains from the early years of the nation's atomic energy program.

A 1977 radiological survey conducted by Oak Ridge National Laboratory had established that contamination existed at the site. The 1983 survey was necessary to define locations and boundaries of the contamination. The survey was conducted by the FUSRAP Program Management Contractor, Bechtel National, Inc., and its radiological subcontractor, Eberline Analytical Corporation (EAC).

Measurements taken during the 1983 radiological survey indicate that four of the six site areas surveyed are contaminated above current guidelines. In both soil and water samples, the major contaminant was found to be uranium-238. In some areas, contamination was found at depths greater than 3 m (9 ft), and in some cases contamination extended into the water table.

If remedial action were performed at the site, approximately 6300 m<sup>3</sup> (8200 yd<sup>3</sup>) of contaminated materials would require removal to decontaminate exterior areas. One building would require surface decontamination [approximately 50 m<sup>3</sup> (70 yd<sup>3</sup>) of material] or total demolition [approximately 2300 m<sup>3</sup> (3000 yd<sup>3</sup>) of material]. However, in the areas of subsurface contamination, measures currently enforced by DuPont to protect against the site's chemical contaminants are adequate to protect personnel from the low-level radioactive contamination. DuPont does not permit excavation in areas of known chemical contamination and this prohibition extends to low-level radioactive contamination. Additionally, DuPont has positive access controls to the site.

TABLE OF CONTENTS

	<u>Page</u>
Abbreviations	viii
1.0 Introduction and Summary	1
2.0 Site Description and History	3
2.1 Location and Description	3
2.2 Site History and Previous Radiological Surveys	3
2.3 Present Site Conditions	6
3.0 Health and Safety Plan	8
4.0 Survey Procedures	9
4.1 Field Survey Procedures	9
4.1.1 Measurements Taken and Methods Used	9
4.1.2 Sample Collection and Analyses	10
4.2 Building 845 Survey Procedures	18
4.2.1 Measurements Taken and Methods Used	18
4.2.2 Sample Collection and Analyses	22
5.0 Survey Results	23
5.1 Field Survey Results	23
5.1.1 Building 845 Area	24
5.1.2 Central Drainage Ditch	25
5.1.3 F Corral Parking Area	26
5.1.4 Building J-26 Area	27
5.1.5 East Burial Area	27

	<u>Page</u>
5.1.6 Lagoon A	28
5.2 Building 845 Survey Results	28
5.2.1 First Level	29
5.2.2 Second Level	30
5.2.3 Third Level	31
5.2.4 Fourth Level	32
6.0 Significance of Findings	47
6.1 Field Survey	47
6.1.1 Building 845 Area	47
6.1.2 Central Drainage Ditch	49
6.1.3 F Corral Parking Area	49
6.1.4 Building J-26 Area	50
6.1.5 East Burial Area	50
6.1.6 Lagoon A	53
6.2 Building 845 Survey	53
References	64



LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
2-1	Location of the DuPont Chambers Works Plant	4
2-2	Aerial Photograph of the DuPont Chambers Works Plant, Looking East	5
4-1	Boreholes and Sampling Locations in the Vicinity of Building 845	11
4-2	Borehole and Sediment Sample Locations, Central Drainage Ditch and Feeder Ditch	14
4-3	Boreholes and Sampling Locations, F Corral Area	15
4-4	Boreholes and Water Sampling Locations, Building J-26 Area	16
4-5	Borehole and Sampling Locations, East East Burial Area	17
4-6	Borehole and Sediment Sampling Locations, Lagoon A	19
4-7	Core Borings and Soil Sample Locations, Building 845 (Ground Floor)	21
6-1	Building 845 Area and Wooden Trough Requiring Remedial Action	46
6-2	F Corral Area Requiring Remedial Action	51
6-3	East Burial Area Requiring Remedial Action	52
6-4	Building 845, First Floor: Areas of Surface Contamination on Floor, Walls, and Floor/Wall Intersections	55
6-5	Building 845, First Floor Ceiling: Areas of Surface Contamination	56
6-6	Building 845, Second Floor: Areas of Contamination on Floor, Walls, and Floor/Wall Intersections	57
6-7	Building 845, Second Floor Ceiling: Areas of Surface Contamination	58
6-8	Building 845, Third Floor: Areas of Surface Contamination on Floor, Walls, and Floor/Wall Intersections	59

<u>Figure</u>	<u>Title</u>	<u>Page</u>
6-9	Building 845, Third Floor Ceiling: Areas of Surface Contamination	60
6-10	Building 845, Fourth Floor, Areas of Surface Contamination on Floor, Walls, and Floor/Wall Intersections	61
6-11	Building 845, Fourth Floor Ceiling: Areas of Surface Contamination	62
6-12	Areas of Contamination Beneath Building 845	63

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
5-1	Background Radiation Rates and Radionuclide Concentrations in Soil	33
5-2	Radionuclide Concentrations in the Delaware River	34
5-3	Residual Contamination Guidelines and Criteria for FUSRAP Sites	35
5-4	DuPont Chambers Works Site: Pre-Remedial Action Summary of Outdoor Measurement Results	36
5-5	DuPont Chambers Works Site: Gamma Spectrometry of Soil Samples	37
5-6	DuPont Chambers Works Site: Gamma Spectrometry of Sediment Samples	42
5-7	DuPont Chambers Works Site: Gamma Spectrometry of Water Samples	43
5-8	DuPont Chambers Works Site: Pre-Remedial Action Summary of Building 845 Measurement Results	45

## ABBREVIATIONS

cm	centimeter
cm <sup>2</sup>	square centimeter
cpm	counts per minute
dpm/cm <sup>2</sup>	disintegrations per minute per square centimeter
ft	foot
ha	hectare
l	liter
m	meter
μR/h	microroentgens per hour
mg	milligram
mrad/h	millirads per hour
pCi/g	picocuries per gram
pCi/l	picocuries per liter
yd <sup>3</sup>	cubic yards

## 1.0 INTRODUCTION AND SUMMARY

This report describes the procedures, results, and significance of findings for a radiological survey conducted during October and November 1983 at the DuPont Chambers Works Plant in Deepwater, New Jersey. The survey was conducted as part of the Formerly Utilized Sites Remedial Action Program (FUSRAP). FUSRAP is a U. S. Department of Energy (DOE) program to identify, clean up, or otherwise control sites where low-level radioactive contamination, at levels above current guidelines, remains from the early years of the nation's atomic energy program. Under contract to DOE, Bechtel National, Inc., (BNI) acts as the Program Management Contractor (PMC) for FUSRAP.

An earlier radiological survey, performed in 1977 by Oak Ridge National Laboratory (ORNL), established that contamination existed at the site and resulted in its designation as a FUSRAP site (Ref. 1). The 1983 radiological survey was necessary to define the locations and boundaries of the contamination identified in the ORNL survey, as a prelude to possible remedial action at the site. BNI and its radiological subcontractor, Eberline Analytical Corporation (EAC), conducted the 1983 survey.

Six separate areas were surveyed throughout the site: Building 845 (interior and exterior); Central Drainage Ditch; F Corral Parking Area; Building J-26 Area; East Burial Area and Lagoon A.

Surface and subsurface measurements in the J-26 and Lagoon A areas indicate the areas are not contaminated above guidelines and do not require remedial action. The remaining areas surveyed were contaminated above guidelines. In some areas, subsurface contamination exists at depths greater than 3 m (9 ft). Due to the high water table under the DuPont site, contamination at depths below the water line could not be quantified. The major on-site contaminant was found to be uranium-238, both in water and soil samples.

Groundwater uranium-238 concentrations collected from the F Corral Parking area ranged from background levels to over 105,105 pCi/l. Contamination in soil was found to exist in stratified layers down to the water table.

External-gamma radiation levels ranged from 11.2 to 27.8  $\mu\text{R/h}$ . These levels are above the normal background level for the DuPont area; however, they are below the DOE guideline of 60  $\mu\text{R/h}$  above background.

The survey also determined the extent of contamination present in Building 845. The building was surveyed for beta-gamma and alpha contamination; elevated dose rates and above-guideline alpha surface contamination were measured on all four levels of the building. First floor corehole loggings indicated areas of contamination beneath the building up to depths of 1.2 m (4 ft).

If remedial action were to be performed at the site, a total of approximately 6300  $\text{m}^3$  (8200  $\text{yd}^3$ ) of contaminated materials would have to be excavated from the site's exterior areas. In addition, surface decontamination of Building 845 would result in approximately 50  $\text{m}^3$  (70  $\text{yd}^3$ ) of contaminated material. Total demolition of Building 845 would result in approximately 2300  $\text{m}^3$  (3000  $\text{yd}^3$ ) of contaminated material. In areas of subsurface radioactive contamination, measures presently required by DuPont to protect against chemical contaminants are adequate to protect personnel from the low-level radioactive contamination. DuPont does not permit excavation in areas of known chemical contamination and this prohibition extends to low-level radioactive contamination. Additionally, DuPont has positive access controls to the site.

## 2.0 SITE DESCRIPTION AND HISTORY

### 2.1 LOCATION AND DESCRIPTION

The DuPont Chambers Works Plant is an active chemical plant which primarily manufactures organic chemicals. Products include fluorinated hydrocarbons (Freon), petroleum chemicals (tetraalkyl lead), elastomers (Viton and Hytrel), specialty chemicals (Zepel and organic titanates), and aromatics (phenylene diamines). The Chambers Works covers approximately 283 ha (700 acres) in Pennsville and Carneys Point townships on the southeast shore of the Delaware River, adjacent to the residential community of Deepwater, New Jersey. The site location is illustrated in Figure 2-1.

The following areas were investigated as part of the site radiological survey: Building 845 interior and exterior areas, F Corral (demolished Building 708, now a parking area), Building J-26 Area, East Burial Area, sections of the Central Drainage Ditch, and Lagoon A. These areas are shown in an aerial photograph of the site presented in Figure 2-2.

### 2.2 SITE HISTORY AND PREVIOUS RADIOLOGICAL SURVEYS

Operations involving uranium at the Chambers Works began in 1942. DuPont was conducting experiments with uranium hexafluoride under contract to the U. S. Office of Scientific Research and Development when the Manhattan Engineer District (MED) was established. As a part of its work on the MED program, DuPont worked on developing a process for converting uranium oxide to produce uranium tetrafluoride and small quantities of uranium metal. Other research activities were also performed.

All MED activities were transferred to the Atomic Energy Commission (AEC) when that agency was created by Congress in 1946. DuPont continued its research activities for AEC until late 1947.




Figure 2-1  
Location of the DuPont Chambers Works Plant





FIGURE 2-2 AERIAL PHOTOGRAPH OF THE DUPONT CHAMBERS WORKS PLANT, LOOKING EAST

In 1948 and 1949, the AEC conducted radiological surveys and decontamination activities at the site. These activities included sandblasting, vacuuming, and washing building surfaces. Following a radiological survey based on then-existing criteria, AEC released the buildings back to DuPont in 1949.

In March 1977, another radiological survey of the site was conducted by ORNL as part of FUSRAP. The 1977 survey results indicated that elevated concentrations of uranium were present in rubble from the operations building and in some surface and subsurface soil samples. Alpha and beta-gamma contamination levels in some areas of Building 845 were above present federal guidelines (Ref. 1). The 1977 survey concluded that, under current conditions of site use, this contamination does not cause employees working at the site to receive radiation exposures appreciably different from those due to background radiation. However, under different conditions of use (e.g., actions which involved agitation or abrasion of dry contaminated surfaces), the potential for low-level radiation exposures to employees and the public could result.

Based on the 1977 survey results, the DOE Assistant Secretary for Environment determined that the DuPont site warranted remedial action under FUSRAP. In its role as PMC for FUSRAP, BNI conducted the 1983 survey to more accurately define the boundaries and depth of contamination at the site.

### 2.3 PRESENT SITE CONDITIONS

Of the three buildings used for MED activities, only Building 845 remains. Building 845 is presently used as a miscellaneous stores warehouse. The other two buildings were demolished from 1945 to 1953.

In 1945, part of Building 708 was demolished and removed from the site. In 1953, the remainder of Building 708 was removed along with several feet of underlying earth. Materials removed in 1953 were

disposed of in the Lagoon A area (Ref. 2). A parking facility, F Corral, is now located on the location of Building 708.

Following release of the site by the AEC in 1949, Building J-16 was demolished and disposed of in the Lagoon A area (Ref. 2). A new building, J-26, now stands at this location.

The East Burial Area contains some equipment from the demolition of Building 845. In addition, various chemical wastes and small amounts of New Jersey-approved low-level radioactive material have been stored in this area.

The Central Drainage Ditch is in approximately the same location as in the 1940s. The primary purpose of the ditch is to carry residual wastes from chemical operations. In the past, residual wastes from Building 845 were discharged into a wooden trough located east of the building. The trough dumped into the Central Drainage Ditch approximately 150 feet north of Building 845. The Central Drainage Ditch flows toward the northeast, adjacent to the northwest corner of Building 845, and drains out into the eastern corner of Lagoon A. The composite from Lagoon A is then pumped into the on-site water treatment facility for chemical processing of the waste.

### 3.0 HEALTH AND SAFETY PLAN

The presence of various chemicals used and manufactured at the site posed potential health hazards to employees involved in the sampling and handling of subsurface soil and water samples. These conditions necessitated the use of special measures to protect employees involved with the subsurface investigations and a Health and Safety Plan was designed by BNI.

The primary components of the Health and Safety Plan were: pre-work medical examinations; safety education in handling and sampling precautions; personal protective equipment consisting of gloves, shoe covers, disposable coveralls, eye protection, hard hats, and butyl-rubber air-supplied suits; urine sampling; and follow-up medical examinations performed upon completion of the survey. Controls required for chemical protection were reviewed and approved by DuPont. All drilling and soil sampling in the Central Drainage Ditch, Lagoon A, and East Burial Area, under direction from DuPont, were carried out with drillers and support personnel attired in one-piece, air-supplied butyl-rubber suits. In addition, two 30-minute self-contained breathing apparatus air cylinders were used during the sediment sampling conducted west and northwest of Building 845 along secondary drainage ditches.

During the radiological survey, the FUSRAP BNI Safety Supervisor was present and supervised operations. There were no recorded illnesses or injuries involving any person working on this survey. Medical examinations given at the conclusion of the survey showed no evidence of personnel having been exposed to hazardous chemicals.

## 4.0 SURVEY PROCEDURES

### 4.1 FIELD SURVEY PROCEDURES

The survey grid system for the site, exclusive of the grid for the interior of Building 845, was established by a civil surveyor during October 1983 and was based on the New Jersey state geological survey. The areas surveyed on a 15-m (50-ft) grid included Lagoon A, East Burial Area, Central Drainage Ditch, F Corral parking lot, areas around Building J-26, and areas around Building 845. The radiological measurements taken and the methods used for taking the measurements are described in the following subsections.

#### 4.1.1 Measurements Taken and Methods Used

Within the grid blocks of all field areas, beta-gamma measurements were made on the ground surfaces at 6-m (20-ft) intervals. The measurements were made using a pancake geometry (Geiger-Mueller) probe coupled to a digital ratemeter/scaler [Eberline Instrument Corporation (EIC) models HP-210 and PRS-1, respectively].

Near-surface gamma measurements were made 30 cm (12 in.) above the ground surface at 6-m (20-ft) intervals within the grid using a 5- x 5-cm (2- x 2-in.) sodium-iodide (NaI) detector. This detector (EIC model SPA-3) was mounted in a probe assembly surrounded with a conical lead shield to reduce the gamma intensity through the sides, thus producing a downward directional response.

Gamma exposure rates at 1 m (3 ft) above the ground were measured using a pressurized ionization chamber (PIC) with a response to gamma radiation that is proportional to exposure in roentgens. Readings were made at 15-m (50-ft) intervals above all open area surfaces in all gridded areas (gamma exposure rate measurements were not taken in the J-26 area).

Boreholes 15 cm (6 in.) in diameter were drilled in all areas. Material from the boreholes was returned to the holes. Drilling was conducted in accordance with safety precautions described in Section 3.0. The locations and number of holes in each area were based on near-surface gamma measurements made in the area and the historical data on the site. A section of 10-cm (4-in.) diameter PVC plastic pipe with a closed bottom was inserted into each hole as a temporary sleeve to allow gamma logging. A 5- x 5-cm (2- x 2-in.) NaI (Tl) gamma scintillation detector (SPA-3 NaI crystal in a modified probe used specifically for borehole logging), coupled with a PRS-1 ratemeter/scaler, was lowered into the pipe to obtain a profile of the depth of contamination. Timed gamma measurements were made at 15-cm (6-in.) vertical intervals. By calibrating these measurements with the results from laboratory analyses of soil samples, borehole loggings provide a reliable estimate of radionuclide concentrations in subsurface soils.

#### 4.1.2 Sample Collection and Analyses

##### Building 845 (Exterior) Area

In the area surrounding Building 845, in addition to the boreholes drilled for gamma logging, undisturbed (Shelby tube) soil samples, water samples, and sediment samples were taken. The locations of the boreholes and of each type of sample taken are illustrated in Figure 4-1. In some cases, more than one type of sample was taken at the same location.

Based on the gamma logs, four Shelby tube soil samples were taken in areas which had revealed the most significant subsurface deposits of radioactivity. The soil samples extended to 30 cm (1 ft) below the depth of the radionuclide deposits as indicated by the gamma logging. Shelby tubes, 61 cm long and 7.6 cm in diameter (24 x 3 in.) were used to collect these soil samples. The soil in the tubes was extruded in 10-cm (4-in.) sections, placed in 500-ml plastic containers, identified, and packaged. The samples were




FIGURE 4-1 BOREHOLES AND SAMPLING LOCATIONS IN THE VICINITY OF BUILDING 845

shipped to DOE's Niagara Falls Storage Site where they were dried, pulverized, and homogenized before they were analyzed for uranium-238. The samples were analyzed by EAC personnel using the high resolution gamma spectrometry system in the FUSRAP in situ van (Ref. 3). Each sample was analyzed for 10 minutes using an intrinsic germanium detector housed in a lead counting cave lined with cadmium and copper. The detector is coupled to a computer base pulse height analyzer. Following the initial gamma spectrometry analysis of the soil samples, aliquots of selected samples were taken and sent to the EAC laboratory in Albuquerque, New Mexico, for radiochemical analysis. This analysis was performed to measure the concentrations of uranium-234 and uranium-235 in the samples and also to verify the uranium-238 analysis.

Water samples also were collected from all boreholes in the Building 845 area whenever the water table was reached. Water table depth proved to vary from 1 to 1.3 m (3 to 4 ft). Water samples were collected in 1-liter plastic sample bottles, clearly marked, and identified. (Chemical contamination of the water samples was evident through both odor and consistency of the liquid. For handling precautions, analytical laboratory personnel were advised of the possibility of chemical contamination.) All water samples collected were shipped to the EAC Albuquerque laboratory for analysis for uranium-234, uranium-235, and uranium-238 by radiochemical techniques.

Ten sediment samples were collected at 15-m (50-ft) intervals in the wooden drainage trough east of Building 845. Prior to analysis, all samples were heated on-site in an oven (at the in situ van) to 600°C (1112°F) to remove organics and eliminate possible chemical exposures during handling. Sediment samples then were analyzed using the same methods used for soil samples.

#### Central Drainage Ditch

Ten sediment samples were collected from the Central Drainage Ditch between grid location N4700-2485 and N5150-E3220. Sediment sampling



locations are shown in Figure 4-2. Sediment samples were collected primarily utilizing foot and traffic bridges and in areas of the ditch that were accessible during drilling operations.

Four sediment samples were collected at 15-m (50-ft) intervals from the Feeder Ditch. All sediment samples taken were heated to 600°C (1112°F) to remove organics and to eliminate possible chemical exposures during handling. Samples were then analyzed for radioactivity by the same methods used for soil samples.

#### F Corral Parking Area

Two Shelby tube soil samples were collected in the F Corral parking area. Samples were collected and analyzed in the same manner as described earlier. Water samples also were collected from boreholes in the F Corral when applicable. Water was collected and analyzed as described earlier. Sampling locations are shown in Figure 4-3.

#### Building J-26 Area (Formerly J-16)

Water samples were collected from boreholes, when possible, in the Building J-26 area. Boreholes and water sample locations are shown in Figure 4-4.

#### East Burial Area

In the East Burial Area, two locations were selected for Shelby tube soil samples. These samples were taken in the immediate vicinity of the two boreholes which revealed the most significant subsurface deposits of radioactivity. Water samples also were collected from boreholes when possible. Sampling locations are shown in Figure 4-5.







FIGURE 4-2 BOREHOLE AND SEDIMENT SAMPLE LOCATIONS, CENTRAL DRAINAGE DITCH AND FEEDER DITCH



**LEGEND**

- BOREHOLE
- ⊗ BOREHOLE & WATER SAMPLE
- ⊠ BOREHOLE, SHELBY TUBE, & WATER SAMPLE

FIGURE 4-3 BOREHOLES AND SAMPLING LOCATIONS, F CORRAL AREA



**LEGEND**

- BOREHOLE
- ⊗ BOREHOLE & WATER SAMPLE

FIGURE 4-4 BOREHOLES AND WATER SAMPLING LOCATIONS, BUILDING J-26 AREA




FIGURE 4-5 BOREHOLE AND SAMPLING LOCATIONS, EAST BURIAL AREA

## Lagoon A

Two sediment samples were taken from Lagoon A and were processed using the same method used on the sediment samples taken from central drainage ditch. Sampling locations are shown in Figure 4-6.

### 4.2 BUILDING 845 SURVEY PROCEDURES

The grid system used for Building 845 consisted of a 1.8- x 1.8-m (6- x 6-ft) grid established on the walls, floors, and ceilings. Building 845 presently has four floors. During early plant operation this was not the case. The building contained equipment that reached from the ground floor to the upper parts of the building, and upper floors were only partial -- to varying extents. The present upper floors contain original flooring and recently added "new" flooring. For the purposes of this radiological survey, each floor of Building 845 was gridded independently and random measurements were made on the new floor areas to verify that these areas were not contaminated.

#### 4.2.1 Measurements Taken and Methods Used

The surface of each floor of Building 845 was monitored for beta-gamma radiation, with a total of five measurements made in each grid segment on the original floor areas and random measurements made on the new floor areas. Measurements were made with a thin window ( $7 \text{ mg/cm}^2$ ) Geiger-Mueller detector with digital readout (EIC model HP-210/PRS-1). The HP-210 detector was in contact with floor surfaces. Five 30-second counts were obtained and recorded in each grid block. Measurements were made along the floor/wall intersection and along new and old floor joints at 3-ft intervals.

Wall surface measurements were obtained in the same manner as floor surface measurements. A 1.8-m (6-ft) grid was used from the floor to a height of 1.8 m (6 ft) above the floor. For upper walls the




FIGURE 4-6 BOREHOLE AND SEDIMENT SAMPLING LOCATIONS, LAGOON A

grid was increased to 5 m (16 ft). All horizontal surfaces, such as window sills, also were scanned and radiation levels were recorded. All wall measurements are referenced to the floor grid numbering system.

Ceilings were monitored in the same manner as floors and walls. Measurement points were selected on horizontal and vertical surfaces such as beams, pipes, and ledges in each building unit (rooms, halls). All ceiling measurements were referenced to the floor grid numbering system.

Alpha radiation measurements were made at the same locations as beta-gamma measurements, using a 59-cm<sup>2</sup> zinc sulfide (ZnS) scintillation detector with digital readout (EIC models AC-3/PRS-1).

Based on results of the 1977 ORNL survey and surface beta-gamma measurements conducted during the 1983 building survey, 27 locations were identified for coring through the ground floor concrete slab. Locations are illustrated in Figure 4-7. Typical cores indicated the concrete slab was 10 to 15 cm (4 to 6 in.) thick, with a spread foundation footing 15 to 45 cm (6 to 18 in.) deep under columns.

A sealed drain trench was located in core boring number 4 (CB-4) and CB-6. The trench extended approximately 11 m (35 ft) south of CB-6 and was an average 45 cm (1.5 ft) deep. In CB-6, a 7.5-cm (3-in.) diameter steel drain pipe was located in the sealed trench at a depth of 22 to 30 cm (9 to 12 in.). This pipe contained elevated levels of radiological contamination in a dry, yellow powder form.

Augering techniques inside the building varied from methods used in the exterior areas of the plant due to limited overhead clearances. A 15-cm (6-in.) diameter hand auger was used to remove soil in 10-cm (4-in.) increments, allowing sufficient clearance for insertion of the PVC pipe for downhole gamma logging.






FIGURE 4-7 CORE BORINGS AND SOIL SAMPLE LOCATIONS, BUILDING 845 (GROUND FLOOR)

#### 4.2.2 Sample Collection and Analysis

Shelby tube soil samples were collected inside Building 845 near all core boring locations. These samples were collected and analyzed using the same methods described in Subsection 4.1.2 of this report. Water samples also were taken from the borings when possible and processed as noted in Subsection 4.1.2.

During this radiological survey, four particulate air samplers (EIC Model RAS-1) were employed. These samplers, one on each floor, ran continuously and sampling filters were exchanged daily. Composite samples for each location were sent to the NFSS, where they were analyzed for gross alpha and beta-gamma.

Two composite dust samples also were collected from the first and fourth floors of Building 845. These samples were analyzed for uranium-238 and radium-226 at the EAC Albuquerque Laboratory.

## 5.0 SURVEY RESULTS

### 5.1 FIELD SURVEY RESULTS

All direct field measurements and laboratory results in this report represent gross readings; background measurements and concentrations have not been subtracted.

Background measurements were made in 1977 as part of the ORNL survey. At six locations on the DuPont property, at distances ranging from 300 to 1800 m (1000 to 6000 ft) from the nearest area in which radioactive materials were handled or stored, surface soil samples were taken to determine radionuclide concentrations. Concentrations of uranium-238 in the background soil samples ranged from 0.3 to 4.0 pCi/g and averaged 1.8 pCi/g.

External gamma measurements 1 m (3 ft) above the ground were made at the same six points. Background external gamma readings ranged from 3 to 6  $\mu\text{R/h}$  and averaged 4.5  $\mu\text{R/h}$  (Ref. 1). Background radiation rates and radionuclide concentrations in soil are summarized in Table 5-1, at the end of Section 5.0.

In addition to these background data, a series of additional external gamma exposure rate measurements were made throughout the state of New Jersey. The average statewide measurement was 6.1  $\mu\text{R/h}$  (Ref. 4).

During the 1977 ORNL survey, three river water samples, which were assumed to represent background concentrations, were collected from the Delaware River. The results of these samples are presented in Table 5-2.

Background near-surface gamma measurements for the DuPont site were made during the 1983 BNI survey using an EIC SPA-3 detector. These measurements showed the site's near-surface gamma reading to be 2500 cpm.

Current DOE guidelines for radionuclide concentrations in soil, sediment and water are presented in Table 5-3.

In all field areas, measurements were taken for near-surface gamma, surface beta-gamma, and gamma exposure rates 1 m (3 ft) above the ground (gamma exposure rates were not measured in the J-26 area). Boreholes were drilled and gamma logging was performed, and undisturbed (Shelby tube) soil samples, water samples, and sediment samples were taken in each area as appropriate.

The results of near-surface gamma, surface beta-gamma, and gamma exposure rates are summarized in the following subsections. A summary table, Table 5-4, is presented at the end of Section 5.0. Analysis results for soil, sediment, and water samples also are summarized in the following sections, with specific results reported in Tables 5-5 (soil), 5-6 (sediment), and 5-7 (water) at the end of Section 5.0.

#### 5.1.1 Building 845 Area

Near-surface gamma readings taken in the Building 845 area ranged from 1770 to 12,246 cpm. Only four surface areas east of Building 845 exhibited readings greater than twice background. All beta-gamma measurements were below the DOE guideline of 0.20 mrad/h dose rate averaged over one square meter.

Gamma exposure rates in the area ranged from 11.6 to 27.8  $\mu\text{R}/\text{h}$ . As noted earlier, the overall site background rate measured by ORNL is 4.5  $\mu\text{R}/\text{h}$ . The DOE criteria for continuous exposure to an individual in the general population is 60  $\mu\text{R}/\text{h}$  above background.

Twenty-five boreholes, ranging in depth from 1.4 to 2.8 m (4.5 to 9 ft) were drilled in the area around Building 845. Borehole gamma logging then was performed to indicate general depth and concentrations of contamination. When possible, the borehole gamma loggings were correlated with undisturbed (Shelby tube) soil samples

analyses, relating the gamma detector's cpm response to the specific radionuclide concentration in picocuries per gram (pCi/g).

Due to the high water table encountered under the DuPont site, in many instances soil samples could not be collected. However, four Shelby tube soil samples were taken in the area east of Building 845 (refer to Figure 4-1). Specific analysis results are presented in Table 5-5, which lists the samples by coordinates and depth. The results indicate uranium is the major contaminant in the Building 845 exterior area, with levels ranging from 0.63 to 7398.0 pCi/g. The DOE remedial action guideline for uranium is 150 pCi/g.

Ten sediment samples were collected from the drainage trough located east of Building 845. Sampling locations are shown in Figure 4-1. All samples were analyzed for uranium-238, and concentrations ranged from 1.9 to 255.6 pCi/g. Selected samples also were analyzed for uranium-234, uranium-235, thorium-232, and radium-226. Results are given in Table 5-6. All results were below the DOE guidelines for these radionuclides (Ref. 5).

Twenty-one water samples were collected from boreholes in the area around Building 845. These samples were analyzed for total uranium. Results, given in Table 5-7, range from 1.5 to 11,712.0 pCi/l.

#### 5.1.2 Central Drainage Ditch

Near-surface gamma measurements and beta-gamma measurements were made along both sides of the Central Drainage Ditch and the Feeder Ditch. Near-surface gamma readings ranged from 1806 to 14,532 cpm. Three measurements taken in the southwest portion of the Feeder Ditch had readings greater than twice background. All beta-gamma dose rates were below the DOE guideline.

Gamma exposure rates in the area of the Central Drainage Ditch ranged from 12.8 to 15.4  $\mu$ R/h. These measurements are elevated above natural background but are below the DOE guideline of 60  $\mu$ R/h.

Eleven boreholes were drilled 1.8 to 2.6 m (6 to 8.5 ft) deep along the sides of the Central Drainage Ditch (refer to Figure 4-2). Boreholes were gamma logged, and elevated measurements were detected along both sides of the ditch. All measurements were below but near the guideline limit.

Sediment samples were collected from 10 locations in the Central Drainage Ditch and 4 locations in the Feeder Ditch. These samples were analyzed for uranium-234, -235, and -238. Results ranged from 0.90 to 4.10 pCi/g for uranium-238, 1.20 to 1.90 pCi/g for uranium-234, and 0.04 to 0.15 pCi/g for uranium-235. Complete results are given in Table 5-6. All results were below the DOE guidelines.

### 5.1.3 F Corral Parking Area

Near-surface gamma measurements and beta-gamma measurements were made in the F Corral parking area at 6-m (20-ft) intervals. Near-surface gamma readings ranged from 1608 to 5020 cpm. All beta-gamma dose rates were below the DOE guideline. Gamma exposure rates in the F Corral parking area ranged from 11.6 to 13.8  $\mu$ R/h.

Nineteen boreholes ranging from 0.6 to 2.7 m (2 to 9 ft) in depth were drilled in the F Corral area (refer to Figure 4-3). Based on gamma logs, subsurface contamination is indicated in layers to a depth greater than 2.7 m (9 ft).

Two Shelby tube soil samples were collected from the F Corral, and sample results are given in Table 5-5 by depth and coordinate. Uranium-238 was the major contaminant found in the parking area, with concentrations ranging from 0.90 to 4347 pCi/g.

Eleven water samples were collected from boreholes located in the F Corral. These samples were analyzed for total uranium. Results, given in Table 5-7, ranged from 1.50 to 105,105 pCi/l.

#### 5.1.4 Building J-26 Area

In the Building J-26 area, near-surface gamma measurements ranged from 1568 to 4334 cpm. Beta-gamma dose rates were below the DOE guideline.

Six boreholes were drilled in the area around Building J-26 (refer to Figure 4-4), and one water sample was collected. The total uranium concentration of the sample was 13.51 pCi/l. Analysis results are given in Table 5-7.

#### 5.1.5 East Burial Area

Near-surface gamma readings in the East Burial area ranged from 1212 to 17,878 cpm. Three measurements exceeded normal background levels. All beta-gamma dose rates were below the DOE guideline. Gamma exposure rates in the East Burial area ranged from 12.2 to 15.0  $\mu$ R/h.

Twenty boreholes were drilled in the East Burial area (refer to Figure 4-5). Gamma loggings indicate contamination exists in layers to depths greater than 2.6 m (8.5 ft). Higher count rates were observed in the boreholes drilled adjacent to the road.

Two Shelby tube soil samples were collected in the East Burial area, and samples were analyzed for uranium-238, thorium-232, and radium-226. Uranium-238 was the major contaminant found, with concentrations ranging from 297 to 20,810 pCi/g. Both sampling locations also showed concentrations of radium-226 above the DOE guideline, with concentrations ranging from 0.19 to 27.8 pCi/g. All thorium-232 concentrations were below the DOE guideline. Complete results are given in Table 5-5. Due to the high water table, subsurface soil samples could not be collected below 1 m (3 ft).

Groundwater samples were collected from two locations at a depth of 90 cm (36 in.). Water samples were analyzed for total uranium. Both samples had uranium-238 concentrations below the DOE guideline.

### 5.1.6 Lagoon A

In the Lagoon A area, near-surface gamma measurements ranged from 1566 to 3436 cpm. All beta-gamma dose rates were below the DOE guideline. Gamma exposure rates ranged from 11.2 to 15.8 uR/h.

Ten boreholes were drilled in the Lagoon A area (refer to Figure 4-6). Gamma loggings exhibited readings above background but below the guideline.

A surface water sample was collected from Lagoon A. The total uranium concentration in the sample was 4.20 pCi/l. Results are given in Table 5-7.

## 5.2 BUILDING 845 SURVEY RESULTS

All building survey measurements in this report represent gross readings; background measurements have not been subtracted. Beta-gamma dose-rate measurements taken on the DuPont site in buildings that have not been contaminated with radioactive materials were less than 0.03 mrad/h (Ref. 1). DOE guidelines for the release of property for unrestricted use state that beta-gamma dose rates at 1 cm from the surface shall not exceed 0.2 mrad/h (averaged over one square meter) and 1.0 mrad/h maximum in an area not greater than 100 cm<sup>2</sup> (Ref. 5). The guidelines also state that alpha surface contamination levels shall not exceed 1000 dpm/100 cm<sup>2</sup> average and 3000 dpm/100 cm<sup>2</sup> maximum when natural uranium is known to be the contaminant.

Results of measurements for beta-gamma dose rates and alpha contamination taken in Building 845 are summarized in the following subsections. More detailed results are presented in summary form in Table 5-8. Results for soil and water samples are summarized in the following sections, with specific results reported in Tables 5-5 (soil) and 5-7 (water).



While work was being performed inside Building 845, air particulate samples were taken. All results were within the DOE guideline for gross alpha of  $0.1 \text{ pCi/m}^3$  (for uncontrolled areas) (Ref. 6).

#### 5.2.1 First Level

A total of five measurements were made for beta-gamma and alpha contamination in each floor grid block. Average and maximum values per grid block are recorded in this report. The floor beta-gamma dose rates per grid block ranged from 0 to 4.54 mrad/h. Alpha measurement averages ranged from 0 to 6819 dpm/100  $\text{cm}^2$ , with a maximum reading of 26,544 dpm/100  $\text{cm}^2$ .

Floor/wall intersections were surveyed in 1-m (3-ft) increments for beta-gamma and alpha contamination. Beta-gamma dose rate averages ranged from 0 to 6.05 mrad/h, with a maximum reading of 8.88 mrad/h. Alpha measurement averages ranged from 0 to 10,621 dpm/100  $\text{cm}^2$ , with a maximum reading of 18,041 dpm/100  $\text{cm}^2$ .

Beta-gamma dose rates measured on the ceiling ranged from 0 to 4.78 mrad/h. Alpha measurements ranged from 0 to 5568 dpm/100  $\text{cm}^2$ . Beta-gamma and alpha measurement results are summarized in Table 5-8.

Twenty-seven coreholes were drilled through the first floor of Building 845. Locations are shown in Figure 4-7. In several locations, the auger hit the spread footings of the building's foundation. Thus, the corehole depths ranged from 0.5 to 2 m (1.5 to 6.0 ft). Eighteen boreholes indicated elevated gamma readings.

Soil samples were collected at all corehole locations and were analyzed for uranium-238, thorium-232, and radium-226. The major contaminant was uranium-238, with concentrations ranging from 0.70 to 8334 pCi/g. Thorium-232 and radium-226 concentrations were below the DOE criteria limit. Several samples were selected for uranium-234 and uranium-235 analysis, and concentrations were below guidelines. Results are given in Table 5-5.

Beta-gamma and alpha measurements also were made on accessible lower wall areas during the survey. Beta-gamma dose rates ranged from 0.05 to 10.92 mrad/h. Alpha measurements ranged from 0 to 9068 dpm/100 cm<sup>2</sup>.

Floor/wall intersections and the new floor/old floor intersections also were also surveyed. Beta-gamma dose rate averages ranged from 0.01 to 2.16 mrad/h, with a maximum reading of 2.77 mrad/h. All alpha measurements were below the guideline.

On the ceiling, beta-gamma dose rates ranged from 0.02 to 4.87 mrad/h. Alpha measurements ranged from 8 to 3992 dpm/100 cm<sup>2</sup>.

Results of second level readings are summarized in Table 5-8.

### 5.2.3 Third Level

Beta-gamma and alpha measurements were taken on the old floor areas of the third level, and new floor areas were spot checked for contamination. Beta-gamma dose-rate averages ranged from 0 to 1.40 mrad/h, with a maximum reading of 2.38 mrad/h. Alpha measurement averages ranged from 0 to 1017 dpm/100 cm<sup>2</sup>.

On the lower walls, beta-gamma dose rate averages ranged from 0.08 to 2.84 mrad/h, with a maximum reading of 2.84 mrad/h. Alpha measurements ranged from 37 to 3076 dpm/100 cm<sup>2</sup>.

At floor/wall intersections and new floor/old floor intersections, beta-gamma dose rates ranged from 0 to 0.68 mrad/h, with a maximum reading of 0.98 mrad/h. Alpha measurements ranged from 0 to 1930 dpm/100 cm<sup>2</sup>, with a maximum reading of 2599 dpm/100 cm<sup>2</sup>.

On the third level ceiling, beta-gamma dose rate measurements ranged from 0.02 to 1.49 mrad/h, with a maximum reading of 7.05 mrad/h. Alpha measurement averages ranged from 8 to 1347 dpm/100 cm<sup>2</sup>.

TABLE 5-1  
 BACKGROUND RADIATION RATES AND RADIONUCLIDE  
 CONCENTRATIONS IN SOIL

Location	Gamma Exposure Rate at 1 m ( $\mu$ R/h)	Radionuclide Concentrations (pCi/g)			
		U-238	Ra-226	Ac-227	Th-232
1	4	1.5	0.8	not found	0.7
2	4	1.9	0.5	0.3	0.6
3	6	4.0	0.6	2.2	0.7
4	6	1.6	0.9	not found	1.0
5	3	0.3	0.2	not found	0.3
6	4	1.8	0.8	not found	0.8
Averages	4.5	1.8	0.6	0.4	0.7

Source: ORNL (Ref. 1)

TABLE 5-2  
 RADIONUCLIDE CONCENTRATIONS IN THE DELAWARE RIVER

Location	Radionuclide Concentrations (pCi/ml)			
	U-238	Ra-226	Th-230	Pb-210
W-1	$1.5 \times 10^{-3}$	$9 \times 10^{-6}$	$1.7 \times 10^{-5}$	$9 \times 10^{-4}$
W-2	$1.1 \times 10^{-3}$	$9 \times 10^{-6}$	$1.5 \times 10^{-5}$	$9 \times 10^{-4}$
W-3	$4.3 \times 10^{-4}$	$2.3 \times 10^{-5}$	$3.2 \times 10^{-5}$	$4.5 \times 10^{-4}$

Source: ORNL (Ref. 1)

TABLE 5-4  
 DUPONT CHAMBERS WORKS SITE: PRE-REMEDIAL ACTION  
 SUMMARY OF OUTDOOR MEASUREMENT RESULTS

Measurement Location and Type <sup>a</sup>	Units	Number of Measurements Made	Range	Normal Background (BKG)
<u>Building 845 Area</u>				
Near-surface gamma	cpm	142	1770-12246	2,500
Beta-gamma dose rates	mrad/h	142	BKG - 0.08	0.02
External gamma exposure rates	μR/h	31	11.6 - 27.8	4.5
<u>Feeder Ditch and Central Drainage Ditch</u>				
Near-surface gamma	cpm	73	1806-14532	2,500
Beta-gamma dose rates	mrad/h	73	BKG-0.13	0.02
External gamma exposure rates	μR/h	12	12.8 - 15.4	4.5
<u>F Corral Parking Area</u>				
Near-surface gamma	cpm	203	1608-5020	2,500
Beta-gamma dose rates	mrad/h	203	BKG-0.14	0.02
External gamma exposure rates	μR/h	27	11.6 - 13.8	4.5
<u>Building J-26 Area</u>				
Near-surface gamma	cpm	41	1568-4334	2,500
Beta-gamma dose rates	mrad/h	41	BKG-0.05	0.02
<u>East Burial Area</u>				
Near-surface gamma	cpm	89	1212-17878	2,500
Beta-gamma dose rates	mrad/h	89	BKG-0.04	0.02
External gamma exposure rates	μR/h	15	12.2-15.0	4.5
<u>Lagoon A</u>				
Near-surface gamma	cpm	64	1566-3436	2,500
Beta-gamma dose rates	mrad/h	64	BKG-0.05	0.02
External gamma exposure rates	μR/h	4	11.2-15.8	4.5

<sup>a</sup>Near-surface gamma measurements were made with a SPA-3 coupled with a PRS-1. Beta-gamma dose rates were measured with an HP-210 and PRS-1. Gamma exposure rates were measured with a PIC.

TABLE 5-5

## DUPONT CHAMBERS WORKS SITE: GAMMA SPECTROMETRY OF SOIL SAMPLES

Page 1 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)				
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235
Building 845 Area:						
Grid E	Grid N					
2761	4730	6-10	581.20 + 11.80	1.83 + .28	.96 + .55	---
2761	4730	10-14	427.60 + 9.68	1.07 + .20	1.51 + .56	---
2761	4730	14-18	164.80 + 5.34	.38 + .13	---	---
2761	4730	18-22	61.92 + 21.60	.33 + .22	.86 + .29	---
2761	4730	22-26	4.92 + 1.47	.28 + .23	.62 + .26	---
2761	4745	0-4	7398.00 + 32.70	4.06 + .77	---	---
2761	4745	6-10	720.10 + 9.50	.67 + .20	.66 + .23	---
2761	4745	42-45	321.80 + 7.14	.78 + .19	.46 + .26	---
2761	4745	46-50	358.40 + 11.14	.69 + .21	---	---
2761	4745	50-54	269.50 + 6.88	.36 + .17	.40 + .42	---
2761	4745	54-58	94.98 + 5.88	.37 + .29	---	---
2761	4745	58-62	152.40 + 9.25	.86 + .20	---	---
2761	4745	62-66	.63 + 1.54	.63 + .14	.94 + .28	---
2780	4771	6-10	10.61 + 6.69	---	---	---
2780	4771	10-14	25.61 + 5.12	---	---	---
2780	4771	14-18	159.30 + 10.19	.90 + .29	---	---
2780	4771	36-40	40.87 + 3.39	.92 + .15	.97 + .49	---
2782	4730	2-3	4355.00 + 68.70	5.12 + 2.17	---	---
2782	4730	3-7	561.40 + 11.12	1.99 + .27	---	---
2782	4730	7-11	58.06 + 2.93	.82 + .16	---	---
2782	4730	11-15	.80 + .20	.63 + .11	.58 + .22	.70 + .20
2782	4730	15-19	---	.53 + .13	.48 + .17	---
2782	4730	19-23	---	.42 + .14	.23 + .23	---
2782	4730	23-27	---	.46 + .25	---	---
F Corral Parking Area:						
Grid E	Grid N					
2507	4900	13-17	323.70 + 16.36	1.04 + .42	---	---
2507	4900	17-21	1333.00 + 41.20	8.58 + .93	---	---
2507	4900	21-25	1768.00 + 42.40	8.91 + .86	---	---
2507	4900	25-29	863.30 + 26.24	2.66 + .50	---	---
2507	4900	29-33	3531.00 + 25.90	2.11 + .62	---	---
2507	4900	54-56	1629.00 + 51.30	1.69 + .86	---	---
2507	4900	56-60	4378.00 + 25.29	1.16 + .48	---	---
2507	4900	60-64	4247.00 + 61.35	1.03 + .71	---	---
2507	4900	64-68	1734.00 + 44.40	.76 + .56	---	---
2507	4900	68-72	662.30 + 37.91	1.10 + .58	---	---
2507	4900	72-76	536.20 + 18.65	---	.79 + .26	---
2540	4850	6-10	12.59 + 2.21	.28 + .16	---	---
2540	4850	10-14	1.40 + .20	---	---	---
2540	4850	14-18	.90 + .20	---	---	1.70 + .20
						.12 + .05

TABLE 5-5  
(continued)

Page 2 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)					
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235	
F Corral Parking Area:							
Grid E	Grid N						
2540	4850	18-22	3.90 + 1.01	.15 + .05	---	.80 + .20	.05 + .04
2540	4850	22-26	6.93 + 1.46	.19 + .12	.11 + .12	---	---
2540	4850	26-30	281.20 + 11.70	2.72 + .33	.62 + .18	---	---
2540	4850	36-42	1066.00 + 12.11	6.51 + .51	.84 + .38	---	---
East Burial Area:							
Grid E	Grid N						
5518	3018	9-13	11210. + 39.40	27.84 + 2.28	---	---	---
5518	3018	13-17	20810. + 54.38	25.98 + 2.37	---	---	---
5518	3018	17-21	673.30 + 9.59	1.27 + .10	.69 + .34	---	---
5518	3018	21-25	185.40 + 4.94	1.04 + .08	1.05 + .24	---	---
5518	3018	25-29	296.90 + 6.59	3.93 + .32	---	---	---
5518	3018	29-33	375.40 + 8.33	.19 + .02	---	---	---
5518	3018	34-38	602.10 + 13.30	5.02 + .41	.64 + .53	---	---
5533	3018	6-10	18670. + 16.83	5.13 + .42	---	---	---
5533	3018	10-14	6029.00 + 30.04	16.02 + 1.31	---	---	---
5533	3018	14-18	710.20 + 9.75	5.45 + .45	---	---	---
5533	3018	18-23	577.40 + 11.39	3.73 + .31	---	---	---
5533	3018	22-26	745.80 + 9.92	1.87 + .15	.48 + .60	---	---
5533	3018	26-30	517.20 + 8.04	.63 + .22	---	---	---
5533	3018	30-32	530.10 + 11.10	1.24 + .39	.57 + .58	---	---
Building 845 (Interior)							
Grid No.	Core No.						
9	CB-1	6-9	2092.00 + 3.31	1.44 + .19	1.05 + .40	---	---
9	CB-1	9-13	21.82 + 2.54	.80 + .17	1.14 + .30	---	---
11	CB-13	15-19	3281.00 + 28.45	---	---	---	---
11	CB-13	19-24	1342.00 + 13.80	.43 + .28	---	---	---
11	CB-13	24-29	130.10 + 3.70	.90 + .29	---	---	---
11	CB-13	33-36	1351.00 + 18.00	1.40 + .46	---	---	---
11	CB-13	39-43	18.35 + 2.33	.70 + .14	.73 + .28	---	---
11	CB-13	43-47	1.35 + 1.49	1.30 + .20	1.28 + .25	---	---
11	CB-13	47-51	---	.90 + .45	---	---	---
11	CB-13	51-55	---	1.07 + .18	.97 + .29	---	---
11	CB-13	55-59	1.14 + .93	.65 + .14	---	---	---
11	CB-13	59-63	4.09 + 1.44	.43 + .12	.28 + .31	---	---
40	CB-2	0-6	149.80 + 8.21	1.13 + .20	---	---	---
40	CB-2	0-6	86.89 + 5.00	.33 + .16	.61 + .17	---	---
40	CB-2	12-16	166.40 + 8.10	1.09 + .38	.86 + .45	---	---
40	CB-2	12-16	36.24 + 1.32	.48 + .08	.62 + .14	---	---
40	CB-2	16-20	145.60 + 10.47	---	---	---	---

TABLE 5-5  
(continued)

Page 3 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)					
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235	
Building 845 (Interior):							
Grid No. Core No.							
40	CB-2	16-20	177.20 + 8.04	.48 + .31	.18 + .50	---	---
40	CB-2	20-24	106.20 + 8.36	.57 + .22	---	---	---
40	CB-2	20-24	49.37 + 4.26	.56 + .24	.13 + .45	---	---
40	CB-2	24-28	29.09 + 3.70	.85 + .37	---	---	---
40	CB-2	24-28	56.79 + 4.63	.94 + .28	.23 + .39	---	---
40	CB-2	28-32	43.66 + 6.30	---	---	---	---
40	CB-2	28-32	18.58 + 5.29	---	---	---	---
65	CB-3	0-3	1256.00 + 42.13	---	---	---	---
65	CB-3	3-7	484.70 + 19.50	---	---	---	---
65	CB-3	7-11	569.90 + 10.30	.35 + .19	---	---	---
65	CB-3	11-15	427.80 + 9.74	.22 + .32	.99 + .31	---	---
67	CB-4	23-27	45.87 + 3.64	.77 + .16	.62 + .25	---	---
67	CB-4	27-31	790.10 + 10.00	.66 + .44	---	---	---
71	CB-14	20-23	39.12 + 3.00	.74 + .13	.42 + .21	---	---
80	CB-5	21-30	72.63 + 7.24	.84 + .21	---	---	---
80	CB-5	30-39	10.09 + 2.87	---	---	---	---
106	CB-6	22-27	9.82 + 7.59	---	---	---	---
107	CB-26	6-10	43.14 + 7.67	1.01 + .25	---	---	---
107	CB-26	10-14	37.89 + 2.64	.51 + .20	.91 + .32	---	---
107	CB-26	14-18	42.07 + 3.13	.90 + .13	.37 + .22	---	---
107	CB-26	18-22	17.89 + 2.19	.92 + .14	.71 + .16	---	---
123	CB-15	8-12	2014.00 + 15.80	.78 + .32	1.20 + .41	---	---
123	CB-15	12-16	166.80 + 5.78	.98 + .18	1.22 + .31	---	---
123	CB-15	16-20	71.34 + 4.29	.36 + .16	.75 + .29	---	---
123	CB-15	20-24	12.52 + 2.29	1.10 + .20	1.15 + .39	---	---
123	CB-15	24-28	1.00 + .20	.99 + .18	10.44 + .25	1.00 + .20	.04 + 0.3
136	CB-12	7-12	38.16 + 3.63	.85 + .17	---	---	---
136	CB-12	12-18	56.41 + 3.92	1.64 + .28	.61 + .28	---	---
136	CB-12	18-21	3.30 + .30	---	---	3.40 + .30	.11 + .07
143	CB-7	6-10	991.20 + 11.71	1.42 + .21	---	---	---
143	CB-7	10-14	94.34 + 4.39	.63 + .15	1.16 + .25	---	---
143	CB-7	14-18	1.24 + 6.96	---	---	---	---
143	CB-7	18-22	1.53 + 1.06	.44 + .23	.56 + .29	---	---
143	CB-7	22-26	1.69 + 1.46	1.10 + .15	.54 + .31	---	---
173	CB-16	6-10	2785.00 + 48.20	4.94 + .82	---	---	---
173	CB-16	10-14	5839.00 + 76.74	4.27 + .90	---	---	---
173	CB-16	14-18	8057.00 + 3.62	.83 + .70	---	---	---
173	CB-16	18-22	6721.00 + 31.70	---	---	---	---
173	CB-16	33-37	2083.00 + 16.50	.80 + .35	---	---	---
173	CB-16	37-41	843.20 + 11.10	1.23 + .34	.95 + .33	---	---
173	CB-16	41-45	719.00 + 10.30	1.10 + .24	---	---	---



TABLE 5-5

(continued)

Page 4 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)				
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235
Building 845 (Interior):						
Grid No.	Core No.					
173	CB-16	45-49	7.76 + 3.90	.78 + .17	---	---
173	CB-16	49-53	35.37 + 3.43	.62 + .22	.93 + .32	---
192	CB-17	0-1	4699.00 + 68.90	---	---	---
192	CB-17	6-10	2517.00 + 18.63	.54 + .38	---	---
192	CB-17	10-14	1471.00 + 13.25	---	---	---
192	CB-17	14-18	151.90 + 5.36	.49 + .12	---	---
192	CB-17	18-22	197.10 + 5.91	.35 + .14	.34 + .27	---
194	CB-27	6-10	32.62 + 2.38	.32 + .13	---	---
197	CB-18	6-10	187.90 + 4.78	1.73 + .20	---	---
199	CB-11	6-10	8334.00 + 122.40	---	---	---
199	CB-11	10-14	3938.00 + 31.60	.31 + .77	---	---
199	CB-11	14-18	2168.00 + 58.40	---	---	---
199	CB-11	18-22	409.90 + 10.49	.48 + .30	---	---
199	CB-11	22-26	302.10 + 11.06	.72 + .36	---	---
199	CB-11	26-30	59.62 + 4.04	.58 + .18	.56 + .30	---
221	CB-24	0-4	2.30 + .30	---	---	2.40 + .30
221	CB-24	4-12	3.40 + .30	---	---	3.40 + .30
221	CB-24	4-12	6.89 + 1.75	.67 + .20	.71 + .20	---
221	CB-24	12-16	7.00 + 1.69	.58 + .13	---	---
221	CB-24	12-16	3.23 + 2.22	.55 + .16	.72 + .26	---
221	CB-24	16-20	6.23 + 3.47	---	---	---
221	CB-24	16-20	5.66 + 1.43	.76 + .16	.41 + .19	---
221	CB-24	20-24	3.61 + 3.03	.31 + .14	---	---
221	CB-24	20-24	3.00 + 1.88	.70 + .13	---	---
252	CB-8	6-8	268.90 + 15.50	---	---	---
252	CB-8	8-12	29.24 + 3.92	.26 + .18	---	---
252	CB-8	12-16	23.54 + 2.13	.38 + .15	.33 + .12	---
253	CB-19	35-36	1143.00 + 53.20	---	---	---
253	CB-19	36-40	446.60 + 9.70	.74 + .25	.63 + .20	---
253	CB-19	40-44	817.50 + 27.91	---	---	---
253	CB-19	44-48	1113.00 + 11.70	---	---	---
253	CB-19	48-52	12.83 + 1.72	.55 + .11	---	---
253	CB-19	52-56	---	.52 + .13	.32 + .22	---
253	CB-19	56-60	2.67 + 1.32	.42 + .12	.80 + .18	---
260	CB-20	7-10	25.03 + 4.17	.23 + .10	---	---
260	CB-20	10-14	3.32 + 1.23	.08 + .12	---	---
260	CB-20	14-18	---	.41 + .18	---	---
260	CB-20	18-22	---	.15 + .12	.43 + .13	---
260	CB-20	22-26	1.19 + 1.54	.47 + .16	.55 + .30	---
260	CB-20	26-30	---	.47 + .17	.86 + .27	---
271	CB-9					
277	CB-23	6-10	.70 + .10	.42 + .15	.59 + .19	.80 + .10
277	CB-23	10-14	---	.52 + .29	---	---
277	CB-23	14-18	---	.26 + .10	.59 + .19	---
277	CB-23	18-22	---	.49 + .13	.55 + .15	---

TABLE 5-5  
(continued)

Page 5 of 5

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)				
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235
Building 845 (Interior):						
<u>Grid No.</u>	<u>Core No.</u>					
277	CB-23	22-26	---	.67 + .13	.82 + .18	---
309	CB-21	6-10	17.29 + 2.14	.47 + .14	---	---
309	CB-21	10-14	3.16 + .97	.26 + .08	---	---
309	CB-21	14-18	10.61 + 4.58	.25 + .20	---	---
312	CB-10	6-7	305.50 + 1.96	3.30 + 1.96	---	---
312	CB-10	7-11	17.95 + 1.94	.61 + .10	.34 + .26	---
316	CB-22	6-10	44.95 + 6.20	1.01 + .25	---	---
316	CB-22	10-14	11.50 + 2.05	.60 + .12	.46 + .18	---
316	CB-22	14-18	---	.69 + .28	---	---
316	CB-22	18-22	5.82 + 1.17	.86 + .15	---	---
316	CB-22	22-26	4.64 + 2.07	1.53 + .23	.98 + .36	---
316	CB-22	26-30	---	.55 + .29	---	---
360	CB-25	5-9	3.56 + 1.19	.33 + .14	---	---

TABLE 5-6

## DUPONT CHAMBERS WORKS SITE: GAMMA SPECTROMETRY OF SEDIMENT SAMPLES

Sampling Location	Depth (Inches)	Radionuclide Concentrations (pCi/g +/- 2 Sigma)				
		Uranium-238	Radium-226	Thorium-232	Uranium-234	Uranium-235
Wooden Trough East of Building 845:						
Grid E	Grid N					
2710	4980	0-6	42.03 + 9.62	1.03 + .70	---	---
2730	4935	0-6	255.60 + 18.50	2.45 + .65	1.86 + 1.07	---
2755	4890	0-6	40.98 + 6.11	1.27 + .34	.47 + .64	---
2775	4840	0-6	49.13 + 6.74	.87 + .28	---	---
2775	4848	0-6	10.99 + 4.53	---	---	---
2795	4795	0-6	127.60 + 11.90	1.67 + .73	2.03 + .12	---
2800	4845	0-6	1.90 + .30	---	---	2.10 + .30
2820	4755	0-6	31.99 + 4.45	---	---	---
2845	4715	0-6	16.52 + 6.29	---	---	---
2760	4690	0-6	21.81 + 6.09	2.58 + .46	---	---
Central Drainage Ditch and Feeder Ditch:						
Grid E	Grid N					
2485	4700	0-6	1.20 + .20	---	---	1.40 + .20
2485	4700	0-6	1.00 + .20	---	---	1.20 + .20
2550	4770	0-6	1.70 + .20	---	---	1.60 + .20
2600	4990	0-6	4.10 + 2.85	.50 + .26	---	---
2630	4970	0-6	1.00 + .20	---	---	1.20 + .20
2650	4950	0-6	.90 + .20	.41 + .21	---	1.80 + .20
2670	4940	0-6	1.50 + .20	---	---	1.80 + .20
2700	4990	0-6	1.60 + .20	---	---	1.70 + .20
2740	5060	0-6	1.50 + .20	---	---	1.60 + .20
2805	4820	0-6	1.20 + .20	---	---	1.20 + .20
2840	5130	0-6	1.60 + .20	---	---	1.50 + .20
2900	5145	0-6	1.70 + .20	---	---	1.60 + .20
2950	5160	0-6	1.00 + .20	---	---	1.30 + .20
3050	5150	0-6	2.10 + .30	---	---	1.90 + .30
3220	5150	0-6	1.90 + .30	---	---	1.80 + .30
Lagoon A:						
Grid E	Grid N					
4850	5800	0-6	.20 + .10	---	---	.40 + .10
4980	5665	0-6	1.60 + .20	---	---	1.70 + .20

TABLE 5-7

DUPONT CHAMBERS WORKS SITE:  
RESULTS OF RADIOCHEMISTRY ANALYSIS OF WATER SAMPLES

Page 1 of 2

Sampling Location	Depth (inches)	Total Uranium (pCi/l $\pm$ 2 sigma)
Inside Building 845:	42	7507.51
Building 845 Area:		
<u>Grid E</u>	<u>Grid N</u>	
2534	4710	12.01
2600	4655	10.51
2624	4766	18.02
2650	4766	15.32
2650	4798	1.80
2650	4816	2.70
2667	4600	1.50
2678	4829	1.50
2681	4765	1.50
2717	4824	5.11
2747	4822	2.10
2761	4745	1,381.38
2768	4586	60.06
2768	4750	660.66
2779	4738	246.25
2780	4702	150.15
2790	4771	11,712.00
2799	4701	10.21
2799	4730	132.13
2799	4748	150.15
2816	4670	1,001.80
F Corral:		
<u>Grid E</u>	<u>Grid N</u>	
2444	5000	6.01
2450	4850	105.11
2450	4954	1,621.62
2492	4802	156.16
2500	4950	2,852.85
2500	4995	4.50
2507	4900	105,105.00
2540	4850	16,817.00
2565	4958	264.26
2580	4844	7.51
2603	4897	1.50

TABLE 5-7  
(continued)

Page 2 of 2

Sampling Location	Depth (inches)	Total Uranium (pCi/l $\pm$ 2 sigma)
Building J-26 Area:		
<u>Grid E</u> 1765	<u>Grid N</u> 2910	30
		14
East Burial Area:		
<u>Grid E</u> 5440	<u>Grid N</u> 3080	36
5580	3070	36
		24
		6
Lagoon A:	Surface	4

TABLE 5-8

DUPONT CHAMBERS WORKS SITE: PRE-REMEDIAL ACTION  
SUMMARY OF BUILDING 845 MEASUREMENT RESULTS

Page 1 of 2

Measurement Locations	Measurement Type <sup>a</sup>	Units <sup>a</sup>	No. of Readings Taken	Grid Block Average Range	Maximum Reading Observed
<u>First Level</u>					
Ceiling	Beta-Gamma Dose Rate	mrad/h	41	0-4.78	4.78
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	41	0-5568	5568
Floor	Beta-Gamma Dose Rate	mrad/h	1850	0-4.54	5.78
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	1850	0-6819	26544
East Wall	Beta-Gamma Dose Rate	mrad/h	120	0-10.34	10.34
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	120	2-4169	6229
West Wall	Beta-Gamma Dose Rate	mrad/h	175	0-8.69	16.30
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	175	8-2461	6110
North Wall	Beta-Gamma Dose Rate	mrad/h	105	0.04-3.29	3.65
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	105	17-483	890
South Wall	Beta-Gamma Dose Rate	mrad/h	65	0.08-1.51	1.57
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	65	29-102	161
Floor/Wall Intersection	Beta-Gamma Dose Rate	mrad/h	244	0-6.05	8.88
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	244	0-10621	18041
<u>Second Level</u>					
Ceiling	Beta-Gamma Dose Rate	mrad/h	38	0.02-4.87	4.87
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	38	8-3992	3992
Floor	Beta-Gamma Dose Rate	mrad/h	580	0-2.85	3.45
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	580	0-264	584
East Wall	Beta-Gamma Dose Rate	mrad/h	20	0.09-10.92	10.92
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	20	51-9068	9068
West Wall	Beta-Gamma Dose Rate	mrad/h	30	0.05-5.53	5.53
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	30	0-3712	3712
North Wall	Beta-Gamma Dose Rate	mrad/h	60	0.07-0.96	1.19
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	60	14-763	763
South Wall	Beta-Gamma Dose Rate	mrad/h	15	0.07-0.54	0.54
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	15	34-44	85
Floor/Wall Intersection	Beta-Gamma Dose Rate	mrad/h	118	0.01-2.16	2.77
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	118	0-1221	1516

TABLE 5-8  
(Continued)

Page 2 of 2

Measurement Locations	Measurement Type <sup>a</sup>	Units <sup>a</sup>	No. of Readings Taken	Grid Block Average Range	Maximum Reading Observed
Ceiling	Beta-Gamma Dose Rate	mrad/h	240	0.02-1.49	7.05
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	240	8-1347	1347
Floor	Beta-Gamma Dose Rate	mrad/h	120	0-1.40	2.38
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	120	0-1017	1281
East Wall	Beta-Gamma Dose Rate	mrad/h	24	0.09-2.84	2.84
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	24	53-3976	3076
West Wall	Beta-Gamma Dose Rate	mrad/h	180	0.25-2.37	2.37
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	180	42-1754	1754
North Wall	Beta-Gamma Dose Rate	mrad/h	36	0.08-0.61	0.65
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	36	37-653	653
South Wall	Beta-Gamma Dose Rate	mrad/h	10	0.08-0.08	0.10
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	10	49-69	110
Floor/Wall Intersection	Beta-Gamma Dose Rate	mrad/h	142	0-0.68	0.98
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	142	0-1930	2599
<u>Fourth Level</u>					
Ceiling	Beta-Gamma Dose Rate	mrad/h	39	0.05-4.34	4.34
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	39	76-2703	2703
Floor	Beta-Gamma Dose Rate	mrad/h	1095	0-1.00	1.76
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	1095	0-885	2561
East Wall	Beta-Gamma Dose Rate	mrad/h	33	0.03-1.26	1.26
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	33	36-2331	2331
West Wall	Beta-Gamma Dose Rate	mrad/h	33	0.08-1.46	1.46
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	33	0-3318	3318
North Wall	Beta-Gamma Dose Rate	mrad/h	20	0.07-0.27	0.27
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	20	47-572	572
South Wall	Beta-Gamma Dose Rate	mrad/h	9	0.34-3.39	3.39
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	9	40-3487	3487
Ceiling Heaters	Beta-Gamma Dose Rate	mrad/h	6	0.02-0.06	0.06
	Direct Alpha Activity	dpm/100 cm <sup>2</sup>	6	93-195	195

<sup>a</sup>For beta-gamma dose rate, the average criteria limit is 0.2 mrad/h and maximum criteria limit is 1.0 mrad/h. For direct alpha activity on surfaces, the average criteria limit is 5000 dpm/100 cm<sup>2</sup> and maximum criteria limit is 15,000 dpm/100 cm<sup>2</sup> (Ref. 5).

## 6.0 SIGNIFICANCE OF FINDINGS

The 1983 survey results show that five of the six areas surveyed are contaminated above current guidelines. The interior of Building 845 also is contaminated. These results are explained in greater detail in the following subsections.

### 6.1 FIELD SURVEY

The volumes of material contaminated above applicable remedial action criteria were based on the areal extent of the contamination plus the depth of contamination based on estimates and/or measurements. For soils, the extent of contamination was based on near-surface gamma measurements, surface soil samples, gamma logging of boreholes, and subsurface soil sampling. The depth of contaminated layers was based on actual measurements.

The extent of surface contamination in Building 845 was based on surface alpha and beta-gamma measurements, with beta-gamma measurements used as the primary survey method. The depth of contamination was estimated to be 1 inch, averaged over the contaminated area.

#### 6.1.1 Building 845 Area

Results from near-surface gamma radiation measurements were used to determine the extent of surface contamination. An area east of Building 845 was found to have readings greater than twice background, a finding in agreement with the ORNL survey (Ref. 1). The area that exhibited readings above criteria is shown in Figure 6-1.

Results from borehole gamma logs and subsurface soil samples were used to determine the depth of contamination. The major contaminant was found to be uranium-238, and subsurface contamination appears to be in layers to depths greater than 3 m (9 ft). However, the most






FIGURE 6-1 BUILDING 845 AREA AND WOODEN DRAINAGE TROUGH REQUIRING REMEDIAL ACTION

significant layer of contamination was located in the upper 1 m (3 ft) of soil. Gamma loggings in the soil below the depth of 1 m (3 ft) are approaching remedial action criteria.

Based on results from sediment samples, the wooden drainage trough located east of Building 845 would also require remedial action.

To comply with DOE guidelines, an estimated  $765 \text{ m}^3$  ( $1000 \text{ yd}^3$ ) of material would require removal from the area around Building 845, including the wooden drainage trough, during remedial action.

#### 6.1.2 Central Drainage Ditch

Results from near-surface gamma measurements made in the Central Drainage Ditch area indicated that an area located southwest of the drainage ditch had readings which were greater than twice background. Borehole gamma loggings in this area indicated areas of elevated readings which approach remedial action criteria limits. The elevated areas appear to be in layers which are at depths from 15 cm (6 in.) to greater than 2.5 m (8 ft).

Sediment samples taken from the Central Drainage Ditch and the Feeder ditch indicated below-criteria concentrations of uranium-238, -235, and -234.

During remedial action, the banks of the Central Drainage Ditch would require "hot spotting" to comply with guidelines. During hot spotting operations, approximately  $11 \text{ m}^3$  ( $15 \text{ yd}^3$ ) of material would require removal from the area.

#### 6.1.3 F Corral Parking Area

One near-surface gamma measurement exceeded twice background. All other measurements were within background levels. Borehole gamma loggings indicated contamination at depths greater than 3 m (9 ft), with the most significant layer of contamination located in the

upper 1 m (3 ft) of soil. Major readings below this depth approach remedial action guidelines. Soil samples show the contaminant is uranium-238, and the maximum uranium-238 concentration observed in subsurface soil samples was 4378 pCi/g.

Groundwater sample results from the F Corral parking area showed total uranium concentrations above the criteria limit. The maximum concentration observed for uranium-238 was 105,105 pCi/l. This sample was collected at a depth of 1 m (3 ft).

The area exhibiting measurements above guidelines is shown in Figure 6-2. During remedial action, an estimated 2700 m<sup>3</sup> (3500 yd<sup>3</sup>) would require removal to meet DOE guidelines.

#### 6.1.4 Building J-26 Area

All surface and subsurface measurements made in the Building J-26 area indicate the area is not contaminated. Water samples collected from the J-26 area were below criteria limits.

#### 6.1.5 East Burial Area

Near-surface gamma readings indicate three locations which exceeded twice background levels. All beta-gamma dose rates were below criteria limits.

Borehole gamma logging indicated contaminated layers of soil to depths greater than 2.7 m (8.5 ft). The most significant layer of contamination was located in the upper 1 m (3 ft). Elevated readings below this depth approach remedial action criteria. Higher count rates were observed in the boreholes drilled adjacent to the road. Areas which exhibited measurements above criteria are shown on Figure 6-3.




FIGURE 6-2 F CORRAL AREA REQUIRING REMEDIAL ACTION




FIGURE 6-3 EAST BURIAL AREA REQUIRING REMEDIAL ACTION.

Based on soil sample results, uranium-238 is the major contaminant, and the maximum concentration observed was 20,810 pCi/g. Elevated concentrations of radium-226 were observed in some soil samples (see Table 5-5).

During remedial action, an estimated 2800 m<sup>3</sup> (3700 yd<sup>3</sup>) of material would require removal from the East Burial Area to comply with criteria.

#### 6.1.6 Lagoon A

All surface measurements made in the Lagoon A area were within normal background. Borehole gamma count rates below 1.6 m (5.0 ft) indicated readings above background, but below the guideline.

#### 6.2 BUILDING 845 SURVEY

As shown in Table 5-8, alpha and beta-gamma contamination levels on some interior surfaces of all four levels of Building 845 were in excess of the surface contamination guidelines for release of property for unrestricted use (Ref. 4). Figures 6-4 through 6-11 show floor, wall, and ceiling areas which indicated surface readings above guidelines. The area shown inside the lunch room (Grid Block Numbers 210, 211, 212, 214, 220, 230, 242, 254, and 258) indicated beta-gamma measurements above criteria. This contamination is fixed and poses no health hazard for activities presently carried on in the lunch room.

Building 845 first floor corehole loggings, coupled with Shelby tube soil samples indicated areas of contamination beneath the building up to depths of 1.2 m (4 ft). These areas of contamination are illustrated in Figure 6-12.


Based on these results, an estimated 560 m<sup>3</sup> (760 yd<sup>3</sup>) of soil would require removal from beneath Building 845 to comply with criteria. In addition, remedial action would include the

decontamination of all areas inside Building 845 which exhibited surface measurements above remedial action criteria limits. Surface decontamination of the building would involve removal of 2.5 cm (1 in.) of material from approximately 2050 m<sup>2</sup> (22,000 ft<sup>2</sup>) of contaminated surface areas. This would result in approximately 50 m<sup>3</sup> (70 yd<sup>3</sup>) of material which would require removal. Total demolition of Building 845 would result in approximately 2300 m<sup>3</sup> (3000 yd<sup>3</sup>) of material.

## REFERENCES

1. Oak Ridge National Laboratory. Radiological Survey of the E. I. DuPont de Nemours and Company, Deepwater, New Jersey, DOE/EV-000E/8, prepared for the U.S. Department of Energy, Washington, D.C., 1978.
2. Letter, J. Curry to J. Eastman. "Draft Radiological Survey Report DuPont Chambers Works Site," August 24, 1984.
3. Glenn, R.D., et al. "Radiation Measurement Capability for Decontamination to Unrestricted Use," paper presented at the 1982 International Decommissioning Symposium, Seattle, WA, October, 1982.
4. T. E. Myrick, et al. State Background Radioactive Levels: Measurements Taken during 1975-1979, ORNL Report ORNL/TM-7343, November 1981.
5. Letter, E. L. Keller to R. L. Rudolph. "Comments on the Radiological Survey Report for the Former Middlesex Sampling Plant, Middlesex, New Jersey and the Draft Radiological Survey Report for the DuPont Chambers Works Plant, Deepwater, New Jersey," September 11, 1984.
6. U.S. Department of Energy, Order 5480.1A. "Environmental Protection, Safety, and Health Protection Program for DOE Operations," Washington, DC.





LEGEND: DEPTHS OF CONTAMINATION





FIGURE 6-12 AREAS OF CONTAMINATION BENEATH BUILDING 845



10	20	33	46	59	72	85	98	111	124	134	144	154	164	174	184	194	204	214	224	234	246	258	268	278	288	298	308	318	328	338	348	358	368	378
9	19	32	45	58	71	84	97	110	123	133	143	153	163	173	183	193	203	213	223	233	245	257	267	277	287	297	307	317	327	337	347	357	367	377
8	18	31	44	57	70	83	96	109	122	132	142	152	162	172	182	192	202	212	222	232	244	256	266	276	286	296	306	316	326	336	346	356	366	376
7	17	30	43	56	69	82	95	108	121	131	141	151	161	171	181	191	201	211	221	231	243	255	265	275	285	295	305	315	325	335	345	355	365	375
6	16	29	42	55	68	81	94	107	120	130	140	150	160	170	180	190	200	210	220	230	242	254	264	274	284	294	304	314	324	334	344	354	364	374
5	15	28	41	54	67	80	93	106	119	129	139	149	159	169	179	189	199	209	219	229	241	253	263	273	283	293	303	313	323	333	343	353	363	373
4	14	27	40	53	66	79	92	105	118	128	138	148	158	168	178	188	198	208	218	228	240	252	262	272	282	292	302	312	322	332	342	352	362	372
3	13	26	39	52	65	78	91	104	117	127	137	147	157	167	177	187	197	207	217	227	239	251	261	271	281	291	301	311	321	331	341	351	361	371
2	12	25	38	51	64	77	90	103	116	126	136	146	156	166	176	186	196	206	216	226	238	250	260	270	280	290	300	310	320	330	340	350	360	370
1	11	24	37	50	63	76	89	102	115	125	135	145	155	165	175	185	195	205	215	225	237	249	259	269	279	289	299	309	319	329	339	349	359	369


LEGEND



AREAS OF CEILING SURFACE CONTAMINATION

SCALE 0 6 12 ft  
0 1.8 3.6 m

FIGURE 6-11 BUILDING 845, FOURTH FLOOR CEILING; AREAS OF SURFACE CONTAMINATION



LEGEND

- CONTAMINATED FLOOR AND INTERIOR SURFACES OF EXTERIOR WALLS
- OUTLINE OF OLD FLOOR AREAS

SCALE 0 6 12 ft  
0 1.8 3.6 m

FIGURE 6-10 BUILDING 845, FOURTH FLOOR: AREAS OF SURFACE CONTAMINATION ON FLOOR, WALLS, AND FLOOR/WALL INTERSECTIONS



10	20	33	46	59	72	85	98	111	124	134	144	154	164	174	184	194	204	214	224	234	246	258	268	278	288	298	308	318	328	338	348	358	368	378	
9	19	32	45	58	71	84	97	110	123	133	143	153	163	173	183	193	203	213	223	233	245	257	267	277	287	297	307	317	327	337	347	357	367	377	
8	18	31	44	57	70	83	96	109	122	132	142	152	162	172	182	192	202	212	222	232	244	256	266	276	286	296	306	316	326	336	346	356	366	376	
7	17	30	43	56	69	82	95	108	121	131	141	151	161	171	181	191	201	211	221	231	243	255	265	275	285	295	305	315	325	335	345	355	365	375	
6	16	29	42	55	68	81	94	107	120	130	140	150	160	170	180	190	200	210	220	230	242	254	264	274	284	294	304	314	324	334	344	354	364	374	
5	15	28	41	54	67	80	93	106	119	129	139	149	159	169	179	189	199	209	219	229	241	253	263	273	283	293	303	313	323	333	343	353	363	373	
4	14	27	40	53	66	79	92	105	118	128	138	148	158	168	178	188	198	208	218	228	240	252	262	272	282	292	302	312	322	332	342	352	362	372	
3	13	26	39	52	65	78	91	104	117	127	137	147	157	167	177	187	197	207	217	227	239	251	261	271	281	291	301	311	321	331	341	351	361	371	
2	12	25	38	51	64	77	90	103	116	126	136	146	156	166	176	186	196	206	216	226	238	250	260	270	280	290	300	310	320	330	340	350	360	370	
1	11	24	37	50	63	76	89	102	115	125	135	145	155	165	175	185	195	205	215	225	237	249	259	269	279	289	299	309	319	329	339	349	359	369	379

LEGEND



AREAS OF CEILING SURFACE CONTAMINATION

SCALE 0 6 12 ft  
0 1.8 3.6 m

FIGURE 6-9 BUILDING 845, THIRD FLOOR CEILING: AREAS OF SURFACE CONTAMINATION



10	20	33	46	59	72	85	98	111	124	134	144	154	164	174	184	194	204	214	224	234	246	258	268	278	288	298	308	318	328	338	348	358	368	378
9	19	32	45	58	71	84	97	110	123	133	143	153	163	173	183	193	203	213	223	233	245	257	267	277	287	297	307	317	327	337	347	357	367	377
8	18	31	44	57	70	83	96	109	122	132	142	152	162	172	182	192	202	212	222	232	244	256	266	276	286	296	306	316	326	336	346	356	366	376
7	17	30	43	56	69	82	95	108	121	131	141	151	161	171	181	191	201	211	221	231	243	255	265	275	285	295	305	315	325	335	345	355	365	375
6	16	29	42	55	68	81	94	107	120	130	140	150	160	170	180	190	200	210	220	230	242	254	264	274	284	294	304	314	324	334	344	354	364	374
5	15	28	41	54	67	80	93	106	119	129	139	149	159	169	179	189	199	209	219	229	241	253	263	273	283	293	303	313	323	333	343	353	363	373
4	14	27	40	53	66	79	92	105	118	128	138	148	158	168	178	188	198	208	218	228	240	252	262	272	282	292	302	312	322	332	342	352	362	372
3	13	26	39	52	65	78	91	104	117	127	137	147	157	167	177	187	197	207	217	227	239	251	261	271	281	291	301	311	321	331	341	351	361	371
2	12	25	38	51	64	77	90	103	116	126	136	146	156	166	176	186	196	206	216	226	238	250	260	270	280	290	300	310	320	330	340	350	360	370
1	11	24	37	50	63	76	89	102	115	125	135	145	155	165	175	185	195	205	215	225	237	249	259	269	279	289	299	309	319	329	339	349	359	369

LEGEND



AREAS OF CEILING SURFACE CONTAMINATION

SCALE 0 6 12 ft  
0 1.8 3.6 m

FIGURE 6-7 BUILDING 845, SECOND FLOOR CEILING: AREAS OF SURFACE CONTAMINATION




FIGURE 6-6 BUILDING 845, SECOND FLOOR: AREAS OF CONTAMINATION ON FLOOR, WALLS, AND FLOOR/WALL INTERSECTIONS



10	20	33	46	59	72	85	98	111	124	134	144	154	164	174	184	194	204	214	224	234	246	258	268	278	288	298	308	318	328	338	348	358	368	378
9	19	32	45	58	71	84	97	110	123	133	143	153	163	173	183	193	203	213	223	233	245	257	267	277	287	297	307	317	327	337	347	357	367	377
8	18	31	44	57	70	83	96	109	122	132	142	152	162	172	182	192	202	212	222	232	244	256	266	276	286	296	306	316	326	336	346	356	366	376
7	17	30	43	56	69	82	95	108	121	131	141	151	161	171	181	191	201	211	221	231	243	255	265	275	285	295	305	315	325	335	345	355	365	375
6	16	29	42	55	68	81	94	107	120	130	140	150	160	170	180	190	200	210	220	230	242	254	264	274	284	294	304	314	324	334	344	354	364	374
5	15	28	41	54	67	80	93	106	119	129	139	149	159	169	179	189	199	209	219	229	241	253	263	273	283	293	303	313	323	333	343	353	363	373
4	14	27	40	53	66	79	92	105	118	128	138	148	158	168	178	188	198	208	218	228	240	252	262	272	282	292	302	312	322	332	342	352	362	372
3	13	26	39	52	65	78	91	104	117	127	137	147	157	167	177	187	197	207	217	227	239	251	261	271	281	291	301	311	321	331	341	351	361	371
2	12	25	38	51	64	77	90	103	116	126	136	146	156	166	176	186	196	206	216	226	238	250	260	270	280	290	300	310	320	330	340	350	360	370
1	11	24	37	50	63	76	89	102	115	125	135	145	155	165	175	185	195	205	215	225	237	249	259	269	279	289	299	309	319	329	339	349	359	369

LEGEND



AREAS OF CEILING SURFACE CONTAMINATION

SCALE 0 6 12 ft  
0 1.8 3.6 m

FIGURE 6-5 BUILDING 845, FIRST FLOOR CEILING: AREAS OF SURFACE CONTAMINATION