LINDE FUSRAP PROJECT NO. 07-3210.02, TASK NO. 2 - UTILITY REPLACEMENT PROJECT

SPECIFICATIONS:

0100 GENERAL CONDITIONS

1. CONSTRUCTION SHALL CONFORM TO THE BUILDING CODE OF NEW YORK STATE (BCNYS) 2010. COMPLY WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS.
2. SUBCONTRACTORS ARE RESPONSIBLE FOR SAFETY AND SHORING DURING CONSTRUCTION INCLUDING ANY TEMPORARY SHORING AT EXISTING STRUCTURES.
3. CONSTRUCTION MEANS, METHODS, AND CRAFTSMANSHIP ARE THE RESPONSIBILITY OF THE SUBCONTRACTORS.
4. CONTRACTOR SHALL SET ALL GRADES.
5. SUBCONTRACTORS SHALL VERIFY BY SITE VISIT/FIELD MEASUREMENT ALL EXISTING CONDITIONS PRIOR TO COMMENCEMENT OF CONSTRUCTION. NOTIFY THIS ENGINEER OF ANY CONDITIONS NOT MATCHING THESE DRAWINGS.
6. EXISTING ROUNDED TUNNEL SECTION IS ASSUMED TO HAVE 6'-8"X6'-8" CLEAR DIMENSIONS, TOP OF BOTTOM SLAB ELEVATION OF 593'-2 1/4", THICKNESS OF 8" FOR FLOOR/WALLS, AND THICKNESS OF 5" AT TUNNEL TOP. ALL INFORMATION SHALL BE VERIFIED IN FIELD.
7. EXISTING TUNNEL SECTION NEAR JUNCTION BOX 8A IS ASSUMED TO HAVE 8'x8' CLEAR DIMENSIONS, TOP OF BOTTOM SLAB ELEVATION OF 593'-6 3/4", AND THICKNESS OF 10" FOR FLOOR/WALLS/ROOF. ALL INFORMATION SHALL BE VERIFIED IN FIELD.
8. EXACT DIMENSIONS OF TUNNEL CUT OUT MAY VARY FROM THAT SHOWN.
9. SUBCONTRACTORS TO PATCH, MATCH, AND RESTORE TO EXISTING CONDITION ALL AREAS AFFECTED BY MODIFICATION CONSTRUCTION.
10. SUBCONTRACTORS TO PROVIDE ADEQUATE MEANS TO PROTECT EXISTING AREAS FROM DUST AND FOREIGN MATERIAL DURING MODIFICATION CONSTRUCTION.
11. SUBCONTRACTORS TO PROVIDE ADEQUATE PROVISIONS TO ENSURE THAT AREAS REMAIN WEATHER TIGHT DURING MODIFICATION CONSTRUCTION.
12. SUBCONTRACTORS SHALL BE RESPONSIBLE FOR COMPLIANCE WITH ALL INFORMATION ON DRAWINGS.
13. ALL SUBMITTALS, INCLUDING SHOP DRAWINGS, MUST BE STAMPED BY THE CONTRACTOR. BY STAMPING THE SUBMITTAL, CONTRACTOR ACKNOWLEDGES HAVING REVIEWED THE SUBMITTAL.
14. SHOP DRAWING SUBMITTALS SHALL INCLUDE A MINIMUM OF ONE REPRODUCIBLE AND ONE PRINT AND SHALL BE SUBMITTED TO THIS ENGINEER PRIOR TO FABRICATION.
15. SUBSTITUTIONS WILL BE MADE ON AN "OR EQUIVALENT" BASIS AND ARE TO BE APPROVED BY THIS ENGINEER.
16. IT IS THE RESPONSIBILITY OF THE SUBCONTRACTORS TO VERIFY/CONFIRM THE LOCATION OF ALL EQUIPMENT, ANCHORAGES, OPENINGS (INCLUDING SIZE AND CLEARANCES), DRAINS, PIPING, CONDUIT, ETC., AND REPORT ANY DISCREPANCY TO THIS ENGINEER PRIOR TO COMMENCEMENT OF CONSTRUCTION.
17. DESIGN OF ELECTRIC, PLUMBING, PIPING, HEATING/VENTILATION/AIR CONDITIONING, AND SEWER/SEPTIC SYSTEM SHALL BE BY OTHERS. GENERAL CONTRACTOR WILL INSURE THAT THE FACILITY IS IN COMPLIANCE WITH ALL APPLICABLE CODES, THE NEW YORK STATE BUILDING CODE, AND THE NEW YORK STATE ENERGY CONSERVATION CONSTRUCTION CODE.
18. VIF = VERIFY IN FIELD
19. UNO = UNLESS NOTED OTHERWISE
20. ALL ELEVATIONS SHOWN ON DRAWINGS ARE APPROXIMATE. GENERAL CONTRACTOR SHALL RETAIN SURVEYOR TO VERIFY/CONFIRM ALL ELEVATIONS NECESSARY FOR PROJECT COMPLETION.

0200 SITE WORK

1. PRIOR TO ANY EXCAVATION IN NEW YORK STATE, CALL DIG SAFELY NEW YORK AT 1-800-962-7962.
2. PRIOR TO CONSTRUCTION, GENERAL CONTRACTOR SHALL VERIFY ASSUMED ALLOWABLE SOIL BEARING PRESSURE OF 2000 PSF. NOTIFY THIS ENGINEER IN WRITING IF SOIL BEARING CAPACITY IS LESS THAN THAT STATED.
3. FOUNDATION SHALL BEAR ON FIRM, LEVEL, AND UNDISTURBED NATURAL SOIL OR COMPACTED SELECT STRUCTURAL FILL. REMOVE ALL TOPSOIL, ORGANIC SUBSOIL, FILL SOIL AND DEBRIS FROM LOAD BEARING AREAS. BEARING GRADE SHALL BE FREE OF FROST AND LOOSE MATERIAL. SELECT STRUCTURAL FILL, IF USED, SHALL BE PLACED AND COMPACTED IN LOOSE LIFTS NOT TO EXCEED 9" IN THICKNESS AND COMPACTED TO 95% OF MODIFIED PROCTOR MAXIMUM DENSITY (ASTM D1557.)
4. FOUNDATION SUBGRADE (BEARING GRADE) SHALL BE SLOPED TO DRAIN AND PROVIDED WITH A SUMP (OUTSIDE OF WORK AREA FOOTPRINT) TO KEEP ALL EXCAVATIONS FREE OF STANDING WATER DURING CONSTRUCTION.
5. ALL FOUNDATION EXCAVATIONS ARE TO BE FINISHED BY HAND. COMPACT FOOTING SUBGRADES TO 95% OF MODIFIED PROCTOR MAXIMUM DENSITY (ASTM D1557) WITHIN 2% OF OPTIMUM MOISTURE CONTENT.
6. SOIL AT SITE SHALL BE CLASSIFIED BY AN OSHA COMPETENT PERSON PRIOR TO AND DURING EXCAVATION TO DETERMINE EXCAVATION GEOMETRY AND THE NEED FOR EXCAVATION BRACING.
7. BOTTOM OF FOUNDATION ELEVATION SHALL MATCH ADJACENT EXISTING FOUNDATION UNO.
8. COMMON FILL IS DEFINED AS SOIL MATERIALS WITH THE EXCEPTION OF THOSE CLASSIFIED BY UCSC AS CH, MH, OH AND OL.
9. STRUCTURAL FILL IS DEFINED AS SOIL MATERIALS WITH THE EXCEPTION OF THOSE CLASSIFIED BY UCSC AS CH, MH, OH, OL, ML AND CL-ML.
10. SELECT STRUCTURAL FILL IS DEFINED AS SOIL MATERIALS MEETING THE REQUIREMENTS OF NYSDOT ITEM 304-2.02, TYPE 4 AND THE REQUIREMENTS OF ASTM D-248 WELL-GRADED.
11. BACKFILL SHALL BE STRUCTURAL FILL OR GRADED #2 GRAVEL.
12. STRUCTURAL BACKFILL SHALL BE PLACED IN LOOSE LIFTS OF 9" MAXIMUM. EACH LIFT SHALL BE COMPACTED TO 95% OF MODIFIED PROCTOR MAXIMUM DENSITY (ASTM D1557.)
13. DO NOT PLACE ANY FILL IN WATER, OVER SATURATED GROUND, OR OVER FROZEN SUBGRADE.
14. BACKFILL AGAINST FOUNDATION WALLS BELOW GRADE SO THAT THE DIFFERENCE IN FILL LEVEL ON OPPOSITE SIDES OF JUNCTION BOXES, TUNNELS, ECT DO NOT EXCEED 1'-0" AT ANY TIME. BACKFILL MAY BE PLACED PRIOR TO TOP SLAB PLACEMENT UNO.
15. SOIL REMOVAL AGAINST CONCRETE WALLS SHALL OCCUR SO THAT THE DIFFERENCE IN FILL LEVEL ON OPPOSITE SIDES OF JUNCTION BOXES, TUNNELS, ECT DO NOT EXCEED 1'-0" AT ANY TIME.

0300 CONCRETE

1. CONCRETE CONSTRUCTION/DESIGN SHALL CONFORM TO ACI 318 (INCLUDING CHAPTER 21) AND ACI 301 LATEST EDITIONS.
2. FOR HOT OR COLD WEATHER CONCRETE REQUIREMENTS REFER TO ACI 305 OR ACI 306 LATEST EDITIONS.
3. DO NOT PLACE ANY CONCRETE IN WATER, OVER SATURATED GROUND, OR OVER FROZEN SUBGRADE.
4. ALL CONCRETE SHALL BE NORMAL WEIGHT WITH A NOMINAL AIR DRY DENSITY OF 145 PCF.
5. IF WATER IS ADDED AT THE PROJECT SITE, COMPLY WITH ALL ACI REQUIREMENTS/GUIDELINES. ONLY ONE SUCH ADDITION OF WATER SHALL BE MADE PROVIDED SUCH ADDITION DOES NOT INCREASE THE WATER - CEMENT RATIO BEYOND THE MAXIMUM STATED HEREIN.
6. MINIMUM COMPRESSIVE STRENGTH AT 28 DAYS IS 3500 PSI UNO.
7. SLUMP SHALL BE 3" +/- 1" (WITHOUT HIGH RANGE WATER REDUCER, IF USED.)
8. MAXIMUM WATER/CEMENT RATIO SHALL BE 0.45.
9. PORTLAND CEMENT SHALL COMPLY WITH ASTM C 150 TYPE I OR II.
10. COURSE AGGREGATE SHALL BE #1 AND #2 STONE.
11. NORMAL WEIGHT AGGREGATE SHALL COMPLY WITH ASTM C 33, UNIFORMLY GRADED, 3/4" MAXIMUM AGGREGATE SIZE.
12. ENTRAINED AIR SHALL BE 5% +/- 1% FOR FOOTINGS, WALLS, AND PIERS.
13. FLOWABLE FILL SHALL BE A MIXTURE OF PORTLAND CEMENT, FLYASH, FINE AGGREGATE, WATER, AND POSSIBLY ADMIXTURES WITH A 28 DAY COMPRESSIVE STRENGTH OF 50 TO 150 PSI. SLUMP SHALL BE 8" TO 10" AND THE MIX MUST REMAIN EXCAVATABLE BY STANDARD BACKHOE EQUIPMENT WITHOUT THE USE OF CHIPPING/BREAKING EQUIPMENT.
14. ALL KEYS INDICATED ON DRAWINGS SHALL BE 1-1/2" X 3-1/2" BEVELED.
15. ALL WATERSTOPS INDICATED SHALL BE "GREENSTREAK PVC STYLE #783, 3/8" X 6", SERRATED OR APPROVED EQUIVALENT.
16. SLABS SHALL BE CAST SO THAT THE SLAB THICKNESS IS AT NO POINT LESS THAN THAT INDICATED ON THE DRAWINGS.
17. REINFORCING SHALL CONFORM TO ASTM A615, GRADE 60. LAP 48 BAR DIAMETERS MIN. CORNER BARS SHALL MATCH HORIZONTAL WALL/FOOTING REINFORCING. DO NOT WELD.
18. COVER FOR REINFORCEMENT SHALL BE:

FOOTINGS	3" BOTTOM
	2" SIDE AND TOP
WALLS	2" SIDE AND TOP
PIERS	2" TOP
	1-1/2" TO TIES
COLUMNS	2" TOP
	1-1/2" TO TIES

19. REINFORCEMENT SHALL BE CONTINUOUS THROUGH ALL CONSTRUCTION JOINTS UNO.
20. ALL HOOKS SHALL BE ACI STANDARD UNO.
21. PROVIDE MINIMUM (2) #5 BARS EACH SIDE OF ALL OPENINGS IN FOUNDATION WALLS. BARS SHALL EXTEND A MINIMUM OF 24" BEYOND THE CORNERS OF OPENINGS.
22. FABRICATION, PLACING AND SUPPORTING REINFORCEMENT SHALL COMPLY WITH ALL RECOMMENDATIONS IN CRSI "MANUAL OF STANDARD PRACTICE."
23. BAR SUPPORTS SHALL BE GALVANIZED OR STAINLESS STEEL. BAR SUPPORTS IN CONTACT WITH EXPOSED SURFACES SHALL BE GALVANIZED AND PLASTIC TIPPED.
24. MINIMUM ELAPSED TIME BETWEEN ADJACENT CONCRETE PLACEMENTS SHALL BE 48 HOURS.
25. WHERE NEW CONCRETE ABUTS EXISTING CONCRETE, ROUGHEN EXISTING SURFACE AND BRUSH CLEAN ALL FOREIGN MATERIAL PRIOR TO COATING WITH BONDING AGENT SIKADUR 32 POURABLE EPOXY.
26. NOTIFY ENGINEER OF RECORD A MINIMUM OF 48 HOURS PRIOR TO CONCRETE POUR SO THAT ARRANGEMENTS CAN BE MADE FOR CONCRETE TESTING, OBSERVATION, AND CASTING OF CYLINDERS.
27. CYLINDERS FOR STRENGTH TESTS SHALL BE MOLDED AND LABORATORY CURED PER ASTM C31 AND TESTED IN ACCORDANCE WITH ASTM C39. PROVIDE 4 CYLINDERS FOR EACH 50 CUBIC YARDS OF CONCRETE PLACED.

0500 METALS

1. DETAIL, FABRICATE, AND ERECT STRUCTURAL STEEL IN CONFORMANCE WITH AISC SPECIFICATIONS AND CODES, LATEST EDITIONS.
2. STEEL PIPE SHALL COMPLY WITH ASTM A53 GRADE B WITH A MINIMUM FY=35 KSI.
3. ALL OTHER STRUCTURAL STEEL SHALL COMPLY WITH ASTM A36 OR A992.
4. WELDING SHALL CONFORM TO AWS D1.1 WITH A MINIMUM 3/16" FILLET WELD UNO. ELECTRODES SHALL BE E70XX. ALL WELDS SHALL BE VISUALLY INSPECTED. ALL SHOP WELDS SHALL COMPLY WITH AISC MINIMUMS AND MAXIMUMS.
5. STRUCTURAL STEEL SHALL BE PREPARED BY POWER TOOL PRIOR TO BEING PAINTED WITH RUST RESISTANT, TYPE ONE PAINT. AFTER COMPLETING ERECTION, TOUCH UP ALL AREAS WHERE PAINT IS MISSING, INCLUDING FIELD WELDS.
6. FLOOR AND ROOF DECK SHALL BE MANUFACTURED AND ERECTED IN ACCORDANCE WITH STEEL DECK INSTITUTE SPECIFICATIONS. ATTACH DECK TO SUPPORTING MEMBERS WITH 5/8" DIAMETER PUDDLE WELDS AT 12" OC UNO. (FOR STEEL LESS THAN 1/4", ATTACH WITH #12 SELF-DRILLING FASTENERS AT SPACING ADEQUATE TO PROVIDE DIAPHRAGM STRENGTH EQUAL TO 5/8" PUDDLE WELDS.) FASTEN SIDELAPS AT 30" MAXIMUM ON CENTER.
7. FABRICATE METAL DECKING FROM STEEL WHICH CONFORMS TO ASTM A446, GRADE A, HAVING A MINIMUM YIELD STRENGTH OF 33,000 PSI.
8. METAL DECK SHALL CONFORM TO G90 REQUIREMENTS.
9. PROVIDE CONTINUOUS SHEET METAL CLOSURES AT ALL SLAB OPENINGS AND SLAB EDGES AND CONTINUOUS DECK CLOSURES AT ALL DECK ENDS. PROVIDE SUPPLEMENTARY FRAMING AT OPENINGS AS REQUIRED FOR SUPPORT OF METAL DECK. PROVIDE STRAP ANCHORS AS NECESSARY TO CONTROL CANTILEVER DEFLECTIONS AT FLOOR SLAB EDGES.
10. DO NOT HANG LOADS EXCEEDING 50 LBS. FROM ANY METAL DECKING. HANG ALL DUCTWORK, PIPING, ETC DIRECTLY FROM STRUCTURAL STEEL WORK OR SUPPLEMENTARY MEMBERS OR ANCHORS EMBEDDED IN THE CONCRETE. SUBMIT ALL HANGING LOAD DETAILS FOR REVIEW.

0900 FINISHES

1. SUBCONTRACTOR SHALL COORDINATE REQUIREMENTS WITH OWNER UNO.

NOTES:
1. FOR DRAWING LIST, REFER TO DWG-10060-001.

STATE OF NEW YORK · ROBIN MARIE CLOSS · 084429-1 · LICENSED PROFESSIONAL ENGINEER

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES
MACHINED SURFACES FLATNESS .003 FINISH
TOLERANCES FRACTION: 1/8 2 PLACE: ±.01 3 PLACE: ±.005 ANGLE: 0°±30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
www.rjrpc.com PH. (716)-592-3980 FAX. (716)-592-4216

DRAFTER: MEK
CHECKER: XXX
ENGINEER: RMC

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
SPECIFICATIONS

PROJECT #: 10058

DWG NO. DWG-10058-000
DWG SCALE: NO SCALE
REV: 1
DWG SIZE: D

200.1e
Linde_01.04_0050_a



NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES
MACHINED SURFACES FLATNESS .003 FINISH
TOLERANCES FRACTION: 1/8 # PLACE: ±.005

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
www.rjrpc.com PH. (716)-592-3980 FAX (716)-592-4216

DRAFTER: MEK
CHECKER: XXX
ENGINEER: RMC

LINDE FUSRAP UTILITY REPLACEMENT PROJECT LOCATION PLAN

DWG NO. DWG-10058-002
DWG SCALE: 1/32" = 1'-0" REV: 1
PROJECT #: 10058
DWG SIZE: D

STATE OF NEW YORK · ROBIN MARIE CLOSS · 084429-1 · LICENSED PROFESSIONAL ENGINEER



B2 CAST IN PLACE JUNCTION BOX 9A - PLAN

SCALE: 3/8" = 1'-0"



NOTE:
FIELD TO VERIFY ACTUAL EXISTING TUNNEL SECTION LOCATION. LOCATION OF SAW CUT MAY VARY.

D6 BOTTOM OF EXISTING TUNNEL DEMO PLAN

SCALE: 3/8" = 1'-0"

B6 DEMO SECTION

SCALE: 3/8" = 1'-0"

NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.
2. EVERY THIRD HORIZONTAL/VERTICAL WALL (NOT SLAB/COLUMN/BEAM) REBAR MAY BE CUT FOR PIPING/CONDUIT INSTALLATION.
3. DRAWING IS NOT TO SCALE. THIS WILL BE ADDRESSED IN FUTURE SUBMITTALS.

STATE OF NEW YORK
ROBIN MARIE CLOSS
084429-1
LICENSED PROFESSIONAL ENGINEER

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS IN INCHES
MACHINED SURFACES
FLATNESS .003
FINISH
TOLERANCES
FRACTION: 1/8 2 PLACE: ±.01
3 PLACE: ±.005 ANGLE: 0°±30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
www.rjrpc.com PH. (716)-592-3980 FAX. (716)-592-4216

DRAFTER: MEK
CHECKER: XXX
ENGINEER: RMC

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
JUNCTION BOX 9A
PLAN AND SECTIONS

PROJECT #: 10058

DWG NO. DWG-10058-003
DWG SCALE: SEE DRAWING
REV: 1
DWG SIZE: D



D2 SECTION
DWG-10058-003
SCALE: 3/8" = 1'-0"

NOTE:
SEE SECTION D5 ON DWG-10058-004
FOR REMAINING INFORMATION



D5 SECTION
DWG-10058-003
SCALE: 3/8" = 1'-0"



NOTE:
SEE SECTION D5 ON DWG-10058-004
FOR REMAINING INFORMATION

D7 SECTION
DWG-10058-003
SCALE: 3/8" = 1'-0"



B2 SECTION
DWG-10058-003
SCALE: 3/8" = 1'-0"



B4 DETAIL
DWG-10058-003
SCALE: 1" = 1'-0"

NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.
2. EVERY THIRD HORIZONTAL/VERTICAL WALL (NOT SLAB/COLUMN/BEAM) REBAR MAY BE CUT FOR PIPING/CONDUIT INSTALLATION.

STATE OF NEW YORK · ROBIN MARIE GLOSS · 084429-1 · LICENSED PROFESSIONAL ENGINEER

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES
MACHINED SURFACES FLATNESS .003 FINISH
TOLERANCES FRACTION: 1/8 2 PLACE: ±.01 3 PLACE: ±.005 ANGLE: 0°±30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141–0344
www.rjrpc.com PH. (716)–592–3980 FAX. (716)–592–4216

DRAFTER: MEK
CHECKER: XXX
ENGINEER: RMC

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
JUNCTION BOX 9A
SECTIONS AND DETAILS

PROJECT #: 10058

DWG NO. DWG-10058-004
DWG SCALE: SEE DRAWING
REV: 1
DWG SIZE: D



B3 CAST IN PLACE JUNCTION BOX 7A - PLAN
SCALE: 3/8" = 1'-0"



D6 SECTION
SCALE: 3/8" = 1'-0"



A3 CONCRETE BEAM
SCALE: 1" = 1'-0"



A5 CONCRETE COLUMN
SCALE: 1" = 1'-0"

A7 CONCRETE COLUMNS
SCALE: 1" = 1'-0"

NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.
2. EVERY THIRD HORIZONTAL/VERTICAL WALL (NOT SLAB/COLUMN/BEAM) REBAR MAY BE CUT FOR PIPING/CONDUIT INSTALLATION.

STATE OF NEW YORK · ROBIN MARIE CLOSS · 084429-1 · LICENSED PROFESSIONAL ENGINEER

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES
MACHINED SURFACES FLATNESS .003 FINISH
TOLERANCES FRACTION: 1/8 2 PLACE: ±.01 3 PLACE: ±.005 ANGLE: 0°±30'

DRAFTER: MEK
CHECKER: XXX
ENGINEER: RMC
PROJECT #: 10058

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
PH. (716)-592-3980 FAX. (716)-592-4216
www.rjrpc.com

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
JUNCTION BOX 7A
PLAN, SECTIONS AND DETAILS

DWG NO. DWG-10058-005
DWG SCALE: SEE DRAWING
REV: 1
DWG SIZE: D



B3 CAST IN PLACE JUNCTION BOX 8A - PLAN

SCALE: 3/8" = 1'-0"



NOTE:
FIELD TO VERIFY ACTUAL EXISTING TUNNEL SECTION LOCATION. LOCATION OF SAW CUT MAY VARY.

D7 BOTTOM OF EXISTING TUNNEL DEMO PLAN

SCALE: 3/8" = 1'-0"



B7 DEMO SECTION

SCALE: 3/8" = 1'-0"

NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.
2. EVERY THIRD HORIZONTAL/VERTICAL WALL (NOT SLAB/COLUMN/BEAM) REBAR MAY BE CUT FOR PIPING/CONDUIT INSTALLATION.
3. DRAWING IS NOT TO SCALE. THIS WILL BE ADDRESSED IN FUTURE SUBMISSIONS.

STATE OF NEW YORK · ROBIN MARIE CLOSS · 084429-1 · LICENSED PROFESSIONAL ENGINEER

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES
MACHINED SURFACES FLATNESS .003 FINISH
TOLERANCES FRACTION: 1/8 2 PLACE: ±.01 3 PLACE: ±.005 ANGLE: 0°±30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
www.rjrpc.com PH. (716)-592-3980 FAX. (716)-592-4216

DRAFTER: MEK
CHECKER: XXX
ENGINEER: RMC
PROJECT #: 10058

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
JUNCTION BOX 8A
PLAN AND SECTIONS

DWG NO. DWG-10058-006
DWG SCALE: SEE DRAWING
REV: 1
DWG SIZE: D



D2 SECTION
DWG-10058-006
SCALE: 3/8" = 1'-0"



D6 CONCRETE BEAM
SCALE: 1" = 1'-0"



B2 SECTION
DWG-10058-006
SCALE: 3/8" = 1'-0"



B5 CONCRETE COLUMN
SCALE: 1" = 1'-0"



B6 CONCRETE COLUMN
SCALE: 1" = 1'-0"

NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.
2. EVERY THIRD HORIZONTAL/VERTICAL WALL (NOT SLAB/COLUMN/BEAM) REBAR MAY BE CUT FOR PIPING/CONDUIT INSTALLATION.

STATE OF NEW YORK · ROBIN MARIE CLOSS · 084429-1 · LICENSED PROFESSIONAL ENGINEER

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS IN INCHES
MACHINED SURFACES
FLATNESS .003
FINISH
TOLERANCES
FRACTION: 1/8 2 PLACE: ±.01
3 PLACE: ±.005 ANGLE: 0°±30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
PH. (716)-592-3980 FAX. (716)-592-4216
www.rjrpc.com

DRAFTER: MEK
CHECKER: XXX
ENGINEER: RMC
PROJECT #: 10058

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
JUNCTION BOX 8A
SECTIONS AND DETAILS

DWG NO. DWG-10058-007
DWG SCALE: SEE DRAWING
REV: 1
DWG SIZE: D



PLAN
SCALE: 1/4" = 1'-0"





C6 SECTION
SCALE: 1/4" = 1'-0"

NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.

STATE OF NEW YORK
ROBIN MARIE CLOSS
964429-1
LICENSED PROFESSIONAL ENGINEER
10-3-11

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP
2	VAULT EXTENSION REDESIGN	10/03/11	ELK

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS IN INCHES
MACHINED SURFACES
FLATNESS .003
FINISH 125
TOLERANCES
FRACTION: 1/8 2 PLACE: ±.01
3 PLACE: ±.005 ANGLE: 0°;30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
www.rjrpc.com PH. (716)-592-3980 FAX. (716)-592-4216

DRAFTER: JN
CHECKER: XXX
ENGINEER: RMC

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
EXISTING CABLE VAULT DEMOLITION

PROJECT #: 10058

DWG NO. DWG-10058-008
DWG SCALE: SEE DRAWING
REV: 2
DWG SIZE: D



PLAN

SCALE: 1/4" = 1'-0"

NOTE: DOES NOT SUPPORT H20 LOADING



D5 SECTION

SCALE: 3/8" = 1'-0"



B2 SECTION

SCALE: 1/4" = 1'-0"



NOTE:
SEE SECTION D5 ON DWG-10058-009 FOR REMAINING INFORMATION

B4 SECTION

SCALE: 1/4" = 1'-0"

NOTES:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.
2. * DENOTES COORDINATE WITH ELECTRICAL. DO NOT CUT REBAR FOR PIPING / CONDUIT INSTALLATION.

STATE OF NEW YORK · ROBIN MARIE CLOSS · 084429-1 · LICENSED PROFESSIONAL ENGINEER

10-3-11

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP
2	VAULT EXTENSION REDESIGN	10/03/11	ELK

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS IN INCHES
MACHINED SURFACES FLATNESS .003 125 FINISH
TOLERANCES
FRACTION: 1/8 2 PLACE: ±.01
3 PLACE: ±.005 ANGLE: 0°±30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
www.rjrpc.com PH. (716)-592-3980 FAX. (716)-592-4216

DRAFTER: JN
CHECKER: XXX
ENGINEER: RMC

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
CABLE VAULT EXTENSION
PLAN AND SECTIONS

DWG NO. DWG-10058-009
DWG SCALE: SEE DRAWING REV: 2
PROJECT #: 10058
DWG SIZE: D



D1 DETAIL
SCALE: 3" = 1'-0"



D3 SECTION
SCALE: 3" = 1'-0"



PLAN
SCALE: 1/2" = 1'-0"

NOTE: DOES NOT SUPPORT H20 LOADING



A1 DETAIL
SCALE: 1-1/2" = 1'-0"



A4 DETAIL
SCALE: 1-1/2" = 1'-0"

NOTE:

1. FOR DRAWING LIST, REFER TO DWG-10060-001.

STATE OF NEW YORK
ROBIN MARIE CLOSS
084429-1
LICENSED PROFESSIONAL ENGINEER
10-3-11

REVISIONS			
REV	DESCRIPTION	DATE	INIT
0	FOR REVIEW	06/02/11	MEK
1	ISSUE FOR CONSTRUCTION	08/31/11	TPP
2	VAULT EXTENSION REDESIGN	10/03/11	ELK

UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS IN INCHES

MACHINED SURFACES
FLATNESS .003 125
FINISH

TOLERANCES
FRACTION: 1/8 .2 PLACE: ±.01
3 PLACE: ±.005 ANGLE: 0°±30'

MOLLENBERG-BETZ INC
300 SCOTT STREET
BUFFALO, NY 14204

RJR ENGINEERING, P.C.
PROFESSIONAL ENGINEERS
23 Mechanic Street – P.O. Box 344
Springville, New York 14141-0344
www.rjrpc.com PH. (716)-592-3980 FAX. (716)-592-4216

DRAFTER: JN
CHECKER: XXX
ENGINEER: RMC

LINDE FUSRAP UTILITY REPLACEMENT PROJECT
CABLE VAULT EXTENSION DETAILS

DWG NO. DWG-10058-011
DWG SCALE: SEE DRAWING
REV: 2
DWG SIZE: D

PROJECT #: 10058